



Date	Rev.	Description

REMARK: RoHS COMPLIANT






RECOMMENDED
CABLE STRIPPING DIM'S



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 3. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 4. BRASS JIS H 3250, C 2700
 5. TEFLON MIL-P-19468

	FERRULE	NOTE 4	NOTE 2		
	SPACER	NOTE 1	NOTE 2		
	SPACER	NOTE 5	WHITE		
	CONTACT PIN	NOTE 1	NOTE 3		
	SHELL	NOTE 1	NOTE 2		
	GASKET	SILICONE	RED		
	C RING	SS41	NOTE 2		
	SPRING	SK5	NOTE 2		
	WASHER	SS41	NOTE 2		
	INSULATOR	DELIN	WHITE		
	BODY	NOTE 1	NOTE 2		
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.



1. CRIMPED FERRULE
HEX CRIMP SIZE .178" (4.52mm)
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068" (1.72mm)

DCC. NO.
A4 DRAWING NO.

MATERIAL		GOLDSUN ELECTRONICS CO., LTD.			
		JAMECO NO.	112110	GOLDSUN NO.	G7409-R
DRAWN: Kiki Chen		Description			Rev.
VERIFY PEOPLE: Wendy Chen, Fanny Du		BNC MALE CONNECTOR			1
		UNIT:	SCALE:	SHEET 1 OF 1	CAS No: ERN No:
		mm			