

TABLE I

DASH NO	A INSIDE DIA		B OUTSIDE DIA	
	MIN	MAX	MIN	MAX
09	.24 (6.1)	.28 (7.1)	.38 (9.7)	.42 (10.7)
12	.33 (8.4)	.37 (9.4)	.48 (12.2)	.52 (13.2)
16	.45 (11.4)	.50 (12.7)	.60 (15.2)	.66 (16.8)
20	.57 (14.5)	.62 (15.7)	.71 (18.0)	.77 (20.0)
24	.69 (17.5)	.75 (19.1)	.88 (22.4)	.94 (23.9)
28	.81 (20.6)	.87 (22.1)	1.00 (25.4)	1.08 (27.4)
32	.93 (23.6)	1.00 (25.4)	1.12 (28.4)	1.20 (30.5)
40	1.18 (30.0)	1.25 (31.8)	1.36 (34.5)	1.44 (36.6)
48	1.43 (36.3)	1.50 (38.1)	1.63 (41.4)	1.71 (43.4)
52	1.56 (39.6)	1.63 (41.4)	1.77 (45.0)	1.85 (47.0)

TABLE I

DASH NO	A INSIDE DIA		B OUTSIDE DIA	
	MIN	MAX	MIN	MAX
09	.24 (6.1)	.28 (7.1)	.38 (9.7)	.42 (10.7)
12	.33 (8.4)	.37 (9.4)	.48 (12.2)	.52 (13.2)
16	.45 (11.4)	.50 (12.7)	.60 (15.2)	.66 (16.8)
20	.57 (14.5)	.62 (15.7)	.71 (18.0)	.77 (20.0)
24	.69 (17.5)	.75 (19.1)	.88 (22.4)	.94 (23.9)
28	.81 (20.6)	.87 (22.1)	1.00 (25.4)	1.08 (27.4)
32	.93 (23.6)	1.00 (25.4)	1.12 (28.4)	1.20 (30.5)
40	1.18 (30.0)	1.25 (31.8)	1.36 (34.5)	1.44 (36.6)
48	1.43 (36.3)	1.50 (38.1)	1.63 (41.4)	1.71 (43.4)
52	1.56 (39.6)	1.63 (41.4)	1.77 (45.0)	1.85 (47.0)

STANDARD SHIPPING PACKAGE/3

DASH NO	MAX LENGTH PER PKG
09 & 12	200 FT (60 m)
16 THRU 52	100 FT (30 m)

REVISIONS

SYM.	DESCRIPTION	DATE	APPROVED
A	RELEASED	03/19/02	DM.
B	REVISED PER DCN #20075	11/12/02	DM.
C	REVISED PER DCN #20210	12/17/02	KB
D	REVISED PER DCN #22208	03/30/04	R.P.
E	REVISED PER DCN #36954	10/15/10	ACM
F	REVISED PER DCN #38793	05/05/11	ACM

PART NUMBER DEVELOPMENT

EXAMPLE:

120 - 125 - 16 R

PRODUCT SERIES

BASIC NO

DASH NO, TABLE I

COLOR OPTION

R = RED
Y = YELLOW
BL = BLUE
TN = DESERT TAN
OR = ORANGE (COLOR XRU1689)
(OMIT FOR STD. BLACK)

NOTES:

1. IDENTIFY WITH MANUFACTURERS NAME AND P/N, SPACE PERMITTING.

2. METRIC DIMENSIONS (IN PARENTHESES) ARE GIVEN FOR REFERENCE ONLY, AND ARE BASED UPON 1 INCH = 25.4 mm.

3. UNLESS OTHERWISE SPECIFIED, CONDUIT WILL BE SHIPPED PER STANDARD PACKAGE MIN LENGTH SUPPLIED WILL BE 10 FEET (3m) WITH A MAX OF 4 LENGTH PER PKG.

4. CONSULT FACTORY FOR SIZES NOT SHOWN.

5. MATERIAL/FINISH:
CONVOLUTED TUBING - KYNAR NOT THERMALLY STABILIZED.

LENGTH

(AS SPECIFIED IN P.O.)

A

B

CONVOLUTED TUBING, ANNULAR

THIS COPYRIGHTED DOCUMENT IS THE PROPERTY OF GLENNAIR, INC. AND IS FURNISHED ON THE CONDITION THAT IT IS NOT TO BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART, OR USED TO SOLICIT QUOTATIONS FROM COMPETITIVE SOURCES, OR USED FOR MANUFACTURE BY ANYONE OTHER THAN GLENNAIR, INC. WITHOUT WRITTEN PERMISSION FROM GLENNAIR, INC. THE INFORMATION HEREIN HAS BEEN DEVELOPED AT GLENNAIR'S EXPENSE AND MAY BE USED FOR ENGINEERING EVALUATION AND INCORPORATION INTO TECHNICAL SPECIFICATIONS AND OTHER DOCUMENTS WHICH SPECIFY PROCUREMENT OF PRODUCTS FROM GLENNAIR, INC.

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES

TOLERANCES:

FRACTIONS ± 1/16

DECIMALS ± .XX .03
± .XXX .015

ANGLES ± 2°

DRAWN D.MONTOYA 03/19/02

CHECK K.BAILEY 03/19/02

ENGR M.P.

RELEASE DATE

ORIGINAL RELEASE DATE

GLENNAIR, INC.

1211 AIR WAY - GLENDALE - CALIFORNIA 91201

TUBING, CONVOLUTED, ANNULAR

CODE IDENT. NO. SIZE

06324 C 120-125 F

REV.

DO NOT SCALE THIS DRAWING

B/F 02-1349 P/C 12

NON REPAIRABLE COMMERCIAL ITEM

SCALE N/A

WEIGHT N/A

SHEET 1 OF 1

1 of 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Glenair:

[120-125-09](#) [120-125-12](#) [120-125-12BL](#) [120-125-12R](#) [120-125-12Y](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-20](#) [120-125-20R](#) [120-125-20Y](#) [120-125-24](#) [120-125-24R](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-28Y](#)
[120-125-32](#) [120-125-32R](#) [120-125-40](#) [120-125-52BL](#) [120-125-56](#) [120-125-09BL](#) [120-125-48BL](#)