

**MICROCHIP****MX575ABB200M000****Ultra-Low Jitter 200MHz LVDS XO****ClockWorks® FUSION**

## General Description

The MX575ABB200M000 is an ultra-low phase jitter XO with LVDS output optimized for high line rate applications.

## Features

- 200MHz LVDS
- Typical phase noise:
  - 94fs (Integration range: 1.875MHz-20MHz)
- $\pm 50$ ppm total frequency stability
- $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$  temperature range
- Industry standard 6-Pin 7mm x 5mm LGA package

## Absolute Maximum Ratings

Supply Voltage (VIN).....	+4.6V
Lead Temperature (soldering, 10s).....	260°C
Storage Temperature (T <sub>S</sub> ).....	125°C
ESD Rating (HBM).....	2kV

## Operating Ratings

Supply Voltage (VIN).....	+2.375V to +3.63V
Ambient Temperature (TA).....	-40°C to +85°C

## Electrical Characteristics

VDD = 2.375 - 3.63V, TA =  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ , outputs terminated with 100 Ohms between Q and /Q.<sup>1</sup>

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
IDD	Supply Current			90		mA
F0	Center Frequency		200			MHz
	Frequency Stability	Note 2		$\pm 50$		ppm
$\varnothing$ j	Phase Noise	Integration Range (12kHz to 20MHz) Integration Range (1.875MHz to 20MHz)	140 94			fsRMS
Tstart	Start-Up Time			20		ms
TR/TF	Rise/Fall time		100		400	ps
	Duty Cycle		45		55	%
VOH	Output High Voltage VOH max = VCM max + 1/2 VOD max	LVDS output levels	1.248	1.375	1.602	V
VOL	Output Low Voltage VOL min = VCM min - 1/2 VOD max	LVDS output levels	0.898	1.025	1.252	V
VOD	Output Differential Voltage		247	350	454	mV
VCM	Common Mode Output Voltage		1.125	1.2	1.375	V

**Notes:**

1. Guaranteed after thermal equilibrium.
2. Inclusive of initial accuracy, temperature drift, aging, shock, vibration.

ClockWorks is a registered trademark of Microchip Technology Inc.

**Microchip Technology Inc.**

<http://www.microchip.com>

June 07, 2017  
MX575AB1-2172


Revision 1.0  
[tcghelp@microchip.com](mailto:tcghelp@microchip.com)

## Ordering Information

Ordering Part Number	Marking Line 1	Marking Line 3	Shipping	Package
MX575ABB200M000	MX575AB	B200M000	Tube	6-Pin 7mm x 5mm LGA
MX575ABB200M000-TR	MX575AB	B200M000	Tape and Reel	6-Pin 7mm x 5mm LGA

Devices are Green and RoHS compliant. Sample material may have only a partial top mark.

## Pin Configuration



## Pin Description

Pin Number	Pin Name	Pin Type	Pin Level	Pin Function
1	OE	I, SE	LVC MOS	Output Enable, disables output to tri-state, 0 = Disabled, 1 = Enabled, 50k Ohms Pull-Up
2	DNC			Make no connection, leave floating.
3	GND	PWR		Power Supply Ground
4, 5	Q, /Q	O, Diff	LVDS	Clock Output Frequency = 200MHz
6	VDD	PWR		Power Supply




Figure 1. LVDS Output 200MHz 1.875MHz-20MHz 94fs




Figure 2. LVDS Output 200MHz 12kHz-20MHz 140fs





Figure 3. E5001A Period Jitter @ 200MHz LVDS, RMS TJ: 239fs, Pk-Pk TJ: 2.08ps

## Package Information and Recommended Land Pattern for 6-Pin LGA<sup>3</sup>



### Note:

3. Package information is correct as of the publication date. For updates and most current information, go to [www.microchip.com](http://www.microchip.com).

**Microchip Technology Inc.**

<http://www.microchip.com>

Microchip makes no representations or warranties with respect to the accuracy or completeness of the information furnished in this data sheet. This information is not intended as a warranty and Microchip does not assume responsibility for its use. Microchip reserves the right to change circuitry, specifications and descriptions at any time without notice. No license, whether express, implied, arising by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Microchip's terms and conditions of sale for such products, Microchip assumes no liability whatsoever, and Microchip disclaims any express or implied warranty relating to the sale and/or use of Microchip products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right.

© 2017 Microchip Technology Inc.