



+ CONNECTORS

FPC CONNECTORS



✓ Active

TE CONNECTIVITY (TE)

.5 FPC VT ZIF Type-B 36 CONT

[FPC](#) | [FPC](#)

3-1734741-6

TE Internal Number: 3-1734741-6

EU RoHS Compliant

EU ELV Compliant

Connector System Flex-to-Board

Number of Positions 36

Centerline (Pitch) .5 mm [.0197 in]

Insertion Force ZIF

PCB Mounting Orientation Vertical

PRODUCT DRAWING
[English](#)

3D PDF

DOCUMENTATION

Product Drawings

FPC/FFC CONN., 0.5 MM PITCH, ZIF, VERTICAL, SMT, TYPE B

[PDF \(TIFF AVAILABLE\)](#)

[English](#)

CAD Files

Customer View Model

[2D_DXF.ZIP](#)

[English](#)

3D PDF

[PDF](#)

[3D](#)

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Shrouded Yes

Connector System Flex-to-Board

Insertion Force ZIF

PCB Mounting Orientation Vertical

Actuator Type Stuffer

Sealable No

Connector & Contact Terminates To Flexible Printed Circuit (FPC)

Shielded No

Product Type Connector

Series FPC

Wire/Cable Type FPC/FFC

Connector Style Receptacle

Connector Type Connector Assembly

Configuration Features

Number of Positions 36

Tail Orientation Staggered Type B

Number of Rows 1

Electrical Characteristics

Operating Voltage (VAC) 50

Contact Features

Contact Mating Area Plating Material Gold

Contact Current Rating (Max) (A) .5

Contact Mating Area Plating Thickness .025 µm [120 µin]

Contact Base Material Phosphor Bronze

Contact Type Socket

Contact Transmits (Typical) Signal (Data)

Contact Termination Area Plating Material Gold

Contact Design Single Beam

Contact Termination Area Plating Thickness (µin) 120

Termination Features

Termination Method to PC Board Surface Mount

Mechanical Attachment

PCB Mount Alignment Without

PCB Mount Retention With

Mating Alignment With

Housing Features

Centerline (Pitch) .5 mm [.0197 in]

Housing Material PA 9T GF

Housing Color Black

Dimensions

Height 4.15 mm [.1633 in]

Width 3.8 mm [.1496 in]

Flex Cable Thickness .3 mm [.012 in]

Length 23.7 mm [.9331 in]

Usage Conditions

Operating Temperature Range -20 – 85 °C [-4 – 185 °F]

Identification Marking

Circuit Identification Feature Without

Packaging Features

Packaging Method Tape

Packaging Quantity 1000

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF