


MC10189

Hex Inverter With Enable


The MC10189 provides a high-speed Hex Inverter with a common Enable input. The hex inverting function is provided when Enable is in the low state. When Enable is in the high state all outputs are low.

- $P_D = 200 \text{ mW typ/pkg (No Load)}$
- $t_{pd} = 2.0 \text{ ns (Y-Q)}$
 $= 2.5 \text{ ns (X-Q)}$

LOGIC DIAGRAM



DIP PIN ASSIGNMENT



Pin assignment is for Dual-in-Line Package.

For PLCC pin assignment, see the Pin Conversion Tables on page 18 of the ON Semiconductor MECL Data Book (DL122/D).

TRUTH TABLE


Inputs		Output
X	Y	OUT
L	L	H
L	H	L
H	L	L
H	H	L




ON Semiconductor

<http://onsemi.com>


MARKING DIAGRAMS



CDIP-16
L SUFFIX
CASE 620



PDIP-16
P SUFFIX
CASE 648



PLCC-20
FN SUFFIX
CASE 775



A = Assembly Location
WL = Wafer Lot
YY = Year
WW = Work Week

ORDERING INFORMATION

Device	Package	Shipping
MC10189L	CDIP-16	25 Units / Rail
MC10189P	PDIP-16	25 Units / Rail
MC10189FN	PLCC-20	46 Units / Rail

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Pin Under Test	Test Limits						Unit	
			-30°C		+25°C		+85°C			
			Min	Max	Min	Max	Min	Max		
Power Supply Drain Current	I_E	8		44		40		44	mA	
Input Current	I_{inH}	5		425		265		265	μA	
	I_{inL}	9		890		555		555	μA	
Output Voltage Logic 1	V_{OH}	2	-1.060	-0.890	-0.960	-0.810	-0.890	-0.700	Vdc	
Output Voltage Logic 0	V_{OL}	2	-1.890	-1.675	-1.850	-1.650	-1.825	-1.615	Vdc	
Threshold Voltage Logic 1	V_{OHA}	2	-1.080		-0.980		-0.910		Vdc	
Threshold Voltage Logic 0	V_{OLA}	2		-1.655		-1.630		-1.595	Vdc	
Switching Times (50Ω Load)									ns	
Propagation Delay Enable Data	t_{PHL} t_{PLH}	2	1.1 1.0	3.9 3.3	1.1 1.0	3.5 2.9	1.1 1.0	3.9 3.3		
Rise/Fall Time (20 to 80%)	t_{TLH} t_{THL}	2	1.1	3.7	1.1	3.3	1.1	3.7		


ELECTRICAL CHARACTERISTICS (continued)

@ Test Temperature	Characteristic	Symbol	Pin Under Test	TEST VOLTAGE VALUES (Volts)					(V_{CC}) Gnd				
				V_{IHmax}	V_{ILmin}	V_{IHMin}	V_{ILMax}	V_{EE}					
				-0.890	-1.890	-1.205	-1.500	-5.2					
				+25°C	-0.810	-1.850	-1.105	-1.475					
				+85°C	-0.700	-1.825	-1.035	-1.440					
				TEST VOLTAGE APPLIED TO PINS LISTED BELOW									
				V_{IHmax}	V_{ILmin}	V_{IHMin}	V_{ILMax}	V_{EE}					
Power Supply Drain Current	I_E	8						8	1, 16				
Input Current	I_{inH}	5	5					8	1, 16				
	I_{inL}	9	9					8	1, 16				
Output Voltage Logic 1	V_{OH}	2		5				8	1, 16				
Output Voltage Logic 0	V_{OL}	2	9					8	1, 16				
Threshold Voltage Logic 1	V_{OHA}	2				5		8	1, 16				
Threshold Voltage Logic 0	V_{OLA}	2			5			8	1, 16				
Switching Times (50Ω Load)					$Pulse\ In$	$Pulse\ Out$	-3.2 V	+2.0 V					
Propagation Delay Enable Data	t_{PHL} t_{PLH}	2			9	2	8	1, 16					
Rise/Fall Time (20 to 80%)	t_{TLH} t_{THL}	2			5	2	8	1, 16					


Each MECL 10,000 series circuit has been designed to meet the dc specifications shown in the test table, after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear fpm is maintained. Outputs are terminated through a 50-ohm resistor to -2.0 volts. Test procedures are shown for only one gate. The other gates are tested in the same manner.

PACKAGE DIMENSIONS

PLCC-20
FN SUFFIX
PLASTIC PLCC PACKAGE
CASE 775-02
ISSUE C



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.385	0.395	9.78	10.03
B	0.385	0.395	9.78	10.03
C	0.165	0.180	4.20	4.57
E	0.090	0.110	2.29	2.79
F	0.013	0.019	0.33	0.48
G	0.050 BSC		1.27 BSC	
H	0.026	0.032	0.66	0.81
J	0.020	—	0.51	—
K	0.025	—	0.64	—
R	0.350	0.356	8.89	9.04
U	0.350	0.356	8.89	9.04
V	0.042	0.048	1.07	1.21
W	0.042	0.048	1.07	1.21
X	0.042	0.056	1.07	1.42
Y	—	0.020	—	0.50
Z	2°	10°	2°	10°
G1	0.310	0.330	7.88	8.38
K1	0.040	—	1.02	—




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.
4. DIMENSION F MAY NARROW TO 0.76 (0.030) WHERE THE LEAD ENTERS THE CERAMIC BODY.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.750	0.785	19.05	19.93
B	0.240	0.295	6.10	7.49
C	0.200	0.200	5.08	5.08
D	0.015	0.020	0.39	0.50
E	0.050 BSC	0.050 BSC	1.27 BSC	1.27 BSC
F	0.055	0.065	1.40	1.65
G	0.100 BSC	0.100 BSC	2.54 BSC	2.54 BSC
H	0.008	0.015	0.21	0.38
K	0.125	0.170	3.18	4.31
L	0.300 BSC	0.300 BSC	7.62 BSC	7.62 BSC
M	0°	15°	0°	15°
N	0.20	0.40	0.51	1.01

PDIP-16 P SUFFIX
PLASTIC DIP PACKAGE
CASE 648-08
ISSUE R



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.740	0.770	18.80	19.55
B	0.250	0.270	6.35	6.85
C	0.145	0.175	3.69	4.44
D	0.015	0.021	0.39	0.53
F	0.040	0.70	1.02	1.77
G	0.100 BSC	0.100 BSC	2.54 BSC	2.54 BSC
H	0.050 BSC	0.050 BSC	1.27 BSC	1.27 BSC
J	0.008	0.015	0.21	0.38
K	0.110	0.130	2.80	3.30
L	0.295	0.305	7.50	7.74
M	0°	10°	0°	10°
S	0.20	0.40	0.51	1.01

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

North America Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA

Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support
German Phone: (+1) 303-308-7140 (M-F 2:30pm to 5:00pm Munich Time)
Email: ONlit-german@hibbertco.com
French Phone: (+1) 303-308-7141 (M-F 2:30pm to 5:00pm Toulouse Time)
Email: ONlit-french@hibbertco.com
English Phone: (+1) 303-308-7142 (M-F 1:30pm to 5:00pm UK Time)
Email: ONlit@hibbertco.com

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong 800-4422-3781

Email: ONlit-asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-8549

Phone: 81-3-5740-2745
Email: r14525@onsemi.com

Fax Response Line: 303-675-2167
800-344-3810 Toll Free USA/Canada

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local
Sales Representative.