

1M x 16 (16-MBIT) DYNAMIC RAM WITH EDO PAGE MODE

DECEMBER 2006

FEATURES

- TTL compatible inputs and outputs; tristate I/O
- Refresh Interval:
 - Auto refresh Mode: 1,024 cycles /16 ms
 - **RAS**-Only, **CAS**-before-**RAS** (CBR), and Hidden
 - Self refresh Mode: 1,024 cycles /128 ms
- JEDEC standard pinout
- Single power supply: 3.3V ± 10%
- Byte Write and Byte Read operation via two **CAS**
- Industrial Temperature Range: -40°C to +85°C
- Lead-free available

DESCRIPTION


The *ISSI* IS41LV16100B is 1,048,576 x 16-bit high-performance CMOS Dynamic Random Access Memories. These devices offer an accelerated cycle access called EDO Page Mode. EDO Page Mode allows 1,024 random accesses within a single row with access cycle time as short as 20 ns per 16-bit word.

These features make the IS41LV16100B ideally suited for high-bandwidth graphics, digital signal processing, high-performance computing systems, and peripheral applications.


The IS41LV16100B is packaged in a 42-pin 400-mil SOJ and 400-mil 50- (44-) pin TSOP (Type II).

PIN CONFIGURATIONS

50(44)-Pin TSOP (Type II)



42-Pin SOJ



KEY TIMING PARAMETERS


Parameter	-50	-60	Unit
Max. RAS Access Time (t _{RA} C)	50	60	ns
Max. CAS Access Time (t _{CA} C)	14	15	ns
Max. Column Address Access Time (t _{AA})	25	30	ns
Min. EDO Page Mode Cycle Time (t _{PC})	30	40	ns
Min. Read/Write Cycle Time (t _{RC})	85	110	ns

PIN DESCRIPTIONS

A0-A9	Address Inputs
I/O0-15	Data Inputs/Outputs
WE	Write Enable
OE	Output Enable
RAS	Row Address Strobe
UCAS	Upper Column Address Strobe
LCAS	Lower Column Address Strobe
VDD	Power
GND	Ground
NC	No Connection

Copyright © 2006 Integrated Silicon Solution, Inc. All rights reserved. *ISSI* reserves the right to make changes to this specification and its products at any time without notice. *ISSI* assumes no liability arising out of the application or use of any information, products or services described herein. Customers are advised to obtain the latest version of this device specification before relying on any published information and before placing orders for products.

FUNCTIONAL BLOCK DIAGRAM



TRUTH TABLE

Function	RAS	LCAS	UCAS	WE	OE	Address	tr/tc	I/O
Standby	H	H	H	X	X	X		High-Z
Read: Word	L	L	L	H	L	ROW/COL		Dout
Read: Lower Byte	L	L	H	H	L	ROW/COL		Lower Byte, Dout Upper Byte, High-Z
Read: Upper Byte	L	H	L	H	L	ROW/COL		Lower Byte, High-Z Upper Byte, Dout
Write: Word (Early Write)	L	L	L	L	X	ROW/COL		Din
Write: Lower Byte (Early Write)	L	L	H	L	X	ROW/COL		Lower Byte, Din Upper Byte, High-Z
Write: Upper Byte (Early Write)	L	H	L	L	X	ROW/COL		Lower Byte, High-Z Upper Byte, Din
Read-Write ^(1,2)	L	L	L	H→L	L→H	ROW/COL		Dout, Din
EDO Page-Mode Read ⁽²⁾	L	H→L	H→L	H	L	ROW/COL		Dout
1st Cycle:	L	H→L	H→L	H	L	NA/COL		Dout
2nd Cycle:	L	L→H	L→H	H	L	NA/NA		Dout
Any Cycle:	L	L→H	L→H	H	L	NA/NA		Dout
EDO Page-Mode Write ⁽¹⁾	L	H→L	H→L	L	X	ROW/COL		Din
1st Cycle:	L	H→L	H→L	L	X	NA/COL		Din
2nd Cycle:	L	H→L	H→L	H→L	L→H	NA/COL		Dout, Din
EDO Page-Mode Read-Write ^(1,2)	L	H→L	H→L	H→L	L→H	ROW/COL		Dout, Din
1st Cycle:	L	H→L	H→L	H→L	L→H	NA/COL		Dout, Din
2nd Cycle:	L	H→L	H→L	H→L	L→H	NA/COL		Dout, Din
Hidden Refresh	Read ⁽²⁾	L→H→L	L	L	H	L	ROW/COL	Dout
	Write ^(1,3)	L→H→L	L	L	L	X	ROW/COL	Dout
RAS-Only Refresh		L	H	H	X	X	ROW/NA	High-Z
CBR Refresh ⁽⁴⁾	H→L	L	L	X	X	X		High-Z

Notes:

1. These WRITE cycles may also be BYTE WRITE cycles (either **LCAS** or **UCAS** active).
2. These READ cycles may also be BYTE READ cycles (either **LCAS** or **UCAS** active).
3. EARLY WRITE only.
4. At least one of the two **CAS** signals must be active (**LCAS** or **UCAS**).

Functional Description

The IS41LV16100B is a CMOS DRAM optimized for high-speed bandwidth, low power applications. During READ or WRITE cycles, each bit is uniquely addressed through the 16 address bits. These are entered ten bits (A0-A9) at time. The row address is latched by the Row Address Strobe (**RAS**). The column address is latched by the Column Address Strobe (**CAS**). **RAS** is used to latch the first nine bits and **CAS** is used to latch the latter nine bits.

The IS41LV16100B has two **CAS** controls, **LCAS** and **UCAS**. The **LCAS** and **UCAS** inputs internally generates a **CAS** signal functioning in an identical manner to the single **CAS** input on the other 1M x 16 DRAMs. The key difference is that each **CAS** controls its corresponding I/O tristate logic (in conjunction with **OE** and **WE** and **RAS**). **LCAS** controls I/O0 through I/O7 and **UCAS** controls I/O8 through I/O15.

The IS41LV16100B **CAS** function is determined by the first **CAS** (**LCAS** or **UCAS**) transitioning LOW and the last transitioning back HIGH. The two **CAS** controls give the IS41LV16100B both BYTE READ and BYTE WRITE cycle capabilities.

Memory Cycle

A memory cycle is initiated by bring **RAS** LOW and it is terminated by returning both **RAS** and **CAS** HIGH. To ensures proper device operation and data integrity any memory cycle, once initiated, must not be ended or aborted before the minimum **trAS** time has expired. A new cycle must not be initiated until the minimum precharge time **trP**, **tCP** has elapsed.

Read Cycle

A read cycle is initiated by the falling edge of **CAS** or **OE**, whichever occurs last, while holding **WE** HIGH. The column address must be held for a minimum time specified by **tAR**. Data Out becomes valid only when **trAC**, **tAA**, **tcAC** and **toEA** are all satisfied. As a result, the access time is dependent on the timing relationships between these parameters.

Write Cycle

A write cycle is initiated by the falling edge of **CAS** and **WE**, whichever occurs last. The input data must be valid at or before the falling edge of **CAS** or **WE**, whichever occurs first.

Auto Refresh Cycle

To retain data, 1,024 refresh cycles are required in each 16 ms period. There are two ways to refresh the memory.

1. By clocking each of the 1,024 row addresses (A0 through A9) with **RAS** at least once every 128 ms. Any read, write, read-modify-write or **RAS**-only cycle refreshes the addressed row.
2. Using a **CAS**-before-**RAS** refresh cycle. **CAS**-before-**RAS** refresh is activated by the falling edge of **RAS**,

while holding **CAS** LOW. In **CAS**-before-**RAS** refresh cycle, an internal 9-bit counter provides the row addresses and the external address inputs are ignored.

CAS-before-**RAS** is a refresh-only mode and no data access or device selection is allowed. Thus, the output remains in the High-Z state during the cycle.

Self Refresh Cycle

The Self Refresh allows the user a dynamic refresh, data retention mode at the extended refresh period of 128 ms. i.e., 125 μ s per row when using distributed CBR refreshes. The feature also allows the user the choice of a fully static, low power data retention mode. The optional Self Refresh feature is initiated by performing a CBR Refresh cycle and holding **RAS** LOW for the specified **tRAS**.

The Self Refresh mode is terminated by driving **RAS** HIGH for a minimum time of **trP**. This delay allows for the completion of any internal refresh cycles that may be in process at the time of the **RAS** LOW-to-HIGH transition. If the DRAM controller uses a distributed refresh sequence, a burst refresh is not required upon exiting Self Refresh.

However, if the DRAM controller utilizes a **RAS**-only or burst refresh sequence, all 1,024 rows must be refreshed within the average internal refresh rate, prior to the resumption of normal operation.

Extended Data Out Page Mode

EDO page mode operation permits all 1,024 columns within a selected row to be randomly accessed at a high data rate.

In EDO page mode read cycle, the data-out is held to the next **CAS** cycle's falling edge, instead of the rising edge. For this reason, the valid data output time in EDO page mode is extended compared with the fast page mode. In the fast page mode, the valid data output time becomes shorter as the **CAS** cycle time becomes shorter. Therefore, in EDO page mode, the timing margin in read cycle is larger than that of the fast page mode even if the **CAS** cycle time becomes shorter.

In EDO page mode, due to the extended data function, the **CAS** cycle time can be shorter than in the fast page mode if the timing margin is the same.

The EDO page mode allows both read and write operations during one **RAS** cycle, but the performance is equivalent to that of the fast page mode in that case.

Power-On

After application of the **VDD** supply, an initial pause of 200 μ s is required followed by a minimum of eight initialization cycles (any combination of cycles containing a **RAS** signal).

During power-on, it is recommended that **RAS** track with **VDD** or be held at a valid **VIH** to avoid current surges.

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Symbol	Parameters		Rating	Unit
V _T	Voltage on Any Pin Relative to GND	3.3V	−0.5 to +4.6	V
V _{DD}	Supply Voltage	3.3V	−0.5 to +4.6	V
I _{OUT}	Output Current		50	mA
P _D	Power Dissipation		1	W
T _A	Commercial Operation Temperature		0 to +70	°C
	Industrial Operation Temperature		−40 to +85	°C
T _{STG}	Storage Temperature		−55 to +125	°C

Note:

1. Stress greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

RECOMMENDED OPERATING CONDITIONS (Voltages are referenced to GND.)

Symbol	Parameter		Min.	Typ.	Max.	Unit
V _{DD}	Supply Voltage	3.3V	3.0	3.3	3.6	V
V _{IH}	Input High Voltage	3.3V	2.0	—	V _{DD} + 0.3	V
V _{IL}	Input Low Voltage	3.3V	−0.3	—	0.8	V
T _A	Commercial Ambient Temperature		0	—	70	°C
	Industrial Ambient Temperature		−40	—	85	°C

CAPACITANCE^(1,2)

Symbol	Parameter		Max.	Unit
C _{IN1}	Input Capacitance: A ₀ -A ₉		5	pF
C _{IN2}	Input Capacitance: <u>RAS</u> , <u>UCAS</u> , <u>LCAS</u> , <u>WE</u> , <u>OE</u>		7	pF
C _{IO}	Data Input/Output Capacitance: I/O ₀ -I/O ₁₅		7	pF

Notes:

1. Tested initially and after any design or process changes that may affect these parameters.
2. Test conditions: T_A = 25°C, f = 1 MHz.

ELECTRICAL CHARACTERISTICS⁽¹⁾

(Recommended Operating Conditions unless otherwise noted.)

Symbol	Parameter	Test Condition	Speed	Min.	Max.	Unit
I _{IL}	Input Leakage Current	Any input $0V \leq V_{IN} \leq V_{DD}$ Other inputs not under test = 0V		-10	10	µA
I _{IO}	Output Leakage Current	Output is disabled (Hi-Z) $0V \leq V_{OUT} \leq V_{DD}$		-10	10	µA
V _{OH}	Output High Voltage Level	I _{OH} = -2.0 mA (3.3V)		2.4	—	V
V _{OL}	Output Low Voltage Level	I _{OL} = 2.0 mA (3.3V)		—	0.4	V
I _{CC1}	Standby Current: TTL	<u>RAS</u> , <u>LCAS</u> , <u>UCAS</u> $\geq V_{IH}$	Commercial Industrial	3.3V 3.3V	— —	mA mA
I _{CC2}	Standby Current: CMOS	<u>RAS</u> , <u>LCAS</u> , <u>UCAS</u> $\geq V_{DD} - 0.2V$		3.3V	—	2 mA
I _{CC3}	Operating Current: Random Read/Write ^(2,3,4) Average Power Supply Current	<u>RAS</u> , <u>LCAS</u> , <u>UCAS</u> , Address Cycling, t _{RC} = t _{RC} (min.)		-50 -60	— —	180 mA 170 mA
I _{CC4}	Operating Current: EDO Page Mode ^(2,3,4) Average Power Supply Current	<u>RAS</u> = V _{IL} , <u>LCAS</u> , <u>UCAS</u> , Cycling t _{PC} = t _{PC} (min.)		-50 -60	— —	180 mA 170 mA
I _{CC5}	Refresh Current: <u>RAS</u> -Only ^(2,3) Average Power Supply Current	<u>RAS</u> Cycling, <u>LCAS</u> , <u>UCAS</u> $\geq V_{IH}$ t _{RC} = t _{RC} (min.)		-50 -60	— —	180 mA 170 mA
I _{CC6}	Refresh Current: CBR ^(2,3,5) Average Power Supply Current	<u>RAS</u> , <u>LCAS</u> , <u>UCAS</u> Cycling t _{RC} = t _{RC} (min.)		-50 -60	— —	180 mA 170 mA

Notes:

1. An initial pause of 200 µs is required after power-up followed by eight RAS refresh cycles (RAS-Only or CBR) before proper device operation is assured. The eight RAS cycles wake-up should be repeated any time the t_{REF} refresh requirement is exceeded.
2. Dependent on cycle rates.
3. Specified values are obtained with minimum cycle time and the output open.
4. Column-address is changed once each EDO page cycle.
5. Enables on-chip refresh and address counters.

AC CHARACTERISTICS^(1,2,3,4,5,6)

(Recommended Operating Conditions unless otherwise noted.)

Symbol	Parameter	-50		-60		Units
		Min.	Max.	Min.	Max.	
t _{RC}	Random READ or WRITE Cycle Time	85	—	110	—	ns
t _{RAC}	Access Time from <u>RAS</u> ^(6, 7)	—	50	—	60	ns
t _{CAC}	Access Time from <u>CAS</u> ^(6, 8, 15)	—	14	—	15	ns
t _{AA}	Access Time from Column-Address ⁽⁶⁾	—	25	—	30	ns
t _{TRAS}	<u>RAS</u> Pulse Width	50	10K	60	10K	ns
t _{RP}	<u>RAS</u> Precharge Time	30	—	40	—	ns
t _{CAS}	<u>CAS</u> Pulse Width ⁽²⁶⁾	8	10K	10	10K	ns
t _{CP}	<u>CAS</u> Precharge Time ^(9, 25)	9	—	10	—	ns
t _{CSH}	<u>CAS</u> Hold Time ⁽²¹⁾	50	—	60	—	ns
t _{TRCD}	<u>RAS</u> to <u>CAS</u> Delay Time ^(10, 20)	12	37	20	45	ns
t _{TASR}	Row-Address Setup Time	0	—	0	—	ns
t _{TRAH}	Row-Address Hold Time	8	—	10	—	ns
t _{TASC}	Column-Address Setup Time ⁽²⁰⁾	0	—	0	—	ns
t _{CAH}	Column-Address Hold Time ⁽²⁰⁾	8	—	10	—	ns
t _{TAR}	Column-Address Hold Time (referenced to <u>RAS</u>)	30	—	40	—	ns
t _{TRAD}	<u>RAS</u> to Column-Address Delay Time ⁽¹¹⁾	14	25	15	30	ns
t _{TRAL}	Column-Address to <u>RAS</u> Lead Time	25	—	30	—	ns
t _{TRPC}	<u>RAS</u> to <u>CAS</u> Precharge Time	5	—	5	—	ns
t _{TRSH}	<u>RAS</u> Hold Time ⁽²⁷⁾	14	—	15	—	ns
t _{TCLZ}	<u>CAS</u> to Output in Low-Z ^(15, 29)	0	—	0	—	ns
t _{TCRP}	<u>CAS</u> to <u>RAS</u> Precharge Time ⁽²¹⁾	5	—	5	—	ns
t _{TOD}	Output Disable Time ^(19, 28, 29)	3	12	3	12	ns
t _{TOE/TOEA}	Output Enable Time ^(15, 16)	—	14	—	15	ns
t _{TOEHC}	<u>OE</u> HIGH Hold Time from <u>CAS</u> HIGH	15	—	15	—	ns
t _{TOEP}	<u>OE</u> HIGH Pulse Width	10	—	10	—	ns
t _{TOES}	<u>OE</u> LOW to <u>CAS</u> HIGH Setup Time	5	—	5	—	ns
t _{TRCS}	Read Command Setup Time ^(17, 20)	0	—	0	—	ns
t _{TRRH}	Read Command Hold Time (referenced to <u>RAS</u>) ⁽¹²⁾	0	—	0	—	ns
t _{TRCH}	Read Command Hold Time (referenced to <u>CAS</u>) ^(12, 17, 21)	0	—	0	—	ns
t _{WCW}	Write Command Hold Time ^(17, 27)	8	—	10	—	ns
t _{WCW}	Write Command Hold Time (referenced to <u>RAS</u>) ⁽¹⁷⁾	40	—	50	—	ns

AC CHARACTERISTICS (Continued)^(1,2,3,4,5,6)

(Recommended Operating Conditions unless otherwise noted.)

Symbol	Parameter	-50		-60		Units
		Min.	Max.	Min.	Max.	
tWP	Write Command Pulse Width ⁽¹⁷⁾	8	—	10	—	ns
tWPZ	\overline{WE} Pulse Widths to Disable Outputs	10	—	10	—	ns
tRWL	Write Command to \overline{RAS} Lead Time ⁽¹⁷⁾	13	—	15	—	ns
tcWL	Write Command to \overline{CAS} Lead Time ^(17, 21)	8	—	15	—	ns
twCS	Write Command Setup Time ^(14, 17, 20)	0	—	0	—	ns
tdHR	Data-in Hold Time (referenced to \overline{RAS})	39	—	40	—	ns
toEH	\overline{OE} Hold Time from \overline{WE} during READ-MODIFY-WRITE cycle ⁽¹⁸⁾	14	—	15	—	ns
tdS	Data-In Setup Time ^(15, 22)	0	—	0	—	ns
tdH	Data-In Hold Time ^(15, 22)	8	—	15	—	ns
trWC	READ-MODIFY-WRITE Cycle Time	110	—	155	—	ns
trWD	\overline{RAS} to \overline{WE} Delay Time during READ-MODIFY-WRITE Cycle ⁽¹⁴⁾	65	—	85	—	ns
tcWD	\overline{CAS} to \overline{WE} Delay Time ^(14, 20)	26	—	40	—	ns
tAWD	Column-Address to \overline{WE} Delay Time ⁽¹⁴⁾	40	—	55	—	ns
tPC	EDO Page Mode READ or WRITE Cycle Time ⁽²⁴⁾	30	—	40	—	ns
trASP	\overline{RAS} Pulse Width in EDO Page Mode	50	100K	60	100K	ns
tCPA	Access Time from \overline{CAS} Precharge ⁽¹⁵⁾	—	30	—	35	ns
tPRWC	EDO Page Mode READ-WRITE Cycle Time ⁽²⁴⁾	56	—	56	—	ns
tCOH	Data Output Hold after \overline{CAS} LOW	5	—	5	—	ns
toFF	Output Buffer Turn-Off Delay from \overline{CAS} or \overline{RAS} ^(13, 15, 19, 29)	3	12	3	15	ns
tWHZ	Output Disable Delay from \overline{WE}	3	10	3	15	ns
tCLCH	Last \overline{CAS} going LOW to First \overline{CAS} returning HIGH ⁽²³⁾	10	—	10	—	ns
tCSR	\overline{CAS} Setup Time (CBR REFRESH) ^(30, 20)	5	—	5	—	ns
tCHR	\overline{CAS} Hold Time (CBR REFRESH) ^(30, 21)	8	—	10	—	ns
tORD	\overline{OE} Setup Time prior to \overline{RAS} during HIDDEN REFRESH Cycle	0	—	0	—	ns
tREF	Auto Refresh Period (1,024 Cycles)	—	16	—	16	ms
tREF	Self Refresh Period (1,024 Cycles)	—	128	—	128	ms
tr	Transition Time (Rise or Fall) ^(2, 3)	3	50	3	50	ns

AC TEST CONDITIONS

Output load: One TTL Load and 50 pF ($V_{DD} = 3.3V \pm 10\%$)


Input timing reference levels: $V_{IH} = 2.0V$, $V_{IL} = 0.8V$ ($V_{DD} = 3.3V \pm 10\%$)

Output timing reference levels: $V_{OH} = 2.0V$, $V_{OL} = 0.8V$

Notes:


1. An initial pause of 200 μs is required after power-up followed by eight \overline{RAS} refresh cycle (\overline{RAS} -Only or CBR) before proper device operation is assured. The eight \overline{RAS} cycles wake-up should be repeated any time the t_{REF} refresh requirement is exceeded.
2. V_{IH} (MIN) and V_{IL} (MAX) are reference levels for measuring timing of input signals. Transition times, are measured between V_{IH} and V_{IL} (or between V_{IL} and V_{IH}) and assume to be 1 ns for all inputs.
3. In addition to meeting the transition rate specification, all input signals must transit between V_{IH} and V_{IL} (or between V_{IL} and V_{IH}) in a monotonic manner.
4. If \overline{CAS} and $\overline{RAS} = V_{IH}$, data output is High-Z.
5. If $\overline{CAS} = V_{IL}$, data output may contain data from the last valid READ cycle.
6. Measured with a load equivalent to one TTL gate and 50 pF.
7. Assumes that $t_{RCD} \leq t_{RCF}$ (MAX). If t_{RCF} is greater than the maximum recommended value shown in this table, t_{RAC} will increase by the amount that t_{RCF} exceeds the value shown.
8. Assumes that $t_{RCF} \leq t_{RCF}$ (MAX).
9. If \overline{CAS} is LOW at the falling edge of \overline{RAS} , data out will be maintained from the previous cycle. To initiate a new cycle and clear the data output buffer, \overline{CAS} and \overline{RAS} must be pulsed for t_{CP} .
10. Operation with the t_{RCF} (MAX) limit ensures that t_{RAC} (MAX) can be met. t_{RCF} (MAX) is specified as a reference point only; if t_{RCF} is greater than the specified t_{RCF} (MAX) limit, access time is controlled exclusively by t_{CAC} .
11. Operation within the t_{RAD} (MAX) limit ensures that t_{RCF} (MAX) can be met. t_{RAD} (MAX) is specified as a reference point only; if t_{RAD} is greater than the specified t_{RAD} (MAX) limit, access time is controlled exclusively by t_{AA} .
12. Either t_{RCH} or t_{RRH} must be satisfied for a READ cycle.
13. t_{OFF} (MAX) defines the time at which the output achieves the open circuit condition; it is not a reference to V_{OH} or V_{OL} .
14. t_{WCS} , t_{RWD} , t_{AWD} and t_{CWD} are restrictive operating parameters in LATE WRITE and READ-MODIFY-WRITE cycle only. If $t_{WCS} \leq t_{WCS}$ (MIN), the cycle is an EARLY WRITE cycle and the data output will remain open circuit throughout the entire cycle. If $t_{RWD} \leq t_{RWD}$ (MIN), $t_{AWD} \leq t_{AWD}$ (MIN) and $t_{CWD} \leq t_{CWD}$ (MIN), the cycle is a READ-WRITE cycle and the data output will contain data read from the selected cell. If neither of the above conditions is met, the state of I/O (at access time and until \overline{CAS} and \overline{RAS} or \overline{OE} go back to V_{IH}) is indeterminate. \overline{OE} held HIGH and \overline{WE} taken LOW after \overline{CAS} goes LOW result in a LATE WRITE (\overline{OE} -controlled) cycle.
15. Output parameter (I/O) is referenced to corresponding \overline{CAS} input, I/O0-I/O7 by \overline{LCAS} and I/O8-I/O15 by \overline{UCAS} .
16. During a READ cycle, if \overline{OE} is LOW then taken HIGH before \overline{CAS} goes HIGH, I/O goes open. If \overline{OE} is tied permanently LOW, a LATE WRITE or READ-MODIFY-WRITE is not possible.
17. Write command is defined as \overline{WE} going low.
18. LATE WRITE and READ-MODIFY-WRITE cycles must have both t_{OD} and t_{OEH} met (\overline{OE} HIGH during WRITE cycle) in order to ensure that the output buffers will be open during the WRITE cycle. The I/Os will provide the previously written data if \overline{CAS} remains LOW and \overline{OE} is taken back to LOW after t_{OEH} is met.
19. The I/Os are in open during READ cycles once t_{OD} or t_{OFF} occur.
20. The first $\chi_{\overline{CAS}}$ edge to transition LOW.
21. The last $\chi_{\overline{CAS}}$ edge to transition HIGH.
22. These parameters are referenced to \overline{CAS} leading edge in EARLY WRITE cycles and \overline{WE} leading edge in LATE WRITE or READ-MODIFY-WRITE cycles.
23. Last falling $\chi_{\overline{CAS}}$ edge to first rising $\chi_{\overline{CAS}}$ edge.
24. Last rising $\chi_{\overline{CAS}}$ edge to next cycle's last rising $\chi_{\overline{CAS}}$ edge.
25. Last rising $\chi_{\overline{CAS}}$ edge to first falling $\chi_{\overline{CAS}}$ edge.
26. Each $\chi_{\overline{CAS}}$ must meet minimum pulse width.
27. Last $\chi_{\overline{CAS}}$ to go LOW.
28. I/Os controlled, regardless \overline{UCAS} and \overline{LCAS} .
29. The 3 ns minimum is a parameter guaranteed by design.
30. Enables on-chip refresh and address counters.

READ CYCLE




Note:


1. tOFF is referenced from rising edge of **RAS** or **CAS**, whichever occurs last.

EARLY WRITE CYCLE (\overline{OE} = DON'T CARE)

READ WRITE CYCLE (LATE WRITE and READ-MODIFY-WRITE Cycles)




EDO-PAGE-MODE READ CYCLE




Note:

1. t_{PC} can be measured from falling edge of $\overline{\text{CAS}}$ to falling edge of $\overline{\text{CAS}}$, or from rising edge of $\overline{\text{CAS}}$ to rising edge of $\overline{\text{CAS}}$. Both measurements must meet the t_{PC} specifications.

EDO-PAGE-MODE EARLY-WRITE CYCLE




EDO-PAGE-MODE READ-WRITE CYCLE (LATE WRITE and READ-MODIFY WRITE Cycles)



**Note:**



1. t_{PC} can be measured from falling edge of \overline{CAS} to falling edge of \overline{CAS} , or from rising edge of \overline{CAS} to rising edge of \overline{CAS} . Both measurements must meet the t_{PC} specifications.

EDO-PAGE-MODE READ-EARLY-WRITE CYCLE (Pseudo READ-MODIFY WRITE)



AC WAVEFORMS

READ CYCLE (With \overline{WE} -Controlled Disable)RAS-ONLY REFRESH CYCLE (\overline{OE} , \overline{WE} = DON'T CARE)

CBR REFRESH CYCLE (Addresses; \overline{WE} , \overline{OE} = DON'T CARE)**HIDDEN REFRESH CYCLE⁽¹⁾** (\overline{WE} = HIGH; \overline{OE} = LOW)**Notes:**

1. A Hidden Refresh may also be performed after a Write Cycle. In this case, \overline{WE} = LOW and \overline{OE} = HIGH.
2. $tOFF$ is referenced from rising edge of \overline{RAS} or \overline{CAS} , whichever occurs last.

ORDERING INFORMATION : 3.3V**Commercial Range: 0°C to +70°C**

Speed(ns)	Order Part No.	Package
50	IS41LV16100B-50K	400-mil SOJ
	IS41LV16100B-50KL	400-mil SOJ, Lead-free
	IS41LV16100B-50T	400-mil TSOP (Type II)
	IS41LV16100B-50TL	400-mil TSOP (Type II), Lead-free
60	IS41LV16100B-60K	400-mil SOJ
	IS41LV16100B-60KL	400-mil SOJ, Lead-free
	IS41LV16100B-60T	400-mil TSOP (Type II)
	IS41LV16100B-60TL	400-mil TSOP (Type II), Lead-free



Industrial Range: -40°C to +85°C

Speed(ns)	Order Part No.	Package
50	IS41LV16100B-50KI	400-mil SOJ
	IS41LV16100B-50KLI	400-mil SOJ, Lead-free
	IS41LV16100B-50TI	400-mil TSOP (Type II)
	IS41LV16100B-50TLI	400-mil TSOP (Type II), Lead-free
60	IS41LV16100B-60KI	400-mil SOJ
	IS41LV16100B-60KLI	400-mil SOJ, Lead-free
	IS41LV16100B-60TI	400-mil TSOP (Type II)
	IS41LV16100B-60TLI	400-mil TSOP (Type II), Lead-free


PACKAGING INFORMATION

ISSI®

400-mil Plastic SOJ
Package Code: K



SEATING PLANE



Notes:

1. Controlling dimension: millimeters.
2. BSC = Basic lead spacing between centers.
3. Dimensions D and E1 do not include mold flash protrusions and should be measured from the bottom of the package.
4. Reference document: JEDEC MS-027.

Symbol	Millimeters		Inches		Millimeters		Inches		Millimeters		Inches	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
No. Leads (N)	28		32		36							
A	3.25	3.75	0.128	0.148	3.25	3.75	0.128	0.148	3.25	3.75	0.128	0.148
A1	0.64	—	0.025	—	0.64	—	0.025	—	0.64	—	0.025	—
A2	2.08	—	0.082	—	2.08	—	0.082	—	2.08	—	0.082	—
B	0.38	0.51	0.015	0.020	0.38	0.51	0.015	0.020	0.38	0.51	0.015	0.020
b	0.66	0.81	0.026	0.032	0.66	0.81	0.026	0.032	0.66	0.81	0.026	0.032
C	0.18	0.33	0.007	0.013	0.18	0.33	0.007	0.013	0.18	0.33	0.007	0.013
D	18.29	18.54	0.720	0.730	20.82	21.08	0.820	0.830	23.37	23.62	0.920	0.930
E	11.05	11.30	0.435	0.445	11.05	11.30	0.435	0.445	11.05	11.30	0.435	0.445
E1	10.03	10.29	0.395	0.405	10.03	10.29	0.395	0.405	10.03	10.29	0.395	0.405
E2	9.40 BSC		0.370 BSC		9.40 BSC		0.370 BSC		9.40 BSC		0.370 BSC	
e	1.27 BSC		0.050 BSC		1.27 BSC		0.050 BSC		1.27 BSC		0.050 BSC	

Copyright © 2003 Integrated Silicon Solution, Inc. All rights reserved. ISSI reserves the right to make changes to this specification and its products at any time without notice. ISSI assumes no liability arising out of the application or use of any information, products or services described herein. Customers are advised to obtain the latest version of this device specification before relying on any published information and before placing orders for products.

Integrated Silicon Solution, Inc. — www.issi.com — 1-800-379-4774


Rev. F
10/29/03

Symbol	Millimeters		Inches		Millimeters		Inches		Millimeters		Inches	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
No. Leads (N)	40		42		44							
A	3.25	3.75	0.128	0.148	3.25	3.75	0.128	0.148	3.25	3.75	0.128	0.148
A1	0.64	—	0.025	—	0.64	—	0.025	—	0.64	—	0.025	—
A2	2.08	—	0.082	—	2.08	—	0.082	—	2.08	—	0.082	—
B	0.38	0.51	0.015	0.020	0.38	0.51	0.015	0.020	0.38	0.51	0.015	0.020
b	0.66	0.81	0.026	0.032	0.66	0.81	0.026	0.032	0.66	0.81	0.026	0.032
C	0.18	0.33	0.007	0.013	0.18	0.33	0.007	0.013	0.18	0.33	0.007	0.013
D	25.91	26.16	1.020	1.030	27.18	27.43	1.070	1.080	28.45	28.70	1.120	1.130
E	11.05	11.30	0.435	0.445	11.05	11.30	0.435	0.445	11.05	11.30	0.435	0.445
E1	10.03	10.29	0.395	0.405	10.03	10.29	0.395	0.405	10.03	10.29	0.395	0.405
E2	9.40 BSC		0.370 BSC		9.40 BSC		0.370 BSC		9.40 BSC		0.370 BSC	
e	1.27 BSC		0.050 BSC		1.27 BSC		0.050 BSC		1.27 BSC		0.050 BSC	

PACKAGING INFORMATION


Plastic TSOP

Package Code: T (Type II)



Notes:

1. Controlling dimension: millimeters, unless otherwise specified.
2. BSC = Basic lead spacing between centers.
3. Dimensions D1 and E do not include mold flash protrusions and should be measured from the bottom of the package.
4. Formed leads shall be planar with respect to one another within 0.004 inches at the seating plane.



Plastic TSOP (T - Type II) (MS 25)

Symbol	Millimeters		Inches	
	Min	Max	Min	Max
Ref. Std.				
N	24/26			
A	1.20		0.0472	
A1	0.05	0.15	0.002	0.0059
b	0.30	0.51	0.012	0.0201
c	0.12	0.21	0.005	0.0083
D	17.01	17.27	0.670	0.6899
E ₁	7.49	7.75	0.295	0.3051
e	1.27	BSC	0.050	BSC
E	9.02	9.42	0.462	0.4701
L	0.40	0.60	0.016	0.0236
α	0°	5°	0°	5°

Plastic TSOP (T - Type II) (MS 24)

Symbol	Millimeters		Inches	
	Min	Max	Min	Max
Ref. Std.				
N	40/44			
A	1.20		0.0472	
A1	0.05	0.15	0.002	0.0059
b	0.30	0.45	0.012	0.0157
c	0.12	0.21	0.005	0.0083
D	18.31	18.51	0.721	0.7287
E ₁	10.06	10.26	0.396	0.4040
e	0.80	BSC	0.031	BSC
E	11.56	11.96	0.455	0.4709
L	0.40	0.60	0.016	0.0236
α	0°	8°	0°	8°

Plastic TSOP (T - Type II) (MS 24)

Symbol	Millimeters		Inches	
	Min	Max	Min	Max
Ref. Std.				
N	44/50			
A	1.20		0.0472	
A1	0.05	0.15	0.002	0.0059
b	0.30	0.45	0.012	0.0157
c	0.12	0.21	0.005	0.0083
D	20.85	21.05	0.821	0.8287
E ₁	10.06	10.26	0.396	0.4040
e	0.80	BSC	0.031	BSC
E	11.56	11.96	0.455	0.4709
L	0.40	0.60	0.016	0.0236
α	0°	8°	0°	8°