

LOC	DIST	REVISIONS					
AD	47	P	LTR	DESCRIPTION	DATE	DWN	APVD
			L	REVISED PER ECR-12-009821	14DEC2012	M.Y	A.C

POSITION A1-

$\phi 0.725 \pm 0.075$ —
PLATED THROUGH HOLE


0.54±0.05

⊕	0.20	(M)	N	P	(M)	R	(M)
---	------	-----	---	---	-----	---	-----

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN 2-12-99 T. SHUEY CHK 2-24-99 D. KOVALICK		 TE Connectivity	
DIMENSIONS: mm		TOLERANCES, UNLESS OTHERWISE SPECIFIED: 0 PLC ± — 1 PLC ± — 2 PLC ± 0.13 3 PLC ± — 4 PLC ± — ANGLES ± —		NAME APVD D. KOVALICK 2-24-99 PRODUCT SPEC — APPLICATION SPEC —	
MATERIAL 		FINISH — WEIGHT —		SIZE CAGE CODE DRAWING NO A1 00779 C-223614	
		CUSTOMER DRAWING		PIN ASSY,SIGNAL MODULE,Z-PACK 2mm FB, 2mm CENTERLINE, 4 ROW,120 POSN,PRESS FIT LEADS, WITH 2 LEVELS OF SEQUENCING	
				RESTRICTED TO — SCALE 4:1 SHEET 1 OF 2 REV L	

