

PRODUCT SPECIFICATION

PRODUCT: MULTILAYER CERAMIC CAPACITOR
TYPE : CHIP CAPACITOR

APPROVED BY CUSTOMER

PAN OVERSEAS ELECTRONIC CO., LTD.

TAIWAN HEAD OFFICE:

TEL: 02-25213252~5, 02-25634133

FAX: 02-25373069

TAIWAN FACTORY:

TEL: 06-6982143, 06-6982331

FAX: 06-6983400,(QA:06-6993898)

PAN OVERSEAS (GUANG ZHOU):

TEL: 86-20-82237476

FAX: 86-20-82237475

PAN OVERSEAS (KUN SHAN):

TEL: 86-512-57707888

FAX: 86-512-57711076


QUALITY ASSURANCE DEPARTMENT

APPROVED	CHECKED	PREPARED

1. SCOPE

This specification is applicable to Pan Overseas multilayer ceramic capacitors.

2.CODE CONSTRUCTION :




① Rated Voltage:

Code	Rated voltage	Code	Rated voltage	Code	Rated voltage	Code	Rated voltage	Code	Rated voltage
K	6.3V	T	25V	G	200V	D	630V	M3	3000V
N	10V	U	50V	H	250V	M	1000V	M4	4000V
B	16V	A	100V	C	500V	M2	2000V	M5	5000V

② Part Dimension :

Unit: mm

	Dimension					
	Length (L)	Width (W)	Thickness (T)	MB(Min)	G(Min)	
0402	1.0±0.05	0.5±0.05	0.5±0.05	0.10	0.30	6.3～50V
0603	1.6±0.1	0.8±0.1	0.8±0.1	0.20	0.40	6.3～250V
0805	2.0±0.2	1.25±0.1	1.40 max.	0.25	0.70	6.3～500V
1206	3.2±0.2	1.60±0.2	1.52 max.	0.25	1.40	6.3～1KV
1210	3.2±0.3	2.5±0.3	1.8 max.	0.25	1.40	6.3～1KV
1808	4.5±0.35	2.0±0.3	2.0 max.	0.25	2.15	6.3～5KV
1812	4.5±0.35	3.2±0.3	1.8 max.	0.25	2.15	16～5KV
2220	5.7±0.4	5.0±0.4	1.8 max.	0.25	3.30	16～5KV
2225	5.7±0.4	6.3±0.4	1.8 max.	0.25	3.30	16～5KV
3640	9.2±0.5	10.16±0.5	2.0 max.	0.50	2.70	16～5KV
5550	14.0±0.5	12.7±0.5	2.5 max.	0.50	10.5	16～5KV
8060	20.3±0.5	15.24±0.5	2.5 max.	0.50	16.8	16～5KV



PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 2

③ Temperature Characteristics Code:

Code	Temp. Coefficient	Operation Temp.	Capacitance Change
C	NP0 (Class I)	-55℃ ~ +125℃	0 ± 30 ppm/℃
R	X7R (Class II)	-55℃ ~ +125℃	± 15%
X	X5R (Class II)	-55℃ ~ +85℃	± 15%
F	Y5V (Class II)	-30℃ ~ +85℃	+22% ~ -82%
E	Z5U (Class II)	+10℃ ~ +85℃	+22% ~ -56%

④ Capacitance Code :

Code	Capacitance(pF)	Code	Capacitance(pF)
010	1 *	102	1 000 *
1R5	1.5	222	2 200 *
100	10 *	472	4 700 *
101	100 *	103	10000 *

⑤ Tolerance Code :

Code	Tolerance	Code	Tolerance
B	± 0.1pF	J	±5%
C	±0.25pF	K	±10%
D	±0.50pF	M	±20%
F	± 1%	Z	+80%/-20%
G	± 2%		

- PS: 1. * -- Two significant digits followed by no. of zeros
2. Temperature coefficient (T.C.) vs. Proper tolerance applied:
NPO: For all tolerance
X7R、X5R: K、M Tolerance
Y5V、Z5U: M、Z Tolerance

⑥ Termination Code :

Code	N
Termination Type	Nickel

⑦ Packaging Code :

Code	B	T
Packaging Type	Bulk	Tape & Reel

3. STANDARD TEST CONDITIONS :

Tests shall, unless otherwise specified, be carried out at 15 to 35℃ and RH 45 to 75%.


If any doubt and argument has been encounter in judgement, the final test shall be done at 25±2℃, RH45 to 55% and 860~1060mbar. (Based on JIS standard)

4. DISPOSITION

If question to the measuring result in judgement, take the capacitor under a specified temperature for 30 minutes at least before measurement.

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 3

5. STRUCTURE:



Ag / Pd SERIES :

NO	Specifications	Material	Termination Plating thickness
1	Ceramic dielectric	Ceramic	
2	Internal Electrode	Ag-Pd	
3	End Terminal	Ag layer	40 μ m min
4		Ni layer	1.5-3.5 μ m min
5		Sn-Pb layer or Sn layer	3-8 μ m min

BME SERIES :

NO	Specifications	Material	Termination Plating thickness
1	Ceramic dielectric	Ceramic	
2	Internal Electrode	Ni	
3	End Termination	Cu layer	40 μ m min
4		Ni layer	1.5-3.5 μ m min
5		Sn-Pb layer or Sn layer	3-8 μ m min

6. STORING CONDITION AND TERM

Recommends the storing of products within 6 months at temperature 15~35℃ and humidity 70%RH max. If the product stored over 6 months, please reconfirm its solderability before use.

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 4

7. PERFORMANCE:

NO.	Item	Performance	Test or Inspection method				
(1)	External Appearance	No defects which may affect performance.	Visual inspection & Dimension measurement				
(2)	Voltage Proof	Withstand test voltage without Insulation breakdown or other damage.	DC Tested voltage shall be applied for 1 ~ 5sec. Charge/discharge current shall not exceed 50 mA . (PS: Ra – Rated Voltage)				
			Rated voltage	DC Tested voltage			
				NPO	X7R/X5R	Y5V	
			≤200V	2.5Ra			
			250V	2.0Ra			
			500V/630V	1.5Ra			
			≥1KV	1.5Ra	1.25Ra	-----	
(3)	Insulation Resistance	NPO: 100,000MΩ Min. or R • C ≥ 1,000 Ω • F (Whichever is smaller) X7R, X5R, Y5V, Z5U: 10,000MΩ Min or R • C ≥ 1,000Ω • F (Whichever is smaller)	Apply DC tested voltage for 60± 5 minute. (PS: Ra – Rated Voltage)				
			Rated voltage		DC Tested voltage		
			<1KV		1.0 Ra		
			≥1KV		1KV		
(4)	Capacitance (Cap.)	Within the specified tolerance that refers on page 2	Measuring frequency: Z5U、Y5V、X7R、X5R : 1KHz± 50Hz ◦				
(5)	Dissipation Factor (D. F.)	NPO : ≥30pF : Q ≥ 1000 < 30pF : Q≥400+20C PS: C: Nominal Capacitance (pF) X7R、X5R、Y5V& Z5U:(Max. value)	NPO : >1000pF : 1KHz± 50Hz ◦ ≤1000pF : 1MHz± 100KHz				
			Measuring voltage: Z5U : 0.5 Vrms				
			NPO、X7R、X5R、Y5V : 1.0± 0.2 Vrms				
			T.C.	≥50V	25V	16V	≤10V
			X7R/X5R	2.5%	3.0%	3.5%	5.0%
			Z5U	4.0%	---	---	---
Y5V	5.0%	7.5%	9.0%	12.5%			



PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 5

NO.	Item		Performance			Test or Inspection method		
(6)	Temperature Characteristic of Capacitance		Temperatures Coefficient			The temperature coefficient is determined using the capacitance measured in step 3 as a reference. Test the specimen from step 1 through step 5, the capacitance shall be within the specified tolerance for the capacitance coefficient and capacitance change as left table.		
			T.C.	Operating Temperature	Capacitance Change(ΔC)			
			NPO	-55~+125℃	0±30(ppm/℃)			
			X7R	-55~+125℃	± 15%			
			X5R	-55~+85℃	± 15%	Step	Temperature(℃)	
			Y5V	-30~+85℃	+ 22%~— 82%	1	Base Temp.(25℃)± 2 °C	
			Z5U	+10~+85℃	+22%~-56%	2	Min. Operation Temp.± 2 °C	
						3	Base Temp.(25℃)± 2 °C	
(7)	Solderability		New solder to over 95% of termination			Completely soak both terminal electrodes in solder at specified temperature for 3±0.5 sec.: a. For Tin-Lead Sn/Pb) Termination product: 235±5℃ b. For Lead-free (Pure Sn) Termination product: 245±5℃		
(8)	Leaching		New solder to over 95% of termination			Completely soak both terminal electrodes in solder at 270±5℃ for 40±1 sec.		
(9)	Soldering to Heat	External appearance	No mechanical damage.			Completely immerse both terminations in solder at 270±5℃ for 10±3 sec.		
		Cap. change (ΔC/C)	NPO	±2.5% or ± 0.25 pF max. (Whichever is larger)				
			X7R/X5R	±7.5%		Leave the capacitors in ambient condition for 24± 2 hours before measurement.		
			Z5U	±20%				
			Y5V	±20%				
		D.F.	NPO: C ≥ 30pF : Q ≥ 1000 C < 30pF : Q ≥ 400+20*C PS: C: Nominal Capacitance (pF) X7R、X5R、Y5V & Z5U: (Max. value) T.C. ≤ 50V 25V 16V ≤ 10V					
			X7R/X5R	2.5%	3.0%	3.5%	5.0%	*Preconditioning : (only for Class 2): Perform a heat treatment at 150 +0-10℃ for one hour and then let sit for 24 ± 2 hours at room temperature. Perform the initial measurement.
			Z5U	4.0%	---	---	---	
			Y5V	5.0%	7.5%	9.0%	12.5%	
		I.R.	NPO: 100,000MΩ Min. or R · C ≥ 1,000 Ω · F (Whichever is smaller) X7R、X5R、Y5V、Z5U: 10,000MΩ Min or R · C ≥ 1,000Ω · F (Whichever is smaller)					

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 6

NO.	Item	Performance	Test or Inspection method
(10)	Humidity (Steady state) & Humidity load	External appearance	A. Humidity load: (Not apply for the product with rated voltage $\geq 250\text{V}$): Apply the rated voltage at temperature $40\pm 2^\circ\text{C}$ and humidity 90 to 95%RH for $1000+48/-0$ hours. Leave the capacitors in ambient condition for the following time before measurement. Class 1 : 1~2 hours. Class 2 : 24 ± 2 hours. * Charge / discharge current shall. not exceed 50 mA. * Preconditioning : (only for Class 2): Apply the rated DC voltage for 1hour at $40\pm 2^\circ\text{C}$. Remove and let sit for 48 ± 4 hours at room temperature. Perform initial measurement. B. Humidity (Steady state): The test procedure is same as that in Humidity load but only without rated voltage applied.
		Cap. change ($\Delta C/C$)	
		D.F.	
		I.R.	
(11)	Load Life	External appearance	Apply $2\times$ rated voltage at maximum operating temperature $\pm 2^\circ\text{C}$ for $1000+48/-0$ hours. Leave the capacitors in ambient condition for the following time before measurement. Class I: 1~2 hours Class II: 24 ± 2 hours * Charge / discharge current shall. not exceed 50 mA. * Preconditioning : (only for Class 2): Apply 200% of the rated DC voltage for 1 hour at the maximum operating temperature $\pm 3^\circ\text{C}$. Remove and let sit for 24 ± 2 hours at room temperature. Perform initial measurement.
		Cap. change ($\Delta C/C$)	
		D.F.	
		I.R.	

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 7

NO.	Item		Performance	Test or Inspection method																				
(12)	Vibration	External appearance	Without distinct damage	(Not apply for 0402 product) Solder the capacitors to the test jig as shown in figure below with IR-Reflow method. The capacitor shall be subjected to a simple harmonic motion with the entire frequency range, from 10 to 55 Hz and return to 10 Hz ,shall be transverse in 1 min. Amplitude(total excursion):1.5mm Amplitude tolerance:± 15% This motion shall be applied for a period of 2 hours in each of 3 mutually perpendicular directions (a total of 6 hours) 																				
		Cap. change (Δ C/C)	NPO: ±2.5% or ±0.25pF max. (Whichever is larger) X7R/ X5R: ± 7.5% Y5V 、 Z5U: ±20%																					
		D.F. or Q	NPO: C≥30pF : Q≥1000 C <30pF : Q≥400+20*C PS: C: Nominal Capacitance (pF) X7R 、 X5R 、 Y5V& Z5U : (Max. value) <table><tr><td>T.C.</td><td>≥ 50V</td><td>25V</td><td>16V</td><td>≤ 10V</td></tr><tr><td>X7R/ X5R</td><td>2.5%</td><td>3.0%</td><td>3.5%</td><td>5.0%</td></tr><tr><td>Z5U</td><td>4.0%</td><td>---</td><td>---</td><td>---</td></tr><tr><td>Y5V</td><td>5.0%</td><td>7.5%</td><td>9.0%</td><td>12.5%</td></tr></table>		T.C.	≥ 50V	25V	16V	≤ 10V	X7R/ X5R	2.5%	3.0%	3.5%	5.0%	Z5U	4.0%	---	---	---	Y5V	5.0%	7.5%	9.0%	12.5%
		T.C.	≥ 50V		25V	16V	≤ 10V																	
X7R/ X5R	2.5%	3.0%	3.5%	5.0%																				
Z5U	4.0%	---	---	---																				
Y5V	5.0%	7.5%	9.0%	12.5%																				
(13)	Deflection	External appearance	No cracking or marking defects shall occur																					
		Bending strength	Flexure ≥ 1 mm																					
		Cap. change (Δ C/C)	NPO: ±5% or±0.5pFmax. (Whichever is larger) X7R/ X5R: ±12.5% Y5V: ±30%																					
(14)	Temperature cycle	External appearance	No mechanical damage.	(Not apply for 0402 product) The capacitor shall be subject 5 cycles according to four heat treatments listed in the following table. Then Leave the capacitors in ambient condition for the following time before measurement. Class II: 2 ~ 24 hours <table><tr><th>Step</th><th>Temperature (°C)</th><th>Duration (min.)</th></tr><tr><td>1</td><td>Min. Operation Temp.±3</td><td>30±3</td></tr><tr><td>2</td><td>Room Temp. (25°C)</td><td>2 ~ 5</td></tr><tr><td>3</td><td>Max. Operation Temp.±3</td><td>30±3</td></tr><tr><td>4</td><td>Room Temp. (25°C)</td><td>2 ~ 5</td></tr></table> *Preconditioning : (only for Class 2): Perform a heat treatment at 150 +0-10°C for one hour and then let sit for 24±2 hours at room temperature. Perform the initial measurement.	Step	Temperature (°C)	Duration (min.)	1	Min. Operation Temp.±3	30±3	2	Room Temp. (25°C)	2 ~ 5	3	Max. Operation Temp.±3	30±3	4	Room Temp. (25°C)	2 ~ 5					
		Step	Temperature (°C)		Duration (min.)																			
		1	Min. Operation Temp.±3		30±3																			
		2	Room Temp. (25°C)		2 ~ 5																			
		3	Max. Operation Temp.±3		30±3																			
		4	Room Temp. (25°C)		2 ~ 5																			
		Cap. change (Δ C/C)	NPO: ±2.5% or ±0.25pFmax. (Whichever is larger) X7R/ X5R: ± 7.5% Y5V: ± 20%																					
		D.F.	NPO: C ≥ 30pF : Q ≥ 1000 C < 30pF : Q ≥ 400+20*C X7R 、 X5R Y5V& Z5U: (Max. value) <table><tr><td>T.C.</td><td>≥ 50V</td><td>25V</td><td>16V</td><td>≤ 10V</td></tr><tr><td>X7R/ X5R</td><td>2.5%</td><td>3.0%</td><td>3.5%</td><td>5.0%</td></tr><tr><td>Z5U</td><td>4.0%</td><td>---</td><td>---</td><td>---</td></tr><tr><td>Y5V</td><td>5.0%</td><td>7.5%</td><td>9.0%</td><td>12.5%</td></tr></table>		T.C.	≥ 50V	25V	16V	≤ 10V	X7R/ X5R	2.5%	3.0%	3.5%	5.0%	Z5U	4.0%	---	---	---	Y5V	5.0%	7.5%	9.0%	12.5%
		T.C.	≥ 50V		25V	16V	≤ 10V																	
		X7R/ X5R	2.5%		3.0%	3.5%	5.0%																	
		Z5U	4.0%		---	---	---																	
		Y5V	5.0%		7.5%	9.0%	12.5%																	
	I.R.	10000MΩ min. or 500Ω *F (Whichever is smaller)																						

Capacitance Range Table (Class D)																									Unit: pF			
SIZE		0402	0603		0805				1206					1210					1808									
T. C.		NPO																										
Rated Voltage(VDC)	Code	50	200/250	100	50	500	200/250	100	50	1K	630	500	200/250	100	50	25	1K	630	500	200/500	100	3K	2K	1K	630			
0.5	0R5																											
0.75	0R75																											
1	1R																											
1.5	1R5																											
2	020																											
3	030																											
3.9	3R9																											
4	040																											
5	050																											
6	060																											
7	070																											
8	080																											
9	090																											
10	100																											
11	110																											
12	120																											
13	130																											
15	150																											
16	160																											
18	180																											
20	200																											
22	220																											
24	240																											
27	270																											
30	300																											
33	330																											
36	360																											
39	390																											
43	430																											
47	470																											
51	510																											
56	560																											
62	620																											
68	680																											
75	750																											
82	820																											
91	910																											
100	101																											
110	111																											
120	121																											
130	131																											
150	151																											
160	161																											
180	181																											
200	201																											
220	221																											
240	241																											
270	271																											
300	301																											
330	331																											
360	361																											
390	391																											
430	431																											
470	471																											
510	511																											
560	561																											
620	621																											
680	681																											
750	751																											
820	821																											
910	911																											
1000	102																											
1100	112																											
1200	122																											
1300	132																											
1500	152																											
1600	162																											
1800	182																											
2000	202																											
2200	222																											
2400	242																											
2700	272																											
3000	302																											
3300	332																											
3600	362																											
3900	392																											
4300	432																											
4700	472																											
5100	512																											
5600	562																											
6200	622																											
6800	682																											
7500	752																											
8200	822																											
9100	912																											
10000	103																											

Capacitance Range Table (Class I)

Unit: pF

SIZE		1812								2220								2225								3640							
T. C.		NPO																															
Rated Voltage VDC	Code	3K	2K	1K	630	500	200/250	100	3K	2K	1K	630	500	200/250	100	3K	2K	1K	630	500	200/250	100	5K	4K	3K	2K	1K	500					
10	100																																
11	110																																
12	120																																
13	130																																
15	150																																
16	160																																
18	180																																
20	200																																
22	220																																
24	240																																
27	270																																
30	300																																
33	330																																
36	360																																
39	390																																
43	430																																
47	470																																
51	510																																
56	560																																
62	620																																
68	680																																
75	750																																
82	820																																
91	910																																
100	101																																
110	111																																
120	121																																
130	131																																
150	151																																
160	161																																
180	181																																
200	201																																
220	221																																
240	241																																
270	271																																
300	301																																
330	331																																
360	361																																
390	391																																
430	431																																
470	471																																
510	511																																
560	561																																
620	621																																
680	681																																
750	751																																
820	821																																
910	911																																
1000	102																																
1100	112																																
1200	122																																
1300	132																																
1500	152																																
1600	162																																
1800	182																																
2000	202																																
2200	222																																
2400	242																																
2700	272																																
3000	302																																
3300	332																																
3600	362																																
3900	392																																
4300	432																																
4700	472																																
5100	512																																
5600	562																																
6200	622																																
6800	682																																
7500	752																																
8200	822																																
9100	912																																
10000	103																																
12000	123																																
15000	153																																
18000	183																																
22000	223																																
27000	273																																
33000	333																																
39000	393																																
47000	473																																
56000	563																																

Capacitance Range Table (Class I)

Unit: pF

SIZE	5550						8060																
T. C.	NPO																						
Rated Voltage(VDC)	Code	5K	4K	3K	2K	1K	500	5K	4K	3K	2K	1K	500										
10	100																						
11	110																						
12	120																						
13	130																						
15	150																						
16	160																						
18	180																						
20	200																						
22	220																						
24	240																						
27	270																						
30	300																						
33	330																						
36	360																						
39	390																						
43	430																						
47	470																						
51	510																						
56	560																						
62	620																						
68	680																						
75	750																						
82	820																						
91	910																						
100	101																						
110	111																						
120	121																						
130	131																						
150	151																						
160	161																						
180	181																						
200	201																						
220	221																						
240	241																						
270	271																						
300	301																						
330	331																						
360	361																						
390	391																						
430	431																						
470	471																						
510	511																						
560	561																						
620	621																						
680	681																						
750	751																						
820	821																						
910	911																						
1000	102																						
1100	112																						
1200	122																						
1300	132																						
1500	152																						
1600	162																						
1800	182																						
2000	202																						
2200	222																						
2400	242																						
2700	272																						
3000	302																						
3300	332																						
3600	362																						
3900	392																						
4300	432																						
4700	472																						
5100	512																						
5600	562																						
6200	622																						
6800	682																						
7500	752																						
8200	822																						
9100	912																						
10000	103																						
12000	123																						
15000	153																						
18000	183																						
22000	223																						
27000	273																						
33000	333																						
39000	393																						
47000	473																						
56000	563																						
68000	683																						
100000	104																						
120000	124																						
150000	154																						
180000	184																						

Capacitance Range Table (Class II)																								Unit: pF
SIZE	0402												0603											
T. C.	X7R			X5R					Y5V				X7R					X5R					Z5U	
Rated Voltage(VDC)	Code	50	25	16	50	25	16	10	6.3	50	25	16	200/250	100	50	25	16	50	25	16	10	6.3	50	
100	101																							
150	151																							
180	181																							
220	221																							
270	271																							
330	331																							
390	391																							
470	471																							
560	561																							
680	681																							
820	821																							
1000	102																							
1200	122																							
1500	152																							
1800	182																							
2200	222																							
2700	272																							
3300	332																							
3900	392																							
4700	472																							
5600	562																							
6800	682																							
8200	822																							
10000	103																							
12000	123																							
15000	153																							
18000	183																							
22000	223																							
27000	273																							
33000	333																							
39000	393																							
47000	473																							
56000	563																							
68000	683																							
100000	104																							
120000	124																							
150000	154																							
180000	184																							
220000	224																							
270000	274																							
330000	334																							
390000	394																							
470000	474																							
560000	564																							
680000	684																							
820000	824																							
1000000	105																							
1200000	125																							
1500000	155																							
1800000	185																							
2200000	225																							
2700000	275																							
3300000	335																							
3900000	395																							
4700000	475																							
5600000	565																							
6800000	685																							
8200000	825																							
10000000	106																							

Capacitance Range Table (Class II)

Unit: pF

SIZE		0603				0805																
T. C.		Y5V				X7R					X5R					Z5U		Y5V				
Rated Voltage(VDC)	Code	50	25	16	10	200/250	100	50	25	16	50	25	16	10	6.3	50	25	50	25	16	10	
100	101																					
150	151																					
180	181																					
220	221																					
270	271																					
330	331																					
390	391																					
470	471																					
560	561																					
680	681																					
820	821																					
1000	102																					
1200	122																					
1500	152																					
1800	182																					
2200	222																					
2700	272																					
3300	332																					
3900	392																					
4700	472																					
5600	562																					
6800	682																					
8200	822																					
10000	103																					
12000	123																					
15000	153																					
18000	183																					
22000	223																					
27000	273																					
33000	333																					
39000	393																					
47000	473																					
56000	563																					
68000	683																					
100000	104																					
120000	124																					
150000	154																					
180000	184																					
220000	224																					
270000	274																					
330000	334																					
390000	394																					
470000	474																					
560000	564																					
680000	684																					
820000	824																					
1000000	105																					
1200000	125																					
1500000	155																					
1800000	185																					
2200000	225																					
2700000	275																					
3300000	335																					
3900000	395																					
4700000	475																					
5600000	565																					
6800000	685																					
8200000	825																					
10000000	106																					

Capacitance Range Table (Class II)

Unit: pF

SIZE		1206																		1210						
T. C.		X7R								X5R						Z5U	Y5V					X7R				
Rated Voltage(VDC)	Code	1K	630	500	200/250	100	50	25	16	250	50	25	16	10	6.3	50	50	25	16	10	1K	630	500	200/250	100	
100	101	1			1	1																				
150	151	1			1	1																				
180	181	1	1		1	1																				
220	221	1		1	1	1															1					
270	271	1			1	1	1	1	1																	
330	331	1			1	1	1	1	1												1					
390	391	1			1	1	1	1	1												1	1	1			
470	471	1			1	1	1	1	1												1					
560	561	1			1	1	1	1	1												1					
680	681	1			1	1	1	1	1												1					
820	821	1			1	1	1	1	1												1					
1000	102	1			1	1	1	1	1							1	1								1	
1200	122	1			1	1	1	1	1							1	1								1	
1500	152	1			1	1	1	1	1							1	1								1	
1800	182	1			1	1	1	1	1							1	1								1	
2200	222	1	1		1	1	1	1	1							1	1								1	
2700	272	1			1	1	1	1	1							1	1								1	
3300	332	1			1	1	1	1	1							1	1								1	
3900	392	1			1	1	1	1	1							1	1								1	
4700	472	1			1	1	1	1	1							1	1								1	
5600	562	1			1	1	1	1	1							1	1								1	
6800	682	1			1	1	1	1	1							1	1								1	
8200	822	1			1	1	1	1	1							1	1								1	
10000	103	1			1	1	1	1	1							1	1							1	1	
12000	123	1			1	1	1	1	1							1	1							1	1	
15000	153	1			1	1	1	1	1							1	1							1	1	
18000	183	1			1	1	1	1	1							1	1							1	1	
22000	223	1			1	1	1	1	1							1	1							1	1	
27000	273	1			1	1	1	1	1							1	1							1	1	
33000	333	1			1	1	1	1	1							1	1							1	1	
39000	393	1			1	1	1	1	1							1	1							1	1	
47000	473	1			1	1	1	1	1							1	1							1	1	
56000	563	1			1	1	1	1	1							1	1							1	1	
68000	683	1			1	1	1	1	1							1	1							1	1	
100000	104	1			1	1	1	1	1	1	1	1	1	1	1	1	1							1	1	
120000	124	1			1	1	1	1	1	1	1	1	1	1	1	1	1							1	1	
150000	154	1			1	1	1	1	1	1	1	1	1	1	1	1	1							1	1	
180000	184	1			1	1	1	1	1	1	1	1	1	1	1	1	1							1	1	
220000	224	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
270000	274	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
330000	334	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
390000	394	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
470000	474	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
560000	564	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
680000	684	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
820000	824	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
1000000	105	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
1200000	125	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
1500000	155	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
1800000	185	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
2200000	225	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
2700000	275	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
3300000	335	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
3900000	395	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
4700000	475	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
5600000	565	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
6800000	685	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
8200000	825	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
10000000	106	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	
22000000	226	1			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1				1	1	

Capacitance Range Table (Class II)

Unit: pF

SIZE		1210				1808				1812								2220									
T. C.		X5R				X7R				X7R						X5R				X7R							
Rated Voltage(VDC)	Code	25	16	10	6.3	3K	2K	1K	630	3K	2K	1K	630	500	200/250	100	25	16	10	6.3	3K	2K	1K	630	500	200/250	100
100	101																										
150	151																										
180	181																										
220	221																										
270	271																										
330	331																										
390	391																										
470	471																										
560	561																										
680	681																										
820	821																										
1000	102																										
1200	122																										
1500	152																										
1800	182																										
2200	222																										
2700	272																										
3300	332																										
3900	392																										
4700	472																										
5600	562																										
6800	682																										
8200	822																										
10000	103																										
12000	123																										
15000	153																										
18000	183																										
22000	223																										
27000	273																										
33000	333																										
39000	393																										
47000	473																										
56000	563																										
68000	683																										
100000	104																										
120000	124																										
150000	154																										
180000	184																										
220000	224																										
270000	274																										
330000	334																										
390000	394																										
470000	474																										
560000	564																										
680000	684																										
820000	824																										
1000000	105																										
1200000	125																										
1500000	155																										
1800000	185																										
2200000	225																										
2700000	275																										
3300000	335																										
3900000	395																										
4700000	475																										
5600000	565																										
6800000	685																										
8200000	825																										
10000000	106																										
22000000	226																										
47000000	476																										
100000000	107																										


Capacitance Range Table (Class II)																									Unit: pF	
SIZE		2225							3640					5550					8060							
T. C.		X7R																								
Rated Voltage(VDC)	Code	3K	2K	1K	630	500	200/250	100	4K	3K	2K	1K	500	5K	4K	3K	2K	1K	500	5K	4K	3K	2K	1K	500	
100	101																									
150	151																									
180	181																									
220	221																									
270	271																									
330	331																									
390	391																									
470	471																									
560	561																									
680	681																									
820	821																									
1000	102																									
1200	122																									
1500	152																									
1800	182																									
2200	222																									
2700	272																									
3300	332																									
3900	392																									
4700	472																									
5600	562																									
6800	682																									
8200	822																									
10000	103																									
12000	123																									
15000	153																									
18000	183																									
22000	223																									
27000	273																									
33000	333																									
39000	393																									
47000	473																									
56000	563																									
68000	683																									
100000	104																									
120000	124																									
150000	154																									
180000	184																									
220000	224																									
270000	274																									
330000	334																									
390000	394																									
470000	474																									
560000	564																									
680000	684																									
820000	824																									
1000000	105																									
1200000	125																									
1500000	155																									
1800000	185																									
2200000	225																									
2700000	275																									
3300000	335																									
3900000	395																									
4700000	475																									
5600000	565																									
6800000	685																									
8200000	825																									
10000000	106																									

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 16


10. Packaging :

(1)Reel specification: Standard reel diameter is 7" and 13"


Paper Tape



Plastic Tape




Packed Chips



(2) Quantity for each reel


Chip Size		0402	0603	0805	1206	1210	1808	1812	2220	2225	3640	5550	8060
Reel Size	7"	10000	4000	3000	2500	2000	2000	1000	1000	1000	N/A	N/A	N/A
	13"	50000	16000	12000	10000	8000	8000	4000	4000	4000	N/A	N/A	N/A
Tape wide(mm)		8	8	8	8/12	8/12	8/12	8/12	8/12	8/12	N/A	N/A	N/A

(3) Dimension of Reel:



Dimension		A	B	C	D	E	T	W
Reel Size	7"	178±2	50 min.	13±0.5	21±0.8	2.0±0.5	12±2.0	10±1.5
	13"	330 max					18.4max.	12.4 +1.5/-0

(4) Tape Dimension :



Unit: inch (mm)

Symbol	Description	8 mm tape	12 mm tape
W	Wide of Tape	8(0.135)±0.2(0.008)	12(0.472)±0.2(0.008)
F	Distance between drive hole center and cavity center	3.5(0.138)±0.05(0.002)	5.5(0.213)±0.05(0.002)
E	Distance between drive hole center and tape edge	1.75(0.069)±0.1(0.004)	
P ₁	Distance between cavity center	4(0.156)±0.1(0.004)	8(0.135)±0.1(0.004)
P ₂	Axial distance between drive hole center and cavity center	2(0.079)±0.05(0.002)	
P ₀	Axial distance between drive hole	4(0.156)±0.1(0.004)	
D ₀	Drive hole diameter	1.5(0.059)±0.1(0.004)-0	
t ₁	Base tape thickness	0.3(0.012)±0.1(0.004)	0.4(0.016)±0.1(0.004)
t ₂	Total tape thickness	0.1(0.004) max.	


	0402	0603	0805	1206	1210 and above
A ₀ (Wide of Cavity)	0.65±0.1	1.05±0.1	1.55±0.15	2.0±0.2	Dependent on chip size to minimize rotation
B ₀ (Length of Cavity)	1.15±0.1	1.85±0.1	2.3±0.15	3.6±0.2	

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 18

(5) Peeling off strength of Top tape

The angle between top tape and base tape is $165 \sim 180^\circ$, and the peeling speed is control in 300 ± 10 mm/min, and the peeling force as follows:

- 8mm tape or base tape : 10 ~ 100 grams (0.1~1.0N)
- 12mm tape or base tape: 10 ~ 130 grams (0.1~ 1.3N)



PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 19
<u>PRECAUTION FOR HANDLING</u> The multi-layer ceramic chip capacitors, may fall in a short circuit mode or in an open-circuit mode when subjected to severe conditions of electrical, environmental and/or mechanical stress beyond the specified “Ratings” and specified “Condition” in the Catalog and the Specifications, resulting in burnout, flaming or glowing in the worst case. So some common sense of application by customer is necessary. <u>Here the following article are some key points that need to take attention in application for customer reference only:</u> 1. Operating Conditions and Circuit Design 1.1 Operating temperature range The specified “Operating Temperature Range” in the catalog is absolute maximum and minimum temperature rating. So in any case, each the Capacitor shall be operated within the specified “Operating Temperature Range”. 1.2 Design of Voltage Applications The capacitors shall not be operated exceeding the specified “Rated Voltage” in the catalog. If voltage ratings are exceeded the Capacitors could result in failure of damage. In case of application of DC and AC voltage to the capacitors, the designed peak voltage shall be within the specified “Rated Voltage”. 1.3 Charging and Discharging Current The capacitors shall not be operated beyond the specified “Maximum Charging / Discharging Current Rated” in the specification, Application to a low impedance circuit such as a “secondary power circuit” are not recommended for safety. 1.4 Temperature Rise by Dielectric Loss of the capacitor The “Operating Temperature Range” mentioned above shall include a maximum surface temperature rise of 20°C, which is caused by the Dielectric loss of the Capacitor and applied electrical stress (such as voltage, frequency and wave form etc.) It is recommended to measure and check “Surface temperature of the Capacitor” in your equipment at your estimated / designed maximum ambient temperature.		

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 20

1.5 Restriction on Environmental Conditions

The Capacitors shall not be operated and / or stored under following environmental conditions:

- (a) To be exposed directly to water or salt water.
- (b) To be exposed directly to sunlight.
- (c) Under conditions of dew formation.
- (d) Under conditions of corrosive atmosphere such as hydrogen sulfas, sulfurous acid, chlorine, or ammonia etc.
- (e) Under severe condition of vibrations or shock beyond the specified conditions in the Specifications.

1.6 Secular change in Capacitance

- (1) Peculiar characteristics of “Secular Changes in Capacitance” are observed in the Capacitors (Class 2 High Dielectric Constant Temperature Characteristics “X7R” and “Y5V”. The “secular change” shall be considered in your circuit design.
- (2) The Capacitance change, due to the individual characteristics of ceramic dielectric materials applied, can be recovered to the each initial values at shipping by a heat treatment (140 to 150℃ for 1 hour).

2. Design of Printed Circuit Board

2.1 Selection of Printed Circuit Boards

When the Capacitors are mounted and soldered on an “Aluminum’s Substrate has influences on Capacitor’s reliability against “Temperatures Cycles” and “Heat shock” because of difference of thermal expansion dose not deterioration the characteristics of the Capacitors.

There are some thermal expansion factor for different kink of PC board material as follows:

PC board material	Thermal expansion factor (mm/℃)
Glass epoxy	1.4×10 ⁻⁵
Paper phenol	2.2×10 ⁻⁵
Composite	2.2×10 ⁻⁵
Alumina	6.5×10 ⁻⁶

2.2 Design of Land Pattern

(1) Recommended Dimensions of Lands. As shown in Table 1 and Fig 1.

Note : * Too large land required excess amount of solder.

** The Dimensions shall be symmetrical.

Fig.1 Recommended Land Dimensions :




Table 1: Recommended Land Dimensions in mm.


Size	Chip Dimension		Land Dimension		
	L	W	a	b	c
0402	1.0	0.5	0.30~0.50	0.35~0.45	0.40~0.60
0603	1.6	0.8	0.70~1.00	0.80~1.00	0.60~0.80
0805	2.0	1.25	1.00~1.30	1.00~1.20	0.80~1.10
1206	3.2	1.6	2.10~2.50	1.10~1.30	1.10~1.30
1210	3.2	2.5	2.10~2.50	1.10~1.30	1.90~2.30
1808	4.5	2.0	2.50~3.20	1.80~2.30	1.50~1.80
1812	4.5	3.2	2.50~3.20	1.80~2.30	2.60~3.00
2220	5.7	5.0	4.20~4.70	2.00~2.50	4.20~4.70

(2) Recommend amount of solder:

Recommended amount of solder: As shown in Fig 2.

Excess amount of solder gives large mechanical stresses to the capacitors / Components.

Fig 2: Recommended amount of solder










PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 22
2.3 Component Layout When placing / mounting the capacitors / components near an area which is apt to bend or a grid groove on the PC board. It is advisable to have both electrodes subjected to uniform stresses, or to position the component electrodes at right angles to the grid groove or bending line. Fig 3 : Component Layout 		
Uneven mounting density O : Proper ×: Improper Probability at which the chip capacitor is broken by the stress on PC board break $A > B = C > D > E$		
2.4 Mounting Density and Spaces Placements in too narrow spaces between components may cause “Solder Bridges” during soldering. The minimum space between components shall be 0.5mm in view of the positioning tolerances of the mounting machines and the dimensional tolerances of the components and PC boards.		
2.5 Applications of Solder Resist: Application of Solder Resist are effective to prevent solder bridges and to control amounts of solder on PC boards (As shown in Table 2).		

Table 2: Application Examples of Solder Resist

	Recommended Application Examples	Examples of Solder Bridges
Narrow Spacing between Chip Components		
Radial Components are directly connected to Chip Components		
Common lands are close to Chip Components		

3. Precautions for Assembly

3.1 Adhesives for Mounting

(1) Selection of adhesives


- The viscosity of a adhesive for mountings shall be such that the adhesive dose not flow off on the land during it's curing.
- If the adhesive is too low in its viscosity, mounted components may be out of alignment after or during soldering.
- The adhesives shall not be corrosive of chemically active to the mounted components and the PC boards.
- The amount of adhesive shall be such that the adhesive dose not flow off or be out of alignment.
- Adhesives for mountings can be cured by ultraviolet or infrared radiation. In order to prevent the terminal electrodes of the Capacitors The curing shall be done at conditions of 180°C max, for 2 minutes max.

3.2 Chip Mounting consideration


In mounting the Capacitors / components on a printed circuit board, any bending and expanding force against them shall be kept minimum to prevent them from being damaged or cracked.

Following precautions and recommendation shall be observed carefully in the process:

- (1) Maximum stroke of the vacuum nozzle shall be adjusted so that the pushing force to the printed circuit board shall be limited to a static of 1 to 3 N (100 to 300 gf) (See Fig.4).
- (2) Maximum stroke of the nozzle shall be adjusted so that the maximum bending of printed circuit board dose not exceeded 0.5mm (See Fig.4)



- (3) The printed circuit board shall be supported by means of adequate supporting pins as shown in Fig.5-(b)



PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 25

3.3 Soldering Flux and Solder

(1) Solder Flux:

- a. The content of halogen in the soldering shall be 0.2 wt% or less.
- b. Rosin-based and non-activated soldering flux is recommended.

(2) Water soluble type Soldering Flux:

In case of water soluble type soldering flux being applied, the flux residue on the surface of PC boards may have influences on the reliability of the components and cause deterioration and failures of them.

(3) Solder:

An eutectic solder (Sn63 : Pb37) is recommended.

3.4 Soldering

Since a multilayer ceramic chip capacitor comes into direct contact with melted solder during soldering. It is exposed to potentially damaging mechanical stress caused by the sudden temperature change. The capacitor may also be subject to silver migration, and to contamination by the flux. Because of these factors, soldering technique is critical. Adhere to the following guidelines.

3.4.1 Hand soldering:

In hand soldering of the Capacitors, large temperature gradient between preheated the capacitors and the tip of soldering iron may cause electrical failures and mechanical damages such as cracking or breaking of the devices. The soldering shall be carefully controlled and carried out so that the temperature gradient is kept minimum with following recommended conditions for hand soldering.

Recommended Soldering Conditions:

(1) Solder:

φ 1mm Thread eutectic solder (Sn63:Pb37) with soldering flux *in the core.

*Rosin-based, and non-activated flux is recommended.

(2) Preheating:

The capacitors shall be preheated so that "Temperature Gradient" between the devices and the tip of soldering iron is 150°C or below.

(3) Soldering iron:

Rated Power of 20W Max with 3mm soldering tip in diameter.

Temperature of soldering iron tip: 300°C max.

(The required amount of solder shall be melted in advance on the soldering tip.)


(4) Cooling:

After soldering, the Capacitors shall cooled gradually at room ambient temperature.

3.4.2.Flow Soldering

In flow soldering process, abnormal and thermal and mechanical stresses, caused by “Temperature Gradient” between the mounted Capacitors, resulting in failures and damages of the capacitors. So it is essential that the soldering process shall controlled to the following recommended conditions and precautions.(See Fig.6)

Fig.6. Recommended Soldering Temperature Time Profile (Flow soldering)



(1) Application of Flux.

The soldering flux(3.3) shall applied to the mounted Capacitors thinly and uniformly by forming method.

(2)Preheating:

The mounted Capacitors / Components shall be preheated sufficiently so that the “Temperature Gradient” between the Capacitors / Components and the melted solder shall be 150°C or below.

(3)Immersion to Soldering Bath:

The Capacitors shall be immersed into a soldering bath of 240 to 250°C for 3 to 5 seconds.

(4)Cooling:

The Capacitors shall be cooled gradually to room ambient temperature with the cooling temperature rates of 8°C/s max. from 250°C to 170°C and 4°C/s max. from 170°C to 130°C.

(5)Flux Cleaning:

When the Capacitors are immersed into cleaning solvent, it shall be confirmed that the surface temperature of devices do not exceed 100°C (See 3.5).

3.4.3 Reflow soldering.

In reflow soldering process, the mounted Capacitors / Components are generally heated and Soldering by a thermal conduction system such as an “Infrared radiation and hot blast soldering system” or a “Vapor Phase Soldering System(VPS)”, Large temperature gradients such as a rapid heating and cooling in the process may cause electrical and mechanical damages if the device. It is essential that the soldering process shall be controlled by following recommended conditions and precaution.(See Fig.7)

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 27

3.4.3.1 For Tin-Lead (Sn/Pb) Termination component:

(1)Preheating 1.

The mounted Capacitors / Components shall be preheated sufficiently, for 60 to 90 seconds so that the surface temperature of them to be 140 to 150°C.

(2)Preheating 2.

After “Preheating 1”, the mounted Capacitors / Components shall be the elevated temperature of 150 to 200°C for 2 to 6 Seconds.

(3)Soldering:

The mounted Capacitors / Components shall be heated under the specified heating conditions (200 to 240 to 200°C for total 20 to 40 seconds, See Fig.7) and shall be soldered at the maximum temperature of 240°C for 10 seconds of less.

(4)Cooling:

After the soldering, the mounted Capacitors / Components shall be gradually cooled to room ambient temperature for preventing mechanical damages such as cracking of the devices.

(5)Flux Cleaning:

When the mounted Capacitors / Components are immersed into cleaning solvent, it shall be confirmed the surfaces temperatures of them do not exceeding 100°C.

Note: If the mounted Capacitors / Components are partially heated in the soldering process, the devices may be separated form the printed circuit board by the surface tension of partially melted solder, and stand up like a “Tomb Stone”.




Fig.7. Recommended Soldering Temperature Time Profile for Tin-Lead component
(Reflow Soldering)

3.4.3.2 For Lead-free (Pure Tin plating termination) Termination component:

Essentially, the soldering temperature for Lead-free component is a little higher than that for Tin-Lead component, but need to take consideration of the thermal effect for all other components mounting on board at the same time. The below picture is a recommended soldering profile for Lead-free component :




Fig.8 Recommended Soldering Temperature Time Profile for Lead-free component (Reflow Soldering)

3.5 Post soldering Cleaning

(1)Residues of corrosive soldering fluxes on the PC board after cleaning may greatly have influences on the electrical characteristics and the reliability, (such as humidity resistance) of the Capacitors, which have been mounted on the board. It shall be confirmed that the characteristic and reliability at the devices are no effected by applied cleaning conditions.

(2)Solubility of alternative cleaning solvent such as alcohol etc., is inferior to that of Freon cleaning solvent in the flux cleaning.

So in case of alternative cleaning solvents, fresh cleaning solvent shall be used, and sufficient rinsing and drying shall carried out.

(3)When an ultrasonic cleaning is applied to the mounted Capacitors on PC board, following conditions energy and the recommended for preventing failures or damages of the devices due to the large vibration energy and the resonant caused by the ultrasonic waves.

Frequency :29KHz max.

Radiated Power :20 W/liter max.

Period :5 minutes max.

PAN OVERSEAS ELECTRONIC CO., LTD		M01-00-E-03
SPECIFICATION OF MULTILAYER CERAMIC CHIP CAPACITOR	Ver: 3	Page: 29

3.6 Process Inspection

When the mounted printed circuit are inspected with measuring terminal pins, abnormal and excess mechanical stresses shall not be applied to the PC board mounted components, to prevent failure or damages of the devices.

- (1) The mounted PC board shall be supported a same adequate supporting pins prevent their banding.
- (2) It shall be confirmed that the measuring pin have the right tip in shape, equal in height and are set in the tight positions.
- (3) The amount of adhesive shall be such that the adhesive dose flow off or be out of alignment.

3.7 Protective Coating

When the surface of a printed board on which the Capacitors has been mounted is coated with Resin to protect against moisture and dust, it shall be confirmed that the protective coat dose not have influences on reliability of the capacitors in the actual equipment.

- (1) Coating materials, such as being corrosive and chemically active, shall not be applied to the capacitors and other components.
- (2) Coating materials with a large expansively shall not be applied to the Capacitors for preventing failures or damages (such as cracking) of the devices in the curing process.

3.8 Dividing / Breaking of PC boards

- (1) Abnormal and excessive mechanical stresses, such as bending or expanding force on the components on the printed circuit board, shall be kept minimum in the dividing / breaking.
- (2) Dividing / Breaking of the PC board shall be done carefully at moderate speed using a Jig boards from mechanical damages.

3.9 Long Term Storage

The Capacitors shall not be stored under severe conditions of high temperatures and high humidity. Store them under 40°C max. and 75%RH max. Use them within 6 months and check the solderability before use.