

**Device markers**  
**CC 15/45 K MC NE GE**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



The **CC 15/45 MC** is ideal for the 45-mm wide contactor relays and motor circuit breakers. It provides a clean, large-area identification in the electrical cabinet. Can be mounted either as a self-adhesive variant or using a CC-rail 1000 tag rail

**General ordering data**

|            |                                                                     |
|------------|---------------------------------------------------------------------|
| Order No.  | <a href="#">1111260000</a>                                          |
| Type       | CC 15/45 K MC NE GE                                                 |
| Version    | Device markers, MultiCard, 15 x 45 mm, Polyamide 66, Colour: Yellow |
| GTIN (EAN) | 4032248887873                                                       |
| Qty.       | 40 pc(s).                                                           |

**Device markers**  
**CC 15/45 K MC NE GE**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|        |        |            |        |
|--------|--------|------------|--------|
| Length | 15 mm  | Width      | 45 mm  |
| Height | 1.2 mm | Net weight | 2.89 g |

**Markings**

|                                                |                            |                                   |              |
|------------------------------------------------|----------------------------|-----------------------------------|--------------|
| Adhesive                                       | Double-sided adhesive tape | Cadmium                           | No           |
| Can be labelled with thermal transfer printers | No                         | Can be printed with plotter       | Yes          |
| Can be written with dot-matrix printer         | No                         | Can be written with laser printer | No           |
| Colour                                         | Yellow                     | Conductor O.D.                    |              |
| Halogen                                        | No                         | Material                          | Polyamide 66 |
| Material colour according to resistance code   | 4                          | Operating temperature range, max. | 60 °C        |
| Operating temperature range, min.              | -40 °C                     | Pin can be written (STI)          | Yes          |
| PrintJet                                       | Yes                        | Silicone                          | No           |
| Speed marking laser                            | No                         | UL 94 flammability rating         | V-2          |
| Version                                        | Self-adhesive              |                                   |              |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 2.0   | EC001288    | ETIM 3.0   | EC001288    |
| UNSPSC     | 30-21-18-01 | eClass 4.1 | 24-19-02-18 |
| eClass 5.1 | 27-14-91-29 | eClass 6.2 | 27-14-91-29 |
| eClass 7.1 | 27-14-91-29 |            |             |

**Product information**

|                        |                                         |
|------------------------|-----------------------------------------|
| Description of article | MultiCard markers for labelling devices |
|------------------------|-----------------------------------------|

**Approvals**

|           |         |
|-----------|---------|
| Approvals |         |
| ROHS      | Conform |