

DMP Series
308-74 2

SERIES DMP

Microprocessor
Interface Modules

Input/Output
AC and DC

GENERAL DESCRIPTION:

The Crydom Series DMP Input and Output Modules are a family of high performance microprocessor interface switches designed to meet the demands of a rapidly expanding industrial control market. These reliable Crydom I/O modules provide an electrically clean, photo-isolated (4000 VRMS min), noise-free interface between programmable controllers, microprocessors and computerized machine controls and external elements such as limit switches, thermostats, pressure switches, motors/motor starters, valves and heaters.

The DMP modules have been designed to achieve high performance at a record low cost by utilizing total machine automation and labor-saving state-of-the-art robotics to assemble the entire module. The inherent quality of product consistency is combined with advanced circuit design and innovative packaging.

In a compact vertical mount package, the modules occupy only 0.90 square inches of board space. The entire module is sealed with a skin tight epoxy coating that provides excellent environmental protection while retaining very high heat transfer characteristics, allowing components to run cooler and to perform more reliably.

While physically different, the DMP modules are electrical plug-in replacements for Crydom (similarly numbered) Series 6 modules, as well as competitors' models listed as equivalents.


INPUT MODULES

The input modules accept power level field control signals and convert them to photo-isolated logic level signals through noise suppression circuitry suitable for input to a microprocessor or logic system.

OUTPUT MODULES

Crydom Output Modules accept logic level control signals to switch AC or DC loads up to 3.0 Amps at 45°C ambient temperature. The AC modules have integral snubbers for low power factor loads and also provide zero-voltage switching. DC models incorporate transient voltage suppression.

- UL Recognized, CSA Certified ■
 - Opto-Isolated, 4000 VRMS ■
 - Zero Voltage Switching (AC) ■
 - High Transient Rating ■
 - High Noise Immunity ■
 - Internal Transient Suppression ■
 - High Packaging Density ■
 - Small Footprint ■
 - Compatible with ■
- Microprocessor 5 Volt Logic Systems




Input/Output Modules (and Equivalents)

Model No.	Electrical Equivalents ①	Type	Maximum Load Current/Voltage
DMP6101A ✓	IDC5	DC/IN	25 mA @ 30 VDC
DMP6201A ✓	IAC5	AC/IN	25 mA @ 30 VDC
DMP6202A ✓	IAC5A	AC/IN	25 mA @ 30 VAC
DMP6301A ✓	ODC5	DC/OUT	3.0A DC @ 60 VDC
DMP6402A ✓	OAC5A	AC/OUT	3.0A(RMS) @ 280 VAC

General Characteristics			Units
Dielectric Strength @ 50/60 Hz (Input/Output) ①		4000	V(RMS)
Insulation Resistance @ 500 VDC (Input/Output)		10 ¹⁰	Ohms
Max Capacitance (Input/Output)		8	pF
Ambient Temperature Range	Operating	-40 to 80	°C
	Storage	-40 to 125	°C

DC Input, 5 volt logic

Electrical Specifications ($-40^{\circ}\text{C} \leq T_A \leq 80^{\circ}\text{C}$)

INPUT	MIN	MAX	UNITS
Input On Voltage	10	32	VDC
Input Off Voltage	-32	3.0	VDC
Allowable Input Current for Output Off-State		2.0	mA
Input Current (@ 12 VDC)		9.0	mA
Input Current (@ 32 VDC)		32	mA
Input Resistance (in series with coupler LED)	1100		Ohms

OUTPUT


(Note: All voltages referenced to Pin 5)

Breakdown Voltage (Pin 4)	30		VDC
Output Current (Pin 4)		25	mA
On-State Voltage (Pin 4) (@ 25 mADC)		0.4	VDC
Off-State Leakage (Pin 4) (@ 30 VDC)		100	μA
Logic Supply Voltage (Pin 3)	3.5	6.0	VDC
Logic Supply Current No Ext. LED (V applied to Pin 3)		20	mA
Logic Supply Current With Ext. LED (V applied to LED)		15	mA
Turn-On Time ($T_D + T_R$)		100	μs
Turn-Off Time ($T_D + T_F$)		100	μs

Footnotes (refer to circled numbers)

- ① Voltage applied for 1 minute
- ② Inductive loads should be diode suppressed.
- ③ LED optional. May be placed in series with logic supply (pin 3) to indicate on-state (reduces voltage at pin 3 by approximately 1.7V). LEDs are included in system mounting boards (see bulletin C100-5).
- ④ Derate 0.04 Amp/ $^{\circ}\text{C}$ from 45°C (see derating curve, Figure 1).
- ⑤ Built-in snubber will commutate inductive load to 0.5 power factor over temperature range.
- ⑥ Zener diode built-in to suppress transient voltage in excess of ratings.
- ⑦ For low load current, on-state voltage may go to 3.5V max, because of pilot-only turn-on.
- ⑧ Off-state dv/dt test method per EIA/NARM standard RS-443, paragraph 13.11.1.
- ⑨ The DMP series modules are electrical plug-in replacements for competitors' models listed as equivalents (parenthesized above) as well as Crydom Series 6 parts with same basic part numbers.

DC Output, 5 volt logic

Electrical Specifications ($-40^{\circ}\text{C} \leq T_A \leq 80^{\circ}\text{C}$)

INPUT	MIN	MAX	UNITS
Input On Voltage ①	3.0	6.0	VDC
Input Off Voltage	-32	1.0	VDC
Input Current (@ 5V)		15	mA
Input Resistance (in series with coupler LED)	270		Ohms

OUTPUT

Load Current (@ 45°C) (See Fig. 1) ②	0.02	3.0	A
Load Voltage ③	3.0	60	VDC
Surge Current (1 sec)		5.0	A
On-State Voltage (@ Max. Current)		1.5	VDC
Off-State Leakage (@ 60 VDC)		1.0	mA
Turn-On Time ($T_D + T_R$)		100	μs
Turn-Off Time ($T_D + T_F$)		100	μs





Figure 1. Maximum Output Current vs Ambient Temperature

DMP6201A
DMP6202A
AC Input, 5 volt logic

(IAC5)
(IAC5A)



Electrical Specifications ($-40^{\circ}\text{C} \leq T_A \leq 80^{\circ}\text{C}$)

INPUT		MIN	MAX	UNITS
Input On Voltage	DMP6201A	90	140	V (RMS)
	DMP6202A	180	280	V (RMS)
Input Off Voltage	DMP6201A	0.0	30	V (RMS)
	DMP6202A	0.0	60	V (RMS)
Allowable Input Current for Output Off-State	DMP6201A		2.0	mA (RMS)
	DMP6202A		1.5	mA (RMS)
Input Current (@ 120V)	DMP6201A		6.0	mA (RMS)
	DMP6202A		6.0	mA (RMS)
Frequency Range		47	420	Hz
		600		V(peak)
Input Impedance	DMP6201A	20	24	K Ohms
	DMP6202A	50	60	K Ohms

OUTPUT (Note: All voltages referenced to Pin 5)

Breakdown Voltage (Pin 4)	30		VDC
Output Current (Pin 4)		25	mA
On-State Voltage (Pin 4) (@ 25 mADC)		0.4	VDC
Off-State Leakage (Pin 4) (@ 30 VDC)		100	μA
Logic Supply Voltage (Pin 3)	3.5	6.0	VDC
Logic Supply Current	No Ext. LED (V applied to Pin 3)	20	mA
	With Ext. LED (V applied to LED)	15	mA
Turn-On Time ($T_D + T_R$)		20	ms
Turn-Off Time ($T_D + T_F$)		200	ms

Surge Characteristics — AC Output Module


The curves in Figure 2 apply to a non-repetitive uniform amplitude surge of a given time and peak current, preceded and followed by any rated load condition. Also shown is the number of these surge occurrences that can be tolerated before device damage. For example, in Figure 2, a life of 10^8 surge occurrences can be estimated for a 16 A (Peak) surge of 0.1 seconds duration. The junction temperature must be allowed to return to its steady-state value before reapplication of surge current.

Control of conduction may be momentarily lost if currents exceed the 10^4 curve values from initial junction temperatures greater than 40°C .

DMP6402A

(OAC5-A)

AC Output, 5 volt logic



Electrical Specifications ($-40^{\circ}\text{C} \leq T_A \leq 80^{\circ}\text{C}$)

INPUT	MIN	MAX	UNITS
Input On Voltage ③	3.0	6.0	VDC
Input Off Voltage	-32	1.0	VDC
Input Current (@ 5V)		15	mA
Input Resistance (in series with coupler LED)	270		Ohms

OUTPUT

Load Current (@ 45°C) (See Fig. 1) ① ③	0.02	3.0	A (RMS)
Load Voltage	12	280	V (RMS)
Frequency Range	47	63	Hz
Surge Current 1-Cycle (Non-Rep.)		80	A (peak)
Transient Overvoltage	600		V (peak)
On-State Voltage (@ Max. Curr.) ⑦		1.5	V (peak)
Off-State Leakage @ 240 V (RMS)		5.0	mA (RMS)
Off-State dv/dt ①	200		V/ μs
Turn-On Time (Next Zero Voltage)		1/2	Cycle
Turn-Off Time (Next Zero Current)		1/2	Cycle





Figure 2. Peak Surge Current vs Duration, AC Output Module


MECHANICAL SPECIFICATIONS



Weight: 0.8 oz. (23 grams)
Encapsulant: Thermally conductive epoxy
Pins: Tin-plated copper
Tolerances: ± 0.020 in. (0.5mm)
Dimensions: Inches (mm)

PLUG-IN MOUNTING HARDWARE FOR 1/16" PCB

AUGAT SOCKET
 NO. 8134-HC-12P3
 PRESSED INTO
 0.081 ± 0.002
 IN DIA PLATED
 THRU HOLE
 OR
 AMP MIN SPRING
 SOCKET NO 50865-8
 SOLDERED INTO HOLE
 +0.004
 0.101 -0.001 IN. DIA.
 (5 PLACES)



Note: Dimensions in (mm) for reference only

Data and specifications subject to change without notice

CRYDOM

COMPANY

U.S.A.

Crydom Company
 17215 Studebaker Road
 Cerritos, CA 90701
 Phone (213) 865-3536
 FAX (213) 865-3318
 Telex 910 250 5756

CANADA

International Rectifier
 101 Bentley Street
 Markham, Ontario L3R 311
 Phone (416) 475-1897
 FAX (416) 475-8801
 Telex 06 966 650

WEST GERMANY

Crydom GMBH
 Quellenweg 9
 D6935 Waldbrunn 2
 Phone 6274 6437
 FAX 6274 1472
 Telex 17627492

ENGLAND

Crydom UK
 42 Station Road East
 Oxted Surrey RH 8 OPG
 Phone 0883 717250
 FAX 0883 717253
 Telex 957 440

Sales Offices, Agents and Distributors in Major Cities throughout the World

Printed in U S A 10 88- 5M