

# DESCO

**Product Number: 17292**

**FOOT GROUNDERS, FULL COVERAGE, PREMIUM, 2MEG, LARGE**



## **Features & Benefits:**

- **New 2 Meg Resistor**  
Added Operator Safety ensuring a minimum of 1 meg-ground resistance  
Complies with UL and OSHA standards at all times
- **New 3 point hook and loop fastening system**  
Greater durability, comfort, ease of installation
- Improved design ensures maximum contact area, for superior grounding effectiveness
- Choice for HBM class 0 applications
- **Tear Resistant dual layer rubber with inner scrim**  
Provides long life and saves money
- **One Megohm Series Resistor**  
To protect operator from accidental contact with equipment line voltage.
- **UL listed**  
Independent review of the adequacy of the product's design.
- **Date coded**  
Providing traceability for quality control

**Estimated Shipping Weight: 7.68 Pounds**

“For standing operations, personnel shall be grounded via a wrist strap system or by a flooring/footwear system.”

Suitable for ESD footwear component in Flooring - Footwear System as primary grounding method <math>3.5 \times 10^7</math>ohms per ESD STM 97.1 Floor Materials and Footwear-Resistance in Combination with a Person.

“Compliance verification should be performed prior to each use (daily, shift change, etc.). The accumulation of insulative materials may increase the foot grounder system resistance. If foot grounders are worn outside the ESD protected area testing for functionality before reentry to the ESD protected area should be considered.”