

Important notice

Dear Customer,

On 7 February 2017 the former NXP Standard Product business became a new company with the tradename **Nexperia**. Nexperia is an industry leading supplier of Discrete, Logic and PowerMOS semiconductors with its focus on the automotive, industrial, computing, consumer and wearable application markets

In data sheets and application notes which still contain NXP or Philips Semiconductors references, use the references to Nexperia, as shown below.

Instead of <http://www.nxp.com>, <http://www.philips.com> or <http://www.semiconductors.philips.com> , use <http://www.nexperia.com>

Instead of sales.addresses@www.nxp.com or sales.addresses@www.semiconductors.philips.com, use salesaddresses@nexperia.com (email)

Replace the copyright notice at the bottom of each page or elsewhere in the document, depending on the version, as shown below:

- © NXP N.V. (year). All rights reserved or © Koninklijke Philips Electronics N.V. (year). All rights reserved

Should be replaced with:


- © **Nexperia B.V. (year). All rights reserved.**

If you have any questions related to the data sheet, please contact our nearest sales office via e-mail or telephone (details via salesaddresses@nexperia.com). Thank you for your cooperation and understanding,

Kind regards,

Team Nexperia

DATA SHEET



1N4531; 1N4532 High-speed diodes

Product data sheet
Supersedes data of April 1996

1996 Sep 03

High-speed diodes

1N4531; 1N4532

FEATURES

- Hermetically sealed leaded glass SOD68 (DO-34) package
- High switching speed: max. 4 ns
- Continuous reverse voltage: max. 75 V
- Repetitive peak reverse voltage: max. 75 V
- Repetitive peak forward current: max. 450 mA.

APPLICATIONS

- High-speed switching
- Protection diodes in reed relays.

DESCRIPTION

The 1N4531, 1N4532 are high-speed switching diodes fabricated in planar technology, and encapsulated in hermetically sealed leaded glass SOD68 (DO-34) packages.



The diodes are type branded.

Fig.1 Simplified outline (SOD68; DO-34) and symbol.

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{RRM}	repetitive peak reverse voltage		—	75	V
V_R	continuous reverse voltage		—	75	V
I_F	continuous forward current	see Fig.2	—	200	mA
I_{FRM}	repetitive peak forward current		—	450	mA
I_{FSM}	non-repetitive peak forward current	square wave; $T_j = 25^\circ\text{C}$ prior to surge; see Fig.4 $t = 1 \mu\text{s}$ $t = 1 \text{ ms}$ $t = 1 \text{ s}$	— — —	4 1 0.5	A
P_{tot}	total power dissipation	$T_{\text{amb}} = 25^\circ\text{C}$	—	500	mW
T_{stg}	storage temperature		—65	+200	°C
T_j	junction temperature		—	200	°C

High-speed diodes

1N4531; 1N4532

ELECTRICAL CHARACTERISTICS

 $T_j = 25^\circ\text{C}$; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_F	forward voltage	$I_F = 10 \text{ mA}$; see Fig.3	–	1000	mV
I_R	reverse current IN4531	see Fig.5 $V_R = 20 \text{ V}$	–	25	nA
		$V_R = 20 \text{ V}; T_j = 150^\circ\text{C}$	–	50	μA
	IN4532	$V_R = 50 \text{ V}$	–	100	nA
		$V_R = 50 \text{ V}; T_j = 150^\circ\text{C}$	–	100	μA
C_d	diode capacitance IN4531 IN4532	$f = 1 \text{ MHz}; V_R = 0$; see Fig.6	–	4	pF
			–	2	pF
	reverse recovery time IN4531 IN4532	when switched from $I_F = 10 \text{ mA}$ to $I_R = 60 \text{ mA}; R_L = 100 \Omega$; measured at $I_R = 1 \text{ mA}$; see Fig.7	–	4	ns
	reverse recovery time IN4532	when switched from $I_F = 10 \text{ mA}$ to $I_R = 10 \text{ mA}; R_L = 100 \Omega$; measured at $I_R = 1 \text{ mA}$; see Fig.7	–	2	ns
			–	4	ns
V_{fr}	forward recovery voltage	when switched from $I_F = 100 \text{ mA}$; $t_r \leq 30 \text{ ns}$; see Fig.8	–	3	V

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th j\text{-tp}}$	thermal resistance from junction to tie-point	lead length 5 mm	120	K/W
$R_{th j\text{-a}}$	thermal resistance from junction to ambient	lead length 5 mm; note 1	350	K/W

Note

1. Device mounted on a printed circuit-board without metallization pad.

High-speed diodes

1N4531; 1N4532

GRAPHICAL DATA




Fig.2 Maximum permissible continuous forward current as a function of ambient temperature.




Fig.3 Forward current as a function of forward voltage.





Fig.4 Maximum permissible non-repetitive peak forward current as a function of pulse duration.


High-speed diodes

1N4531; 1N4532



$V_R = 50 \text{ V}$
Solid line; maximum values.
Dotted line; typical values.

Fig.5 Reverse current as a function of junction temperature.



$f = 1 \text{ MHz}; T_j = 25 \text{ }^{\circ}\text{C}$.

Fig.6 Diode capacitance as a function of reverse voltage; typical values.

High-speed diodes

1N4531; 1N4532




Fig.7 Reverse recovery voltage test circuit and waveforms.





Fig.8 Forward recovery voltage test circuit and waveforms.

High-speed diodes

1N4531; 1N4532

PACKAGE OUTLINE



Dimensions in mm.

Fig.9 SOD68 (DO-34).

High-speed diodes

1N4531; 1N4532**DATA SHEET STATUS**

DOCUMENT STATUS ⁽¹⁾	PRODUCT STATUS ⁽²⁾	DEFINITION
Objective data sheet	Development	This document contains data from the objective specification for product development.
Preliminary data sheet	Qualification	This document contains data from the preliminary specification.
Product data sheet	Production	This document contains the product specification.

Notes

1. Please consult the most recently issued document before initiating or completing a design.
2. The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

DISCLAIMERS

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions

above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

NXP Semiconductors

Customer notification

This data sheet was changed to reflect the new company name NXP Semiconductors. No changes were made to the content, except for the legal definitions and disclaimers.

Contact information

For additional information please visit: <http://www.nxp.com>

For sales offices addresses send e-mail to: salesaddresses@nxp.com

© NXP B.V. 2009

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

Date of release: 1996 Sep 03

Founded by

PHILIPS