

UMC-201 : USB-to-Serial-Adapter USB Cable with Hot-Plugging Functions



- **Key characteristics:**
 - o USB (Universal Serial Bus) 1.1 specification compatibility
 - o Full plug-and-play, and hot-plugged functions
 - o USB/serial converter supports most common used RS-232 baud rates
 - o Compact size provides one USB cable with A-connector and one DB25 (or DB9) male connector
 - o No power supply needed
 - o Application to RS-232 Microsoft mouse, digital camera, modem, ISDN-TA, barcode reader, card reader,
 - o Palm III and Palm V, tablet, label writer, POS, fingerprint verification, security system
- **Properties:**
 - o USB port: one USB cable with A type connector
 - o RS-232 port: one DB-9 EIA serial interface
 - o Chipset: FTDI /232 RL
 - o LED: three LED: power, TX, RX
 - o Baud rate: 1200bps to 921.6kbps
 - o Parity bit: none, even, odd
 - o Data bit: 5, 6, 7, 8
 - o Stop bit: 1, 2
 - o Handshaking: software, hardware, none
 - o Power mode: bus-power mode
 - o Operating temperature: 5 to 45 degrees Celsius
 - o Stock temperature: -20 to 70 degrees Celsius
 - o Humidity: 20% to 80% RH, non-condensing
 - o Cable length: 1 m
 - o Housing: plastic/black color
- **System requirement:**
 - o Windows 98/98SE/ME/2000/XP, Mac8.6 to 9.1, Linux
 - o USB Host Controller installed on the system
- **Contents:**
 - o USB to RS-232 converter (length 1m)
 - o Driver C