




LEAD STYLE		TERMINAL	'L' OVERALL LENGTH (REF)
SERIES D&Z	SERIES E		
07	N/A	T-1S6-07-XXX-2	.430
08	N/A	T-1S6-08-XXX-2	.530
09	09	T-1S6-09-XXX-2	.730
10	10	T-1S6-10-XXX-2	.830
11	11	T-1S6-11-XXX-2	.930
12	12	T-1S6-12-XXX-2	1.030
13	13	T-1S6-13-XXX-2	1.230
14	14	T-1S6-14-XXX-2	1.430
15	15	T-1S6-15-XXX-2	.630
16	N/A	T-1S6-16-XXX-2	.445
17	N/A	T-1S6-17-XXX-2	.480
19	19	T-1S6-19-XXX-2	1.330
20	20	T-1S6-20-XXX-2	1.130



NUMBER POSITIONS WITH .330, .110, OR ZW TAIL DOWN

SHEET 1 OF 2

-G: 10µ" GOLD IN CONTACT AREA, 3µ" GOLD ON TAIL
 -T: MATTE TIN CONTACT AND TAIL
 -S: 30µ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
 -H: 30µ" GOLD IN CONTACT AREA, 3µ" GOLD ON TAIL
 -L: 10µ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
 -F: 3µ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
 -E: 50µ" GOLD IN CONTACT AREA, 3µ" GOLD ON TAIL (STYLE -13 ONLY)
 -STL: 30µ" SELECTIVE GOLD IN CONTACT AREA, TIN/LEAD (90/10 +/-5%) TAIL
 -FM: 3µ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
 -LH: 10µ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
 -SM: 30µ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
 -Tn: MATTE TIN CONTACT AND TAIL



SERIES

1. HEIGHT VARIATION BETWEEN ANY TWO PINS AND ROW SHALL BE .010 MAX

DELETED -2. S PLATING- PLATED AREA WILL BE ON THE LONGER TAIL.

DELETED -3. S PLATING- HEAVY GOLD ON LONGER TAIL.

DELETED -4. L PLATING- GOLD ON LONGER TAIL.

DELETED -5. H PLATING- HEAVY GOLD ON LONGER TAIL.

DELETED -6. F PLATING- FLASH SELECTIVE GOLD ON LONGER TAIL.

DELETED -7. P PLATING- GOLD FLASHED PALLADIUM NICKEL ON LONGER TAIL.

DELETED -8. L PLATING- EXTRA HEAVY GOLD ON LONGER TAIL.

9. ($\varnothing$) REPRESENTS A CRITICAL DIMENSION.

10. -F -S -I -P GOLD TO BE ON LONGER T

10. -G, -H, -E, HEAVY GOLD TO BE ON LONGER TAIL.
11. CRIMPED TAILS OF .090 TO BE TOLERANCED +.008/- .000.
12. TSW-50-D TO BE USED IF RTSW-50-D IS NOT AVAILABLE
.000 MIN IF TAIL LENGTH IS GREATER THAN OR EQUAL TO .055.
14. TERMINAL PUSHOUT FORCE: 3 LBS. MIN.
15. MAXIMUM CUT FLASH: .010[.25]

16. FOR ADDED MECHANICAL STABILITY, SAMTEC RECOMMENDS MECHANICAL BOARD SPACERS EXISPROD\ASSEMBLY\100 BE USED IN APPLICATIONS WITH GOLD OR SELECTIVE GOLD PLATED CONNECTORS. CONTACT XW-XX-XX-XXX-X-XXXX-XXX-XX-XXX-ASM1

NO. 310, 3/4 HARD,
TENSILE RANGE 95-105 KS

2) 944-6733
CODE 55322

XW-XX-XX-XXX-X-XXXX-XXX-XX-XX

SHEET 1 OF 2

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC INC. AND SHALL NOT BE
REPRODUCED OR TRANSFERRED TO
OTHER DOCUMENTS OR DISCLOSED TO
OTHERS OR USED FOR ANY PURPOSE
OTHER THAN THAT FOR WHICH IT WAS
OBTAINED WITHOUT THE EXPRESSED
WRITTEN CONSENT OF SAMTEC INC.