

Fig. 2 Fig. 1

Type **NT**

T-CONNECTOR

Type NT

Tubing Run—Tubing Tap

A high copper alloy Multigrip type T-Connector for tubing run and tap. Slotted between bolts to provide independent high pressure areas of contact. High strength Durium oval shank bolts are readily installed with only one wrench. Finished to provide minimum contact resistance.

Listed by C.S.A.

For use on ALUMINUM conductors, add -W to catalog number

IPS RUN	IPS TAP	CATALOG NUMBER	APPROX. SHIP. WT. IN LBS.	FIG. NO.	DIMENSIONS IN INCHES A	AA	B	H (MAX.)	J	L	W	BB	Y
1/4"	1/4"	NT1111	1.0	1	.540	.540	1 3/8	1 7/16	3/8	3 3/16	1 15/16	1 3/8	2 1/4
3/8"	1/4"	NT1211	1.1	1	.675	.540	1 3/8	1 7/16	3/8	3 3/8	1 15/16	1 3/8	2 5/16
3/8"	3/8"	NT1212	1.2	1	.675	.675	1 3/8	1 7/16	3/8	3 3/8	2 1/8	1 3/8	2 5/16
1/2"	1/4"	NT1311	1.2	1	.840	.540	1 3/8	1 11/16	3/8	3 1/2	1 15/16	1 3/8	2 3/8
1/2"	3/8"	NT1312	1.3	1	.840	.675	1 3/8	1 11/16	3/8	3 1/2	2 1/8	1 3/8	2 3/8
1/2"	1/2"	NT1313	2.1	2	.840	.840	2	1 11/16	3/8	3 15/16	2 1/4	2	2 13/16
3/4"	3/8"	NT1412	1.3	1	1.050	.675	1 3/8	1 15/16	3/8	3 11/16	2 1/8	1 3/8	2 7/16
3/4"	1/2"	NT1413	2.1	2	1.050	.840	2	1 15/16	3/8	4 1/8	2 1/4	2	2 7/8
3/4"	3/4"	NT1414	2.3	2	1.050	1.050	2	1 15/16	3/8	4 1/8	2 7/16	2	2 7/8
1"	3/8"	NT1512	1.3	1	1.315	.675	1 3/8	2	3/8	3 15/16	2 1/8	1 3/8	2 5/8
1"	1/2"	NT1513	2.3	2	1.315	.840	2	2 1/16	3/8	4 3/8	2 1/4	2	3
1"	3/4"	NT1514	2.5	2	1.315	1.050	2	2 1/8	3/8	4 3/8	2 7/16	2	3
1"	1"	NT1515	2.7	2	1.315	1.315	2	2 1/8	3/8	4 7/16	2 3/4	2	3 1/16
1 1/4"	1/2"	NT1613	2.6	2	1.660	.840	2	2 3/8	3/8	4 3/4	2 1/4	2	3 3/16
1 1/4"	3/4"	NT1614	2.7	2	1.660	1.050	2	2 7/16	3/8	4 3/4	2 7/16	2	3 3/16
1 1/4"	1"	NT1615	3.2	2	1.660	1.315	2	2 7/16	3/8	4 3/4	2 3/4	2	3 3/16
1 1/4"	1 1/4"	NT1616	5.6	2	1.660	1.660	2 11/16	2 5/8	1/2	5 11/16	3 1/2	2 11/16	3 15/16
1 1/2"	1/2"	NT1713	2.7	2	1.900	.840	2	2 9/16	3/8	5	2 1/4	2	3 1/4
1 1/2"	3/4"	NT1714	3.1	2	1.900	1.050	2	2 11/16	3/8	5 1/16	2 7/16	2	3 5/16
1 1/2"	1"	NT1715	3.3	2	1.900	1.315	2	2 11/16	3/8	5 1/16	2 3/4	2	3 5/16
1 1/2"	1 1/4"	NT1716	6.0	2	1.900	1.660	2 11/16	2 3/4	1/2	6 1/16	3 1/2	2 11/16	4 1/8
1 1/2"	1 1/2"	NT1717	6.5	2	1.900	1.900	2 11/16	2 3/4	1/2	6 1/16	3 15/16	2 11/16	4 1/8
2"	1/2"	NT1813	3.2	2	2.375	.840	2	3 1/16	3/8	5 9/16	2 1/4	2	3 3/16
2"	3/4"	NT1814	3.3	2	2.375	1.050	2	3 1/8	3/8	5 9/16	2 7/16	2	3 3/16
2"	1"	NT1815	3.7	2	2.375	1.315	2	3 3/16	3/8	5 5/8	2 3/4	2	3 3/16
2"	1 1/4"	NT1816	6.5	2	2.375	1.660	2 11/16	3 3/16	1/2	6 9/16	3 1/2	2 11/16	3 7/8
2"	1 1/2"	NT1817	7.2	2	2.375	1.900	2 11/16	3 1/4	1/2	6 5/8	3 15/16	2 11/16	3 7/8
2"	2"	NT1818	8.2	2	2.375	2.375	3 1/16	3 5/16	1/2	6 11/16	4 5/8	2 11/16	4 3/8
2 1/2"	1/2"	NT1913	3.4	2	2.875	.840	2	3 9/16	3/8	6 1/16	2 1/4	2	3 7/8
2 1/2"	3/4"	NT1914	3.8	2	2.875	1.050	2	3 11/16	3/8	6 1/8	2 7/16	2	3 7/8
2 1/2"	1"	NT1915	4.1	2	2.875	1.315	2	3 11/16	3/8	6 1/8	2 3/4	2	3 13/16
2 1/2"	1 1/4"	NT1916	6.9	2	2.875	1.660	2 11/16	3 3/4	1/2	7 1/8	3 1/2	2 11/16	4 5/8
2 1/2"	1 1/2"	NT1917	7.7	2	2.875	1.900	2 11/16	3 3/4	1/2	7 3/16	3 15/16	2 11/16	4 5/8
2 1/2"	2"	NT1918	9.2	2	2.875	2.375	3 1/16	3 7/8	1/2	7 1/4	4 5/8	2 11/16	4 5/8
2 1/2"	2 1/2"	NT1919	11	2	2.875	2.875	3 5/8	3 7/8	1/2	7 1/4	5 1/4	2 11/16	4 5/8
3"	1/2"	NT2013	4.3	2	3.500	.840	2	4 1/4	3/8	6 3/4	2 1/4	2	4 1/8
3"	3/4"	NT2014	4.4	2	3.500	1.050	2	4 5/16	3/8	6 3/4	2 7/16	2	4 1/8
3"	1"	NT2015	4.7	2	3.500	1.315	2	4 3/8	3/8	6 13/16	2 3/4	2	4 1/8
3"	1 1/4"	NT2016	7.8	2	3.500	1.660	2 11/16	4 3/8	1/2	7 3/4	3 1/2	2 11/16	4 15/16
3"	1 1/2"	NT2017	8.7	2	3.500	1.900	2 11/16	4 7/16	1/2	7 13/16	3 15/16	2 11/16	4 15/16
3"	2"	NT2018	10	2	3.500	2.375	3 1/16	4 1/2	1/2	7 13/16	4 5/8	2 11/16	4 15/16
3"	2 1/2"	NT2019	10	2	3.500	2.875	3 5/8	4 9/16	1/2	7 7/8	5 1/4	2 11/16	5
3"	3"	NT2020	17	2	3.500	3.500	4 5/16	4 5/8	5/8	8 5/8	6 3/16	3 1/4	5 9/16

(CONTINUED)

REV.	DATE	REVISION DESCRIPTION	BY	CK'D
10	8-26-66	SHEET #2 AFFECTED (Q-252-1573)	LJP	MTM
9	11-5-65	BB & Y DIM.S ADDED (DC3267)	M.A.P.	MJM

TEE CONNECTOR

CAT. NO. NT SCALE

DRAWN J.A.B. 5-3-48 CHECKED 10-16-57

BURNDY Corporation NORWALK, CONNECT.

DRAWING NO. SA11718 REV. 10

APPROVED

SHEET 1 OF 2 SHEETS
SUPERSEDES SC 11718-7