

Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

BAS16T **BAW56T** BAV70T **BAV99T**

Features

- Ultra-Small Surface Mount Package
- For General Purpose Switching Applications
- **High Conductance**
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0









Maximum Ratings


- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C


Electrical Characteristics @ 25°C Unless Otherwise Specified


| Peak Repetitive Reverse Voltage | V_{RRM} | 85V | | |
|---|------------------|------------------------------------|--|--|
| Continuous Forward Current | I _F | 75mA | | |
| Power Dissipation | P_{D} | 150mW | | |
| Peak Forward Surge Current @t=1.0us @t=1.0ms @t=1.0s | I _{FSM} | 4.0A 1.0A 0.5A | | |
| Maximum Instantaneous Forward Voltage | V_{F} | 715mV 855mV 1000mV 1250mV | $I_F = 1mA$ $I_F = 10mA$; $I_F = 50mA$ $I_F = 150mA$ | |
| Maximum DC Reverse Current At Rated DC Blocking Voltage | I _R | 2μA 0.03μA | V _R =75Volts V _R =25Volts | |
| Typical Total Capacitance | C _T | 1.5pF | Measured at 1.0MHz, V _R =0V | |
| Reverse Recovery Time | T _{rr} | 4nS | IF = IR = 10mA, Irr = 0.1 x IR, RL = 100Ω | |

150mW 85Volt **Switching Diode**










| DIMENSIONS | | | | | | | |
|------------|--------------|------|-------------|------|------|--|--|
| | INCHES | | ММ | | | | |
| DIM | MIN | MAX | MIN | MAX | NOTE | | |
| Α | .059 | .067 | 1.50 | 1.70 | | | |
| В | .030 | .033 | 0.75 | 0.85 | | | |
| С | .057 | .069 | 1.45 | 1.75 | | | |
| D | .020 Nominal | | 0.50Nominal | | | | |
| Е | .035 | .043 | 0.90 | 1.10 | | | |
| G | .000 | .004 | .000 | .100 | | | |
| Н | .028 | .031 | .70 | 0.80 | | | |
| J | .004 | .008 | .100 | .200 | | | |
| K | .010 | .014 | .25 | .35 | | | |


BAS16T/BAW56T BAV70T/BAV99T



Micro Commercial Components



 T_S , SOLDERING POINT TEMPERATURE (°C) Fig. 1 Current Derating Curve



V , INSTANTANEOUS FORWARD VOLTAGE (V) Fig. 2 Forward Characteristics




Fig. 3, Typical Reverse Characteristics



Micro Commercial Components

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.