

# MICRO SWITCH

A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR COMPANY  
FREEPORT, ILLINOIS

FED. MFR. CODE 91929

# ASSEMBLY- TOGGLE SWITCH

CATALOG LISTING

6AT17

6AT17

M

DRAWING  
NUMBER

6

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

3

REPLACES

RELEASE NO. SR 4510

CNT 13 MAY 55

CNT 13 MAY 55

CNT 13 MAY 55

GRH 13 MAY 55

CNT 13 MAY 55

FKR 16 MAY 55

CNT 13 MAY 55

CNT 13 MAY 55

CNT 13 MAY 55

N.C. TO C. CIRCUIT MADE  
(MAINTAINED POSITION)

40°±8°  
TOTAL  
TRAVEL

N.O. TO C. CIRCUIT MADE  
(MAINTAINED POSITION)

±.020  
1.156

.47

.38

.774 REF.74

±.020

.06

FLEXIBLE INSULATORS

0.58 DIA. HOLE  
IN TERMINALS.

±.010  
.260

±.010  
.342

±.010  
.090

HEX NUT .56  
ACROSS FLATS X  
.078±.010 THICK.

.240 DIA.

.072 WIDE X .038 DEEP  
KERF

15-32 NS THREAD TO  
WITHIN .094 OF SHOULDER

CORROSION RESISTANT  
BUSHING

CORROSION RESISTANT  
INTERNAL TOOTH  
LOCKWASHER .60 DIA.

CORROSION RESISTANT  
STEEL KEYING WASHER  
.031 THICK X .72 DIA,  
TAB .110 WIDE,  
.110 DIA.

## NOTE

1-UNIT INCLUDES (1) CAT. LIST. ISM23  
BASIC SWITCH.

2-TERMINALS ARE PLATED FOR SOLDERING.

3-CONTACT MATERIAL SOLID GOLD.

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

## CHARACTERISTICS

## ELECTRICAL DATA

## SCALE FULL

CONTACT ARRANGEMENT  
S. P. D. T.

BREAK DISTANCE  
.010 MIN.

DO NOT SCALE PRINT

UNLESS OTHERWISE  
SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES ARE:

ONE PLACE (.0) ±.030  
TWO PLACE (.00) ±.015  
THREE PLACE (.000) ±.005  
ANGLES ±10°

WEIGHT .05 LB.