

KB847

GENERAL PURPOSE
HIGH ISOLATION VOLTAGE
SINGLE TRANSISTOR TYPE
PHOTOCOUPLER SERIES

FEATURES

- 1.High isolation voltage between input and output ($V_{iso}=5000$ Vrms)
- 2.Compact dual-in-line package
- KB847:1-channel type
- 3.Recognized by UL and CUL, file NO. E225308

DESCRIPTION

- 1.The KB847 (4-channel) is optically coupled isolators containing a GaAs light emitting diode and an NPN silicon phototransistor.
- 2.The lead pitch is 2.54mm
- 3.Solid insulation thickness between emitting diode and output phototransistor: ≥ 0.6 mm.


APPLICATIONS

- 1.Computer terminals
- 2.Registers, copiers, automatic vending machines
- 3.System appliances, measuring instruments
- 4.Programmable logic controller
- 5.Signal transmission between circuits of different potentials and impedances

Kingbright**KB847**

* PACKAGE DIMENSIONS (UNIT: mm)

DIP Type

TOLERANCE : $\pm 0.5[\pm 0.02]$ UNLESS OTHERWISE NOTED.**KB847*****Absolute Maximum Ratings ($T_a=25^\circ\text{C}$)**

Parameter		Symbol	Rating	Unit
Input	Forward current	I_F	50	mA
	Reverse voltage	V_R	6	V
	Power dissipation	P	70	mW
Output	Collector-emitter voltage	V_{CEO}	35	V
	Emitter-collector voltage	V_{ECO}	6	V
	Collector current	I_C	50	mA
	Collector power dissipation	P_c	150	mW
Total power dissipation		P_{tot}	200	mW
¹ Isolation voltage		V_{iso}	5000	Vrms
Operating temperature		T_{opr}	-30~+100	°C
Storage temperature		T_{stg}	-55~+125	°C
² Soldering temperature		T_{sol}	260	°C

¹ 40 to 60% RH,AC for 1 minute.² For 10 seconds.

KB847

* Electro-optical Characteristics

Parameter		Symbol	Conditions	Min.	Typ.	Max.	Unit
Input	Forward voltage	V _F	I _F =20mA	—	1.2	1.4	V
	Peak forward voltage	V _{FM}	I _{FM} =0.5A	—	—	3.0	V
	Reverse current	I _R	V _R =4V	—	—	10	μA
Output	Collector dark current	I _{CEO}	V _{CE} =20V, I _F =0mA	—	—	10 ⁻⁷	A
Transfer characteristics	* ¹ Current transfer ratio	CTR	I _F =5mA, V _{CE} =5V	50	—	600	%
	Collector-emitter saturation voltage	V _{CE(sat)}	I _F =20mA, I _C =1mA	—	0.1	0.2	V
	Cut-off frequency	f _c	V _{CE} =5V, I _C =2mA R _L =100Ω, -3dB	—	80	—	kHz
	Response time	t _r	V _{CE} =2V, I _C =2mA R _L =100Ω	—	4	18	μS
	Fall time	t _f		—	3	18	μS


*¹ Classification table of current transfer ratio is shown below.

$$\text{CTR} = \frac{I_C}{I_F} \times 100\%$$


Model No.	Rank mark	CTR (%)
KB847L	L	50 to 100
KB847A	A	80 to 160
KB847B	B	130 to 260
KB847C	C	200 to 400
KB847D	D	300 to 600
KB847AB	A or B	80 to 260
KB847BC	B or C	130 to 400
KB847CD	C or D	200 to 600
KB847AC	A,B or C	80 to 400
KB847BD	B,C or D	130 to 600
KB847AD	A,B,C or D	80 to 600
KB847	L,A,B,C,D or No mark	50 to 600

Kingbright**KB847**


**Fig. 1 Current Transfer Ratio vs.
Forward Current**




**Fig. 2 Forward Current vs.
Forward voltage**




**Fig. 3 Collector Current vs.
Collector-emitter Voltage**



**Fig. 4 Relative Current Transfer Ratio
vs. Ambient Temperature**



**Fig. 5 Collector-emitter Saturation
Voltage vs. Ambient Temperature**



**Fig. 6 Collector Dark Current vs.
Ambient Temperature**




Fig. 7 Forward Current vs. Ambient Temperature




Fig. 8 Collector Power Dissipation vs. Ambient Temperature





Fig. 9 Response Time vs. Load Resistance



Test Circuit for Response Time





Fig. 10 Frequency Response



Test Circuit for Frequency Response





Fig. 11 Collector-emitter Saturation Voltage vs. Forward Current



* NOTES ON HANDLING

1. Recommended soldering conditions (Dip soldering)

(1) Dip soldering

Temperature	260 °C or below (molten solder temperature)
Time	Less than 10 seconds.
Cycle	One cycle allowed to be dipped in solder including plastic mold portion.
Flux	Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt % is recommended.)

(2) Cautions

Fluxes

Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent.

2. Cautions regarding noise

Be aware that power is suddenly into the component any surge current may cause damage happen, even if the voltage is within the absolute maximum ratings.

KB847

CAUTION

Within this device there exists GaAs (Gallium Arsenide) material which is a harmful substance if ingested.


GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them.

RESTRICTIONS ON PRODUCT USE



- The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version. Not all devices / types available in every country.
- We are mention about our product quality stability, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing KINGBRIGHT products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a KINGBRIGHT product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that KINGBRIGHT products are used within specified operating ranges as set forth in the most recent products specifications.

Kingbright**KB847**


Dimension of Tube

TOLERANCE : $\pm 0.4[\pm 0.012]$ UNLESS OTHERWISE NOTED.
Unit:mm

A-A Side view



Dimension of Carton



*ORDERING INFORMATION

Part Number	Package	Package Style
KB847	16-pin DIP	25pcs/each tube