



LOW PROFILE GENDER CHANGERS

Ideal for use where a low-profile is needed in a permanent installation (only 0.7" deep at thickest point). Gold flashed contacts. Fully shielded.

Cat. No.	Description	Net Price
45-0517-0000	DB-9 Male/Male	\$3.13
45-0518-0000	DB-9 Female/Female	3.13
45-0519-0000	DB-9 Male/Female	3.24
45-0527-0000	DB-15 Male/Male	3.34
45-0528-0000	DB-15 Female/Female	3.86
45-0507-0000	DB-25 Male/Male	3.13
45-0508-0000	DB-25 Female/Female	3.21
45-0509-0000	DB-25 Male/Female, Slim	3.66



STANDARD NULL MODEM

Standard DB-25 connectors each end, male to female. Fits in line to connect like devices, either DTE or DCE. This is the most commonly used circuit for the Null Modem Adaptors; see schematic for wiring.


Cat. No.	Description	Net Price
45-0582-0000	DB-25 Male/Female	\$3.55



TELCO ADAPTORS FOR DB-9 OR DB-25 PORTS

Allows use of low cost TELCO® (telephone) wire between computers and peripherals. Available in either DB-25 or DB-9 connectors on one end and 4, 6 or 8 contact Telco connectors on the other.

Cat. No.	Description	Net Price
45-5112-0000	DB-9 Female to 6 Conductor	\$2.61
45-5113-0000	DB-9 Female to 8 Conductor	2.61
45-5109-0000	DB-9 Male to 6 Conductor	2.61
45-5110-0000	DB-9 Male to 8 Conductor	2.61
45-0512-0000	DB-25 Female to 4 Conductor	3.11
45-5126-0000	DB-25 Female to 6 Conductor	2.51
45-5127-0000	DB-25 Female to 8 Conductor	2.84
45-5121-0000	DB-25 Male to 4 Conductor	2.36
45-5123-0000	DB-25 Male to 6 Conductor	2.84
45-5108-0000	Telco Adapter DB-9 Male to 4 Conductor	2.61
45-5111-0000	Telco Adapter DB-9 Female to 4 Conductor	2.61



RS-232 DB-25 SWITCH

One I/O DB-25 Female connects to two (A/B). Cross Switch type has four DB-25 Female connectors, two configured as Input, two as Output.

Cat. No.	Description	Net Price
64-2001-0000		\$13.48



45-1035-0000

45-1060-0000

STANDARD "D" CONNECTORS

For cable mounting or shell may be discarded for panel mounting. All contacts molded in place permanently. Hardware included; solder connection.


Cat. No.	Description	Net Price
45-1035-0000	DB9 Male	\$2.90
45-1036-0000	DB9 Female	2.90
45-1060-0000	DB25 Male	2.90
45-1061-0000	DB25 Female	2.90



PORT RECONFIGURATION KITS

These RS232 jumper boxes have both male & female connectors mounted on a printed circuit board with pads for soldering connections and a bus area for tying lines together. A snap-on re-usable shell is provided to protect your connections and make the unit into a permanent adapter.

Cat. No.	Description	Net Price
45-0480-0000	DB25 (M) / (F) + Hardware	\$9.21



CAT 5E DATACOM PATCH AND JUMPER CABLES

Pre-made jumper cables are tested and certified to 350 MHz. All cables have snagless boots that join the connector to the cable and prevents disconnection due to accidental stresses. Connectors are plated to 50 micro-inches of gold. Cable is stranded Cat 5e (4 pair/24 AWG) UTP, meeting and tested to UL and CSA requirements.

Cat. No.	Description	Net Price
45-6860-00BU	3' snagless boot, blue	\$1.59
45-6867-00BU	7' snagless boot, blue	2.61
45-6868-00BU	14' snagless boot, blue	3.99

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[45-0508](#)