

Technical drawing of a probe tip showing two views: a top view and a side view. The top view shows a rectangular base with a central slot and a series of small squares along the top edge. The side view shows a long, thin, tapered tip with a curved end. Dimensions are labeled: E (total width), D (base width), C REF. (base thickness), F REF. (total length), A $\pm .01 (.25)$ (tip thickness), and B $\pm .01 (.25)$ (tip width). The tip is labeled "CURVED TIP".

PANDUIT PART NO. *	BUNDLE DIA.		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	MIN. LOOP TENSILE ^{lbs.} (N)	CROSS SECTION	WEIGHT ^{lbs.} /100 pcs. (g)
	MIN. ⁱⁿ (mm)	MAX. ⁱⁿ (mm)									
PLT1M	.06 (1.5)	.87 (22)	.043 (1.1)	.098 (2.5)	.169 (4.3)	.154 (3.9)	.180 (4.6)	3.9 (99)	18 (80)	MINIATURE	.07 (32)
PLT2I	.06 (1.5)	2.00 (51)	.045 (1.1)	.142 (3.6)	.206 (5.2)	.180 (4.6)	.240 (6.1)	8.0 (203)	40 (178)	INTERMEDIATE	.20 (91)
PLT2S	.06 (1.5)	1.88 (48)	.052 (1.3)	.190 (4.8)	.258 (6.6)	.220 (5.6)	.316 (8.0)	7.4 (188)	50 (222)	STANDARD	.29 (132)
PLT3S	.06 (1.5)	3.00 (76)	.052 (1.3)	.190 (4.8)	.265 (6.7)	.220 (5.6)	.337 (8.6)	11.5 (292)	50 (222)	STANDARD	.45 (204)

* 1. SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE. SEE NOTE 2 FOR PART NUMBER SUFFIX FOR PART COLOR.

2. CABLE TIES ARE AVAILABLE IN 4 DIFFERENT FLUORESCENT COLORS:

<u>PART</u>	<u>NUMBER</u>	<u>SUFFIX</u>	<u>COLOR</u>
	-53		ORANGE
	-54		YELLOW
	-55		GREEN
	-59		PINK

CAD FILENAME/LAYERS
DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS

PANDUIT CORP. TINLEY PARK, ILLINOIS

PAN-TY FLUORESCENT LOCKING CABLE TIE

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:

(.X) ±	(.XXX) ±
(.XX) ±	ANGLES ±

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
C. HARVELL

MAT'L:

DATE	11/08/91
------	----------

NYLON
6.6

SCALE	NONE
-------	------

DRAWING NO.

SS-26476

DWG
A
SIZE

5	9/10/04	ERW		CORRECTED METRIC CONVERSIONS	26476	5			
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP	