



368572-9 Product Details

 Share  Print  Email



 Active

 View 3D PDF

Power Double-Lock Connectors

PDL 3P CAP 3.96 F/H(GWT) BLK

368572-9 

TE Internal Number: 368572-9

Product Highlights [View All](#)

- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Housing
- Connector Style = Receptacle

Pricing & Availability

Request Sample

Add to My Part List

Buy Product through
Distributor


Feedback

Documents **Features** Compliance

Please Note:
Use the Product Drawing for all design activity

Product Type Features	
Product Type	Connector
Connector Type	Housing
Wire/Cable Type	Discrete Wire
Sealed	No


Mechanical Attachment	
Mating Retention Type	Latch(ing)



Electrical Characteristics	
Operating Voltage Reference	AC 
Operating Voltage (VAC)	300




Termination Features	
Termination Method to Wire/Cable	Crimp

Body Features	
Wire Type	Stranded
Mating Retention	With

Contact Features	
Contact Type	Tab
Contact Layout	In-Line

Housing Features	
Connector Style	Receptacle
Centerline (mm [in]) 	3.96 [0.156]
Housing Material	PA66
Housing Color	Black
Mating Alignment	With
Mating Alignment Type	Polarization

Configuration Features	
Number of Positions 	3
Number of Rows	1
Number of Double-Lock Plates Required 	1

Industry Standards	
RoHS/ELV Compliance 	RoHS compliant, ELV compliant
Lead Free Solder Processes 	Not relevant for lead free process 
RoHS/ELV Compliance History	Always was RoHS compliant
Agency/Standard	CNR, USR
UL File Number	C22.2 No. 182.3, UL 1977
UL Flammability Rating	UL 94V-0

Environmental	
Operating Temperature (°C [°F])	65 [149]

Conditions for Usage	
Applies To	Wire/Cable
Glow Wire Rating	Glow Wire
For Use With	Plug (GWT): 368571, Contacts: 177916 or 177917, Double Lock Plate 177919-1

Operation/Application	
Application Use	Wire-to-Wire
Contact Transmits (Typical Application)	Signal (Data)/Power

Other	
Brand	TE Connectivity
Comment	Double lock plates should certainly be used when mfging. cable assemblies.

Related Products

Not quite the product
you're looking for?
[Find Similar Products](#)

[View Part in Product
Feature Selector](#)

[Check for Tooling](#)

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [Global Accessibility Statement](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

