

SUPERSEDED △ ₁₆		CONTAINS LEAD	45.72 [1.800]	18	1-641214-8
SUPERSEDED △ ₁₆			43.18 [1.700]	17	1-641214-7
			40.64 [1.600]	16	1-641214-6
			38.10 [1.500]	15	1-641214-5
			35.56 [1.400]	14	1-641214-4
SUPERSEDED △ ₁₆			33.02 [1.300]	13	1-641214-3
			30.48 [1.200]	12	1-641214-2
			27.94 [1.100]	11	1-641214-1
			25.40 [1.000]	10	1-641214-0
△ ₁₆ SUPERSEDED			22.86 [.900]	9	641214-9
			20.32 [.800]	8	641214-8
			17.78 [.700]	7	641214-7
			15.24 [.600]	6	641214-6
SUPERSEDED △ ₁₆			12.70 [.500]	5	641214-5
			10.16 [.400]	4	641214-4
			7.62 [.300]	3	641214-3
		5.08 [.200]	2	641214-2	
		DIM (L)	NO.OF POSN	ASSEMBLY	

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. HOOVER 26-JAN-2005 CHK D. BOSSI 26-JAN-2005		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 0.13 [.005] 3 PLC ± 4 PLC ± ANGLES ±		NAME MTA-100 HEADER ASSEMBLY, POLARIZED, NOTCHED, .025 SQUARE RIGHT ANGLE POST, .00030 GOLD PLATED	
		PRODUCT SPEC APPLICATION SPEC		SIZE GAGE CODE DRAWING NO.	
MATERIAL 		FINISH 		RESTRICTED TO WEIGHT A1 00779 C=641214	
CUSTOMER DRAWING				SCALE 8:1 SHEET 1 of 1 REV V1	