



T&B® Fittings

T&B Catalog Number:	LT75P
UPC Number:	78621045066
Description:	3/4" Non-Metallic liquidtight Bullet® - Straight. For use with liquidtight non-metallic Type B conduit or liquidtight non-metallic tubing.
Status:	Active

WEB_USE

-T&B Product Line	012
-------------------	-----

Features

-	Outside surface has friction reducing ridges.
-	Inner surface teeth bite into conduit or tubing to enhance clamping and sealing action.
-	Fitting ferrule designed to accept variations in conduit sizes and field conduit cuts.
-	Smooth ferrule profile reduces friction to ensure a tight conduit-to-fitting seal.

Application

-	The Bullet® meets performance requirements when terminating Type B liquidtight non-metallic conduit or flexible non-metallic tubing to a box or enclosure with knockout opening or threaded hub.
---	--

General

-Trade Size (inches)	3/4
-Material	Thermoplastic

Dimension Information

-Dimension A (inches)	0.582
-Dimension B (inches)	1.757
-Dimension C (inches)	1.740
-Dimension D-Minimum Throat (inches)	0.740
-E- NPT Thread (inches)	3/4-14
-A (mm)	14.78
-B (mm)	44.63
-C (mm)	44.20
-D (mm)	18.8
-Dimension A (inches)	0.582
-Dimension B (inches)	1.757
-Dimension C (inches)	1.740

Specifications

-3dmodel	Available on Website
----------	----------------------

Packaging

-T&B Inner Pack	10
-Package in Units	50
-T&B Sold in UOM	Each
-T&B Weight Per UOM	13.1 lbs. per 100

Application Support

-T&B Instruction Sheets	ta00998-tb2
-Guide to Nonmetallic Conduit Applications	Available on Website
-XTRAFLEX System Specifications	Available on Website

Notes

-*Note

Suitable for hazardous locations; Class I Div 2;
Class II Div 1 & 2; Groups E, F, G; Class III per
N.E.C.; Article 501-4, 502-4 and 503-3

Certifications



File Nbr:

E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com