

ESD-115-TT-05

SS, SD, ESD, ESS, HSS SERIES

PRECISION MACHINED SOCKET STRIPS



TS, TD, HTS, BBS,
BBD, BBL, BDL, BHS

For complete specifications see www.samtec.com?SS, www.samtec.com?ESS, www.samtec.com?SD, www.samtec.com?ESD or www.samtec.com?HSS

Lead-Free Solderable:
Wave only

For complete scope
of recognitions see
www.samtec.com/quality




TYPE STRIP	1	NO. PINS PER ROW	PLATING OPTION	LEAD STYLE	OPTION	OTHER OPTION
SS = Standard Single Row Socket	01 thru 32 = SS, ESS Series	01 thru 36 = HSS, SD & ESD Series	-S = 10 μ" (0.25 μm) Gold contact, Tin shell (Styles 2 & 22 only)		-L = Locking Socket Add -L suffix for locking lead socket in end positions. Requires Style -2 or -22 and .035" ± .003 DIA board hole.  Requires -T Plating Option	-N = Non Flush  N/A Style -5A
			-T = 30 μ" (0.76 μm) Gold contact, Tin shell			
			-G = 30 μ" (0.76 μm) Gold contact, 10 μ" (0.25 μm) Gold shell			
ESS = Elevated Single Row Socket			-TT = Tin contact and shell (Styles 1, 2, 4, and 05 except LIF N/A)	ALSO AVAILABLE (MOQ Required) Locking lead option on ESS and ESD series		
Styles -5A & -05 socket heads not countersunk.			LIF= Low Insertion Force			

ALSO AVAILABLE
(MOQ Required)


- Locking lead option on ESS and ESD series

For LIF specify -21A, -21B or -21C
(SS, HSS, SD)




LEAD STYLE	Y
-1A or -21A	(9.14) .360
-1B or -21B	(12.95) .510
-1C or -21C	(6.60) .260

For LIF specify -23
(ESS, ESD)



*For LIF specify -22 or -38 (SS, HSS, SD)



LEAD STYLE	X DIA	Y	Z
-2 or -22	(0.51) .020	(3.18) .125	(7.62) .300
-38	(0.51) .020	(4.57) .180	(8.89) .350
-5A	(0.89) .035	(12.95) .510	(17.86) .703

Locking lead available. See OPTION.

LEAD STYLE	A	B	C
-05	(17.86) .703	(13.46) .530	(4.39) .173
-03 or -23	(11.51) .453	(8.38) .330	(3.12) .123
-04	(14.05) .553	(10.92) .430	(3.12) .123

Note:
Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications.

Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.