

# 6-ft. SCSI Double Shielded Cable (HD50M/HD68M)

MODEL NUMBER: \$410-006



#### **Highlights**

- Premium double-shielded cable
- 34 twisted-pair conductors

#### **System Requirements**

 Any external SCSI III or II device or controller card requiring HD68 or HD50 interface

#### **Package Includes**

 6-ft. SCSI cable HD68M to HD50M double shielded

### Description

Multi-platform SCSI III to II external peripheral cable HD68M/HD50M. This 6ft cable is designed to connect two SCSI III (fast and wide) or SCSI II devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene.

#### **Features**

- Multi-platform SCSI III to II external peripheral cable
- HD68M/HD50M, 6-ft.
- Designed to connect two SCSI III or SCSI II devices together
- Constructed using double shielded 34 twisted pair high impedance cable
- Low-capacitance impedance matched 28 AWG stranded tinned copper insulated in polypropylene
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between

## **Specifications**

General Info		
Product Group	COMPUTER & STORAGE CABLES	
OVERVIEW		
Intended Application	Connecting Drives	
Cable Type	SCSI	
Model Type	SCSI III External	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

INPUT		
Cable Length (ft.)	6	
Cable Length (m)	1.83	
UPC ASSIGNMENT		
Unit Carton UPC#	037332014153	
PHYSICAL		
Color	Beige	
Style	SCSI	
CONNECTIONS		
Connector A	HD68 (MALE)	
Connector B	HD50 (MALE)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.