



PRODUCTS

INDUSTRY SOLUTIONS

CAREERS

RESOURCES


CONTACT MOLEX

FIND DISTRIBUTOR

Home: IDT and Solder Connectors >

Part Number: 26-32-6044

3.96mm KK® IDT Trifurcon™ Contact, 4 Circuits, Gold (Au), Feed-To, 20 Stranded, Blue ID Stripe



Series image - Reference only

Status:
Replacement:**OBsolete**

Contact Molex

Series:

[7674](#)

Category:

IDT and Solder Connectors

Overview:

[KK® Interconnect System - Molex](#) [CHECK DISTRIBUTOR INVENTORY](#) [Add to My Parts](#) [Email this page](#)Go to [Part Detail](#) ▾**Product Environmental Compliance**[EU ELV](#): Product not active[EU RoHS](#): Product not active[EU RoHS Phthalates](#): Product not active[China RoHS](#):[REACH SVHC](#): Product not active[Low-Halogen Status](#): Product not active [EU RoHS Certificate of Compliance \(PDF\)](#) [Multiple Part Product Compliance Statements](#)

EU RoHS, REACH SVHC, & Low-Halogen

[Multiple Part Industry Compliance Documents](#)

*IPC 1752A Class C

*IPC 1752A Class D

*Molex Product Compliance Declaration

Application Tooling**FAQ**

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global**Description****Product #**IDT - Manual - Handtool [11-21-5196](#)IDT Manual Handtool [62100-0400](#)Insertion Tool for 3.96mm Pitch IDT Crimp Terminals [63813-3503](#)**Crimp Quality Equipment**Molex also offers [wire strippers](#), [pull testers](#), [shut-height gauges](#), [micrometers](#) and more**Previously Available Application Tooling**

Check our list of old tooling that used to be available for this part

Questions on Product Environmental Compliance? Email ProductCompliance@molex.comRequest Molex's CMRT from conflictminerals@molex.com**Part Detail****COLLAPSE ALL****General**

Status	Obsolete
Category	IDT and Solder Connectors
Series	7674
Comments	Trifurcon™ contact
Overview	KK® Interconnect System - Molex
Product Name	KK®, Trifurcon™
UPC	800754565967

Physical

Circuits (Loaded)	4
Flammability	94V-2
Gender	Female
Glow-Wire Compliant	No
Lock to Mating Part	Yes
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	3.96mm
Temperature Range - Operating	0°C to +75°C
Wire Size AWG	20 Stranded

Electrical

(Please review the Product Specification for specific details.)

Voltage - Maximum 250V

Agency CertificationPlease find UL Certificates by searching the UL Database using the Molex Series Number.
[Click here to visit the UL Database](#)

UL

E29179

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1