

Heavy Duty Insulation Piercing Clip

- Plunger style insulation piercing clip with insulated jaws
- Stainless steel tip pierces insulated wires for otherwise inaccessible test points
- Extremely small piercing point allows for maximum integrity of insulation
- Pierces insulated wires from 30 AWG (.25 mm²) to 14 AWG (1.5 mm²)
- Recommended for use with Fluke TL24 Silicone Test Leads. Compatible with all test leads having standard 4 mm (.160") shrouded banana plugs
- Conforms to safety standard IEC 1010-2-031, CAT III @ 1000V, CAT IV @ 600V, Pollution Degree 2
- Maximum Current: 5 Amps
- One year warranty

⚠ WARNING to avoid possible electrical shock or personal injury:

- DO NOT USE above maximum ratings.
- Inspect test lead components for damage and check for continuity. DO NOT USE test leads that are damaged or show high resistance.
- Clean with a soft towel moistened with water and mild detergent. DO NOT IMMERSE in liquid.
- Intended for use only with instruments that have adequate arc explosion protection, such as Fluke CAT III and CAT IV rated instruments.
- For assistance or information on Fluke products call: 800-443-5853 in the USA and Canada, 31-40-2-675-200 in Europe or 425-446-5500 from all other countries; or visit us at our website at www.fluke.com.

Explanation of Symbol



AC or DC

Fluke Corporation
P.O. Box 9090
Everett, WA
98206-9090

Fluke Europe B.V.
P.O. Box 1186
5602 BD Eindhoven,
The Netherlands



PLEASE RECYCLE
Rev 2, 3/2001
©2001 Fluke Corporation
All rights reserved.
www.fluke.com
MADE IN AUSTRIA



P/N 873448

0 95969 01228 7