



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS


DDC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
2063	A	RELEASED	JN	08/04/09	JWM	08/06/09	JWM	08/06/09




SPECIFICATION

1. Lead Material: Tin plated copper
2. Soldering characteristic: MIL-STD-202, Method 208E.
3. Insulating coating: Flame retardant epoxy, UL-94V-0
4. Operating Current: 50mA~3.75A
5. Maximum Voltage: 60V
6. Temperature Range: -40°C to 85°C





Lead Size: 24 AWG
Ø0.51mm Diameter



Lead Size: 20 AWG
Ø0.81mm Diameter

Mfg. P/N	A	B	C	D	E	F	Hold Current I _H , A	Trip Current I _T , A	Max. Time To Trip at 5xI _H	Maximum Current I _{MAX} , A	Rated Voltage V _{MAX} , Vdc	Typical Power Pd, W	Resistance		Drawing Option	Time-to-Trip Curve Option
	Maximum	Maximum	Typical	Minimum	Maximum	Typical							R _{MIN} ohms	R _{MAX} ohms		
MC33169	7.4	12.7	5.1	7.6	3.1	1.1	0.1	0.2	4	40	60	0.38	2.5	7.5	Option 1	Option B
MC33170	7.4	12.7	5.1	7.6	3.1	1.1	0.17	0.34	3	40	60	0.48	2	8	Option 1	Option C
MC33171	7.4	12.7	5.1	7.6	3.1	1.1	0.2	0.4	2.2	40	60	0.41	1.83	4.4	Option 1	Option D
MC33172	7.4	12.7	5.1	7.6	3.1	1.1	0.25	0.5	2.5	40	60	0.45	1.25	3	Option 1	Option E
MC33173	7.4	13	5.1	7.6	3.1	1.1	0.3	0.6	3	40	60	0.49	0.88	2.1	Option 1	Option F
MC33174	7.6	13.5	5.1	7.6	3.1	1.1	0.4	0.8	3.8	40	60	0.56	0.55	1.29	Option 1	Option G
MC33175	7.9	13.7	5.1	7.6	3.1	1.1	0.5	1	4	40	60	0.77	0.5	1.17	Option 1	Option H
MC33176	9.7	14.5	5.1	7.6	3.1	1.1	0.65	1.3	5.3	40	60	0.88	0.31	0.72	Option 1	Option I
MC33177	10.4	15.2	5.1	7.6	3.1	1.1	0.75	1.5	6.3	40	60	0.92	0.25	0.6	Option 1	Option J
MC33178	11.7	15.8	5.1	7.6	3.1	1.1	0.9	1.8	7.2	40	60	0.99	0.2	0.47	Option 1	Option K
MC33179	13	18	5.1	7.6	3.1	1.4	1.1	2.2	8.2	40	60	1.5	0.15	0.38	Option 2	Option L
MC33180	14.5	19.6	5.1	7.6	3.1	1.4	1.35	2.7	9.6	40	60	1.7	0.12	0.3	Option 2	Option M
MC33181	16.3	21.3	5.1	7.6	3.1	1.4	1.6	3.2	11.4	40	60	1.9	0.09	0.22	Option 2	Option N
MC33182	17.8	22.9	5.1	7.6	3.1	1.4	1.85	3.7	12.6	40	60	2.1	0.08	0.19	Option 2	Option O
MC33183	21.3	26.4	10.2	7.6	3.1	1.4	2.5	5	15.6	40	60	2.5	0.05	0.13	Option 2	Option P
MC33184	24.9	30	10.2	7.6	3.1	1.4	3	6	19.8	40	60	2.8	0.04	0.1	Option 2	Option Q
MC33185	28.5	33.5	10.2	7.6	3.1	1.4	3.75	7.5	24	40	60	3.2	0.03	0.08	Option 2	Option R



DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:

Jason Nash

CHECKED BY:

JWM

APPROVED BY:

JWM

DATE:

08/06/09

DATE:

08/06/09

DATE:

08/06/09

DRAWING TITLE:

Radial Leaded PTC Resettable Fuse

SIZE

A

DWG. NO.

Ta-1190

ELECTRONIC FILE

Ta-1190.dwg

REV

A

SCALE:

NTS

U.O.M.:

INCHES [mm]

SHEET:

1 OF 1