

## <u>Important notes about Classic Panel Mount Indicator Catalog Pages</u>

## SCROLL DOWN TO VIEW CATALOG PAGE

This catalog page is out-of-print and is used with the understanding that the information shown could be out-of-date. In many cases, part numbers shown on this page are discontinued. Most notably, many "Complete Assembly" parts, which consist of a cap and a base, can no longer be ordered by the 14-digit ordering code. To obtain these parts, please order the cap and base part numbers separately. This process provides the components contained with the original "Complete Assembly" part number.

All Dialight Classic Panel Mount Indicators need a leading 3-digit numerical series. In some cases, this catalog will show a 2-digit series. In this case, please add a leading zero. For example, 81-0211-300 becomes **0**81-0211-300.

Part numbers listed on Dialight catalog pages designate parts with Red lenses. For ordering lens colors other than red, consult the chart below. In most cases, the color is dictated by the 7<sup>th</sup> digit. For example, 095-093**2**-003 for a green cap.

Lens Colors				
1 - Red 2 - Green	5 - White 6 - Light Yellow			
3 - Yellow	7 - Clear			
4 - Blue				

Click here for a cross reference guide to assembly part numbers.

<u>Click here to view Frequently Asked Questions concerning Panel Mount Indicators.</u>

SCROLL DOWN TO VIEW CATALOG PAGE

## Miniature Incandescent Indicators



T-3 1/4 **MINIATURE BAYONET BASE** 

See lamp ratings on page K.

Recognized under the component program of Underwriters' Laboratories Inc.

75W., 125V.






52-5710-0991-301 Screw-in lens cap

FOR MOUNTING IN 11/16" CLEARANCE HOLE FOR 2 TO 120V OPERATION


For materials and finishes of products in this group, see page 6D.



95-1310-0931-301 Screw-in lens cap



132-0410-0991-301 Screw-in lens cap



135-0410-1431-301 Screw-in lens cap

## WITH SCREW-IN LENS CAPS

**52 SERIES** 132 SERIES 135 SERIES

95 SERIES

BASE	PART	NUMBERS	

solder terminals	screw terminals	quick connect terminals	solder terminals *
1/16 X 13/16 O.D. FLANGE 1/16 FANEL (REF.) 1/16 FANEL (REF.) 1/10 2.00 S 8/164 =020 O.D. 1/10 FERNAL TOOTH LOCKWASHER 1/10 X 2.13/16 ACROSS E-LATS HEX. NUT 11/16 27 NS THO. MOUNTING BUSHING 1-SIGN MARKEO ON THE TERMINAL CONVECTED TO THE CENTER CONTACT.  5/54 X 1/18 5/54 X 1/18 5/55 X 1/18 5/56 X 1/18 5/56 X 1/18	SCREWS No. 4-36 THD.	1/16 QIA. HOLES	1/16 X 3/4 O.D. FLANGE  1/16 PANEL (REF.)  0.00 x 14 in 14 - 0.20 O.D.  INTERNAL TOOTH LOCKWASHER  3/32 X 13/16 A CARDS FLATS HEX. NUT  11/16 22 NS THO. MOUNTING BUSHING  + SIGM MARKED ON THE  TERMINAL CONNECTED TO  THE CENTER CONTACT.  5/64 X 1/8  PROJECTION BACK OF PANEL  1-21/32 MAX.
95-0410-09-301	95-1310-09-301	95-5710-09-301	95-9110-09-102

BASE PART NUMBERS	95-0410-09-301	95-1310-09-301	95-5710-09-301	95-9110-09-102
CAP PART NUMBERS	COMPLETE ASSEMBLY PART NUMBERS			
STOVEPIPE 52-0991 internal fluting 52-3191 internal fluting Lexan †	52-0410-0991-301	52-1310-0991-301	52-5710-0991-301	52-9110-0991-102
	52-0410-3191-301	52-1310-3191-301	52-5710-3191-301	52-9110-3191-102
97-6-27 NS THO.  95-0931 transparent 95-0971 translucent 95-3171 translucent Lexan f	95-0410-0931-301	95-1310-0931-301	95-5710-0931-301	95-9110-0931-102
	95-0410-0971-301	95-1310-0971-301	95-5710-0971-301	95-9110-0971-102
	95-0410-3171-301	95-1310-3171-301	95-5710-3171-301	95-9110-3171-102
STOVEPIPE 132-0991 internal fluting	132-0410-0991-301	132-1310-0991-301	132-5710-0991-301	132-9110-0991-102
CYLINDRICAL 135-1431 transparent 135-1471 translucent 135-3271 translucent Lexan † See page P for legends	135-0410-1431-301	135-1310-1431-301	135-5710-1431-301	135-9110-1431-102
	135-0410-1471-301	135-1310-1471-301	135-5710-1471-301	135-9110-1471-102
	135-0410-3271-301	135-1310-3271-301	135-5710-3271-301	135-9110-3271-102

<sup>\*</sup>These units are designed for commercial application where military standards are not required.

Order complete with lamp to be assured of receiving the indicator light and correct lamp together for immediate use.

<sup>†</sup> For use with lamps rated over 2 watts.