

TOSHIBA PHOTO DIODE SILICON PIN

TPS705, TPS706

SILICON PIN PHOTO DIODE FOR REMOTE CONTROL

VARIOUS KINDS OF REMOTE CONTROL SYSTEMS


SMOKE SENSOR

- Small package makes it possible to make a set thin.
- Fluorescent lamp disturbance light cut-off resin is used.
- High sensitivity TPS705 : I_{SC}=0.9μA (Typ.)
 TPS706 : I_{SC}=1.5μA (Typ.)
- High speed response : tr, tf=100ns (Typ.)
- Wide half value angle : $\theta \frac{1}{2} = \pm 65^\circ$ (Typ.)
- TLN105B, TLN115A, etc. are available as high radiant power infrared LEDs.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Reverse Voltage	V _R	20	V
Power Dissipation	P _D	150	mW
Power Dissipation Derating (T _a >25℃)	ΔP _D /℃	−2.36	mW/℃
Operating Temperature Range	T _{opr}	−30~80	℃
Storage Temperature Range	T _{stg}	−40~90	℃
Soldering Temperature · Time	T _{sol}	260℃·3s	

Unit in mm



() : REFERENCE VALUE

JEDEC	—
EIAJ	—
TOSHIBA	0-5J1

Weight : 0.23g (Typ.)

PIN CONNECTION



1. ANODE
2. CATHODE

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing a TOSHIBA product, to observe standard safety and handling practices and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

OPTO-ELECTRICAL CHARACTERISTICS (Ta = 25°C)






CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Short Circuit Current	I _{SC}	E = 0.1mW / cm ² (Note)	TPS705	0.5	0.9	μA
			TPS706	1.0	1.5	
Dark Current	I _D	V _R = 10V, E = 0	—	1	30	nA
Open Circuit Voltage	V _{OP}	E = 0.1mW / cm ² (Note)	150	250	—	mV
Capacitance	C _T	V _R = 3V, f = 1MHz	TPS705	—	12	pF
			TPS706	—	24	
Peak Sensitivity Wavelength	λ _P	—	—	970	—	nm
Switching Time	Rise Time	V _R = 10V, R _L = 1kΩ	—	100	—	ns
	Fall Time		—	100	—	
Half Value Angle	θ _½	—	—	±65	—	°

Note : Color temperature = 2870°K, Standard Tungsten Lamp.


PRECAUTION

Please be careful of the followings.


1. Soldering shall be performed at a portion of lead above 1.75mm from the body of the device.
2. If the lead is formed, the lead should be formed at a distance of 1.75mm from the body of the device.
Soldering shall be performed after lead forming.



DIRECTIONAL SENSITIVITY CHARACTERISTIC
(TYP.) ($T_a=25^{\circ}\text{C}$)



$C_T - V_R$ (TYP.)



SPECTRAL RESPONSE (TYP.)

