



NOTES, UNLESS OTHERWISE SPECIFIED:

TOOL WEIGHT: 1.25 lbs./ 0.56 Kg

ALL DIMENSIONS IN METRIC (mm)  
[ ] DIMENSIONS IN INCHES

HANDLES TO SPRING RETURN FREELY  
TO OPEN POSITION AFTER CRIMPING

TOOL FRAME MEMBERS AND FASTENERS  
TO INCORPORATE BLACK OXIDE FINISH

RECOMMENDED LUBE FOR FRAME LINKAGE:  
MOLYKOTE BR2 PLUS  
(SUPPLIER DOW CORNING)

ALL GAUGE MARKINGS TO BE OF  
EQUAL SIZE OF 1.27[0.05] HEIGHT.

TOOL DIV.  
ENGINEERING DEPT.

AUG 02 2006

COPY

										R23621BA_TP23621C01_01			
										PANDUIT CORP. TINLEY PARK, ILLINOIS			
										CD-CT-1700			
										UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ±.01 (.XX) ±.005 (.XXX) ±.002		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THREE ANGLE PROJECTION	
01	7-28-06	PWG	WJ	A PICTORIAL UPDATE				4212	---	RYB	MAT'L: 1:1		1:1
00	3-11-06	RYB	SZ	RELEASED				3609	---	RFL	DATE 3-11-06		TP23621C01
REV	DATE	BY	CHK	DESCRIPTION				ECN - R	CUST	SUP	GMH	SZ	C

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Panduit:](#)

[CT-1700](#)