

SN5473, SN54LS73A, SN7473, SN74LS73A DUAL J-K FLIP-FLOPS WITH CLEAR

SDLS118 – DECEMBER 1983 – REVISED MARCH 1988

- Package Options Include Plastic "Small Outline" Packages, Flat Packages, and Plastic and Ceramic DIPs
- Dependable Texas Instruments Quality and Reliability

description


The '73, and 'H73, contain two independent J-K flip-flops with individual J-K, clock, and direct clear inputs. The '73, and 'H73, are positive pulse-triggered flip-flops. J-K input is loaded into the master while the clock is high and transferred to the slave on the high-to-low transition. For these devices the J and K inputs must be stable while the clock is high.

The 'LS73A contains two independent negative-edge-triggered flip-flops. The J and K inputs must be stable one setup time prior to the high-to-low clock transition for predictable operation. When the clear is low, it overrides the clock and data inputs forcing the Q output low and the \bar{Q} output high.

The SN5473, SN54H73, and the SN54LS73A are characterized for operation over the full military temperature range of -55°C to 125°C . The SN7473, and the SN74LS73A are characterized for operation from 0°C to 70°C .

SN5473, SN54LS73A . . . J OR W PACKAGE
SN7473 . . . N PACKAGE
SN74LS73A . . . D OR N PACKAGE

(TOP VIEW)



73
FUNCTION TABLE

| INPUTS | | | | OUTPUTS | |
|--------|-----|---|---|---------|-------------|
| CLR | CLK | J | K | Q | \bar{Q} |
| L | X | X | X | L | H |
| H | ↓ | L | L | Q_O | \bar{Q}_O |
| H | ↓ | H | L | H | L |
| H | ↓ | L | H | L | H |
| H | ↓ | H | H | TOGGLE | |

'LS73A
FUNCTION TABLE

| INPUTS | | | | OUTPUTS | |
|--------|-----|---|---|---------|-------------|
| CLR | CLK | J | K | Q | \bar{Q} |
| L | X | X | X | L | H |
| H | ↓ | L | L | Q_O | \bar{Q}_O |
| H | ↓ | H | L | H | L |
| H | ↓ | L | H | L | H |
| H | ↓ | H | H | TOGGLE | |
| H | H | X | X | Q_O | \bar{Q}_O |

FOR CHIP CARRIER INFORMATION,
CONTACT THE FACTORY

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.





Copyright © 1988, Texas Instruments Incorporated

SN5473, SN54LS73A, SN7473, SN74LS73A DUAL J-K FLIP-FLOPS WITH CLEAR





SDLS118 – DECEMBER 1983 – REVISED MARCH 1988

logic symbols†




†These symbols are in accordance with ANSI/IEEE Std. 91-1984 and IEC Publication 617-12.

schematics of inputs and outputs



logic diagrams (positive logic)



absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

| | |
|---------------------------------------------------|----------------|
| Supply voltage, V_{CC} (See Note 1) | 7 V |
| Input voltage: '73 | 5.5 V |
| 'LS73A | 7 V |
| Operating free-air temperature range: SN54' | -55°C to 125°C |
| SN74' | 0° C to 70°C |
| Storage temperature range | -65°C to 150°C |

NOTE 1: Voltage values are with respect to network ground terminal.

SN5473, SN54LS73A, SN7473, SN74LS73A DUAL J-K FLIP-FLOPS WITH CLEAR

SDLS118 – DECEMBER 1983 – REVISED MARCH 1988

recommended operating conditions

| | | SN5473 | | | SN7473 | | | UNIT |
|-----------------|---------------------------------|----------|-----|------|--------|-----|------|------|
| | | MIN | NOM | MAX | MIN | NOM | MAX | |
| V _{CC} | Supply voltage | 4.5 | 5 | 5.5 | 4.75 | 5 | 5.25 | V |
| V _{IH} | High-level input voltage | 2 | | | 2 | | | V |
| V _{IL} | Low-level input voltage | | | 0.8 | | | 0.8 | V |
| I _{OH} | High-level output current | | | -0.4 | | | -0.4 | mA |
| I _{OL} | Low-level output current | | | 16 | | | 16 | mA |
| t _w | Pulse duration | CLK high | 20 | | 20 | | | ns |
| | | CLK low | 47 | | 47 | | | |
| | | CLR low | 25 | | 25 | | | |
| t _{su} | Input setup time before CLK↑ | 0 | | | 0 | | | ns |
| t _h | Input hold time data after CLK↑ | 0 | | | 0 | | | ns |
| T _A | Operating free-air temperature | -55 | | 125 | 0 | | 70 | °C |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS [†] | | | SN5473 | SN7473 | | | UNIT |
|------------------------------|--------------------------------------------------------------------------------------------------|-----------------------------------------------|-----|--------|------------------|-----|------|------|
| | MIN | TYP [‡] | MAX | MIN | TYP [‡] | MAX | | |
| V _{IK} | V _{CC} = MIN, I _I = -12 mA | | | -1.5 | | | -1.5 | V |
| V _{OH} | V _{CC} = MIN, V _{IH} = 2 V, V _{IL} = 0.8 V, I _{OH} = -0.4 mA | 2.4 | 3.4 | | 2.4 | 3.4 | | V |
| V _{OL} | V _{CC} = MIN, V _{IH} = 2 V, V _{IL} = 0.8 V, I _{OL} = 16 mA | 0.2 | 0.4 | | 0.2 | 0.4 | | V |
| I _I | V _{CC} = MAX, V _I = 5.5 V | | | 1 | | | 1 | mA |
| I _{IH} | J or K CLR or CLK | V _{CC} = MAX, V _I = 2.4 V | | | 40 | | 40 | μA |
| | | | | | 80 | | 80 | |
| I _{IL} | J or K CLR CLK | V _{CC} = MAX, V _I = 0.4 V | | | -1.6 | | -1.6 | mA |
| | | | | | -3.2 | | -3.2 | |
| | | | | | -3.2 | | -3.2 | |
| I _{OS} [§] | V _{CC} = MAX | -20 | -57 | -18 | -57 | | | mA |
| I _{CC} [¶] | V _{CC} = MAX, See Note 2 | | 10 | 20 | | 10 | 20 | mA |

[†] For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

[‡] All typical values are at V_{CC} = 5 V, T_A = 25°C.

[§] Not more than one output should be shorted at a time.

[¶] Average per flip-flop.

NOTE 2: With all outputs open, I_{CC} is measured with the Q and \bar{Q} outputs high in turn. At the time of measurement, the clock input is grounded.

switching characteristics, V_{CC} = 5 V, T_A = 25°C (see note 3)

| PARAMETER# | FROM (INPUT) | TO (OUTPUT) | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|------------------|--------------|----------------|------------------------------------------------|-----|-----|-----|------|
| f _{max} | | | R _L = 400 Ω, C _L = 15 pF | 15 | 20 | | MHz |
| t _{PLH} | CLR | \bar{Q} | | 16 | 25 | | ns |
| t _{PHL} | | Q | | 25 | 40 | | ns |
| t _{PLH} | CLK | Q or \bar{Q} | | 16 | 25 | | ns |
| t _{PHL} | | | | 25 | 40 | | ns |

#f_{max} = maximum clock frequency; t_{PLH} = propagation delay time, low-to-high-level output; t_{PHL} = propagation delay time, high-to-low-level output.

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.

recommended operating conditions

| | | SN54LS73A | | | SN74LS73A | | | UNIT |
|-------------|--------------------------------|------------------|-----|------|-----------|-----|------|------|
| | | MIN | NOM | MAX | MIN | NOM | MAX | |
| V_{CC} | Supply voltage | 4.5 | 5 | 5.5 | 4.75 | 5 | 5.25 | V |
| V_{IH} | High-level input voltage | 2 | | | 2 | | | V |
| V_{IL} | Low-level input voltage | | | 0.7 | | | 0.8 | V |
| I_{OH} | High-level output current | | | -0.4 | | | -0.4 | mA |
| I_{OL} | Low-level output current | | | 4 | | | 8 | mA |
| f_{clock} | Clock frequency | 0 | | 30 | 0 | | 30 | MHz |
| t_w | Pulse duration | CLK high | 20 | | 20 | | | ns |
| | | CLR low | 25 | | 20 | | | |
| t_{su} | Set up time-before CLK↓ | data high or low | 20 | | 20 | | | ns |
| | | CLR inactive | 20 | | 20 | | | |
| t_h | Hold time-data after CLK↓ | 0 | | | 0 | | | ns |
| T_A | Operating free-air temperature | -55 | | 125 | 0 | | 70 | °C |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS [†] | SN54LS73A | | | SN74LS73A | | | UNIT |
|------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------|------------------|------|-----------|------------------|------|------|
| | | MIN | TYP [‡] | MAX | MIN | TYP [‡] | MAX | |
| V_{IK} | $V_{CC} = \text{MIN}$, $I_I = -18 \text{ mA}$ | | | -1.5 | | | -1.5 | V |
| V_{OH} | $V_{CC} = \text{MIN}$, $V_{IH} = 2 \text{ V}$, $V_{IL} = \text{MAX}$, $I_{OH} = -0.4 \text{ mA}$ | 2.5 | 3.4 | | 2.7 | 3.4 | | V |
| V_{OL} | $V_{CC} = \text{MIN}$, $V_{IL} = \text{MAX}$, $V_{IH} = 2 \text{ V}$, $I_{OL} = 4 \text{ mA}$ | | 0.25 | 0.4 | 0.25 | 0.4 | | V |
| | $V_{CC} = \text{MIN}$, $V_{IL} = \text{MAX}$, $V_{IH} = 2 \text{ V}$, $I_{OL} = 8 \text{ mA}$ | | | | 0.35 | 0.5 | | |
| I_I | J or K CLR CLK | $V_{CC} = \text{MAX}$, $V_I = 7 \text{ V}$ | | 0.1 | | 0.1 | | mA |
| | | | | 0.3 | | 0.3 | | |
| | | | | 0.4 | | 0.4 | | |
| I_{IH} | J or K CLR CLK | $V_{CC} = \text{MAX}$, $V_I = 2.7 \text{ V}$ | | 20 | | 20 | | μA |
| | | | | 60 | | 60 | | |
| | | | | 80 | | 80 | | |
| I_{IL} | J or K CLR or CLK | $V_{CC} = \text{MAX}$, $V_I = 0.4 \text{ V}$ | | -0.4 | | -0.4 | | mA |
| | | | | -0.8 | | -0.8 | | |
| $I_{OS\$}$ | $V_{CC} = \text{MAX}$ | See Note 4 | -20 | -100 | -20 | -100 | | mA |
| I_{CC} (Total) | $V_{CC} = \text{MAX}$ | See Note 2 | | 4 | 6 | 4 | 6 | mA |

[†] For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

[‡] All typical values are at $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$.

$\$$ Not more than one output should be shorted at a time, and the duration of the short circuit should not exceed one second.

NOTE 2: With all outputs open, I_{CC} is measured with the Q and \bar{Q} outputs high in turn. At the time of measurement, the clock input is grounded.

NOTE 4: For certain devices where state commutation can be caused by shorting an output to ground, an equivalent test may be performed with $V_O = 2.25 \text{ V}$ and 2.125 V for the 54 family and the 74 family, respectively, with the minimum and maximum limits reduced to one half of their stated values.

switching characteristics, $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$ (see note 3)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | TEST CONDITIONS | | | UNIT | |
|-----------|-----------------|------------------|---------------------------------------------------|-----|-----|------|--|
| | | | MIN | TYP | MAX | | |
| f_{max} | | | $R_L = 2 \text{ k}\Omega$, $C_L = 15 \text{ pF}$ | 30 | 45 | MHz | |
| t_{PLH} | CLR or CLK | Q or \bar{Q} | | 15 | 20 | ns | |
| t_{PHL} | | | | 15 | 20 | ns | |

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.

PACKAGING INFORMATION

| Orderable Device | Status ⁽¹⁾ | Package Type | Package Drawing | Pins | Package Qty | Eco Plan ⁽²⁾ | Lead/Ball Finish | MSL Peak Temp ⁽³⁾ |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| 5962-9675101QCA | ACTIVE | CDIP | J | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| 5962-9675101QDA | ACTIVE | CFP | W | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| 5962-9675101QDA | ACTIVE | CFP | W | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| 5962-9675101VCA | ACTIVE | CDIP | J | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| 5962-9675101VCA | ACTIVE | CDIP | J | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| 5962-9675101VDA | ACTIVE | CFP | W | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| 5962-9675101VDA | ACTIVE | CFP | W | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| SN54LS73AJ | ACTIVE | CDIP | J | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| SN54LS73AJ | ACTIVE | CDIP | J | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| SN7473N | OBsolete | PDIP | N | 14 | | TBD | Call TI | Call TI |
| SN7473N | OBsolete | PDIP | N | 14 | | TBD | Call TI | Call TI |
| SN7473N3 | OBsolete | PDIP | N | 14 | | TBD | Call TI | Call TI |
| SN7473N3 | OBsolete | PDIP | N | 14 | | TBD | Call TI | Call TI |
| SN74LS73AD | ACTIVE | SOIC | D | 14 | 50 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73AD | ACTIVE | SOIC | D | 14 | 50 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73ADE4 | ACTIVE | SOIC | D | 14 | 50 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73ADE4 | ACTIVE | SOIC | D | 14 | 50 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73ADR | ACTIVE | SOIC | D | 14 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73ADR | ACTIVE | SOIC | D | 14 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73ADRE4 | ACTIVE | SOIC | D | 14 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73ADRE4 | ACTIVE | SOIC | D | 14 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM |
| SN74LS73AN | ACTIVE | PDIP | N | 14 | 25 | Pb-Free (RoHS) | CU NIPDAU | N / A for Pkg Type |
| SN74LS73AN | ACTIVE | PDIP | N | 14 | 25 | Pb-Free (RoHS) | CU NIPDAU | N / A for Pkg Type |
| SN74LS73ANE4 | ACTIVE | PDIP | N | 14 | 25 | Pb-Free (RoHS) | CU NIPDAU | N / A for Pkg Type |
| SN74LS73ANE4 | ACTIVE | PDIP | N | 14 | 25 | Pb-Free (RoHS) | CU NIPDAU | N / A for Pkg Type |
| SNJ54LS73AFD | OBsolete | LCCC | FK | 20 | | TBD | Call TI | N / A for Pkg Type |
| SNJ54LS73AFD | OBsolete | LCCC | FK | 20 | | TBD | Call TI | N / A for Pkg Type |
| SNJ54LS73AJ | ACTIVE | CDIP | J | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| SNJ54LS73AJ | ACTIVE | CDIP | J | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| SNJ54LS73AW | ACTIVE | CFP | W | 14 | 1 | TBD | Call TI | N / A for Pkg Type |
| SNJ54LS73AW | ACTIVE | CFP | W | 14 | 1 | TBD | Call TI | N / A for Pkg Type |

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBsolete: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


J (R-GDIP-T**)

14 LEADS SHOWN

CERAMIC DUAL IN-LINE PACKAGE



| PINS ** DIM | 14 | 16 | 18 | 20 |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A | 0.300 (7,62) BSC | 0.300 (7,62) BSC | 0.300 (7,62) BSC | 0.300 (7,62) BSC |
| B MAX | 0.785 (19,94) | .840 (21,34) | 0.960 (24,38) | 1.060 (26,92) |
| B MIN | — | — | — | — |
| C MAX | 0.300 (7,62) | 0.300 (7,62) | 0.310 (7,87) | 0.300 (7,62) |
| C MIN | 0.245 (6,22) | 0.245 (6,22) | 0.220 (5,59) | 0.245 (6,22) |




4040083/F 03/03

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package is hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

W (R-GDFP-F14)

CERAMIC DUAL FLATPACK



NOTES:

- All linear dimensions are in inches (millimeters).
- This drawing is subject to change without notice.
- This package can be hermetically sealed with a ceramic lid using glass frit.
- Index point is provided on cap for terminal identification only.
- Falls within MIL-STD 1835 GDFP1-F14 and JEDEC MO-092AB

FK (S-CQCC-N**)

LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. This package can be hermetically sealed with a metal lid.
- D. The terminals are gold plated.
- E. Falls within JEDEC MS-004

N (R-PDIP-T**)


16 PINS SHOWN

PLASTIC DUAL-IN-LINE PACKAGE



D (R-PDSO-G14)

PLASTIC SMALL-OUTLINE PACKAGE



NOTES:

- All linear dimensions are in inches (millimeters).
- This drawing is subject to change without notice.
- Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
- Falls within JEDEC MS-012 variation AB.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| Products | | Applications | |
|------------------|------------------------|---------------------|--------------------------------------------------------------------------|
| Amplifiers | amplifier.ti.com | Audio | www.ti.com/audio |
| Data Converters | dataconverter.ti.com | Automotive | www.ti.com/automotive |
| DSP | dsp.ti.com | Broadband | www.ti.com/broadband |
| Interface | interface.ti.com | Digital Control | www.ti.com/digitalcontrol |
| Logic | logic.ti.com | Military | www.ti.com/military |
| Power Mgmt | power.ti.com | Optical Networking | www.ti.com/opticalnetwork |
| Microcontrollers | microcontroller.ti.com | Security | www.ti.com/security |
| | | Telephony | www.ti.com/telephony |
| | | Video & Imaging | www.ti.com/video |
| | | Wireless | www.ti.com/wireless |

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2006, Texas Instruments Incorporated