

This document was generated on 07/11/2014

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 91778-0202

Status: **Active** 

**RAST 5 Connector System Overview:** 


5.00mm Appli-Mate RAST 5 IDT Housing, Indirect, Female, 10 Amp, 5 Circuit, Position **Description:** 

Keys 1b, Code Keys 03c, d40, Reference K01

**Documents:** 

3D Model Packaging Specification PK-90833-001 (PDF) **Drawing (PDF)** RoHS Certificate of Compliance (PDF)

Product Specification PS-99020-0037 (PDF)



**EU RoHS ELV and RoHS** 

Compliant **REACH SVHC Contains SVHC: No** 

Low-Halogen Status **Not Low-Halogen** 

**China RoHS** 

Series

Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

91778Series

**Mates With** 

90858 RAST Vertical Header,

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

**Description** RAST 5.0 Power Product #

0623006300

Semi-Automatic **Terminator Machine** for 6 and 10 AMP

**Agency Certification** 

**CSA** LR19980 UL E29179

General

Comments

**Product Family IDT** and Solder Connectors Series

91778

"This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options."

Yes

Crimp Quality Equipment

Overview **RAST 5 Connector System Product Name** RAST 5

**UPC** 883906929961

Use With RAST standard interface

**Physical** 

Circuits (Loaded) 4 Circuits (maximum)

Color - Resin Natural (White)

Flammability 94V-2 Gender Female Glow-Wire Compliant Yes Lock to Mating Part Yes

Material - Metal Phosphor Bronze

Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon Net Weight 3.332/gNumber of Rows

Packaging Type Tray Panel Mount No Pitch - Mating Interface 5.00mm Pitch - Termination Interface 5.00mm 5.080µm Plating min - Mating Plating min - Termination 5.080µm Polarized to Mating Part Yes Stackable No

Temperature Range - Operating -20C to +120C
Termination Interface: Style IDT or Pierce
Wire Size AWG 22, 24

**Electrical** 

Current - Maximum per Contact 10A Voltage - Maximum 250V AC

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification PK-90833-001
Product Specification PS-99020-0037
Sales Drawing SD-91778-001

This document was generated on 07/11/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

91778-0202