

General Specifications

Electrical Capacity (Resistive Load)

Logic Level: 0.4VA maximum @ 28V AC/DC maximum
(Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)
Note: Find additional explanation of operating range in Supplement section.

Other Ratings

Contact Resistance: 50 milliohms maximum
Insulation Resistance: 500 megohms minimum @ 500V DC
Dielectric Strength: 500V AC minimum between contacts for 1 minute minimum;
500V AC minimum between contacts & case for 1 minute minimum
Mechanical Life: 100,000 operations minimum for On-None-On & On-Off-On
50,000 operations minimum for other circuits
Electrical Life: 50,000 operations minimum
Nominal Operating Force: 1.47N (momentary); 1.18N (maintained) for .394" (10.0mm) toggles
2.73N (momentary); 1.84N (maintained) for all other toggles
Contact Timing: Nonshorting (break-before-make)
Angle of Throw: 26°

Materials & Finishes

Toggle: Glass fiber reinforced polyamide for antistatic; nickel plated brass for all others
Case Housing: Glass fiber reinforced polyamide
Support Bracket: Tin plated phosphor bronze
Movable Contact: Phosphor bronze with gold plating
Stationary Contacts: Brass with gold plating
Terminals: Brass with gold plating

Environmental Data

Operating Temperature Range: -30°C through +85°C (-22°F through +185°F)
Humidity: 90 ~ 95% humidity for 240 hours @ 40°C (104°F)
Vibration: 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range
& returning in 1 minute; 3 right angled directions for 2 hours
Shock: 50G (490m/s²) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

PCB Processing

Soldering: Wave Soldering Recommended. See Profile A in Supplement section.
Manual Soldering: See Profile B in Supplement section.
Cleaning: Automated cleaning. See Cleaning Specifications in Supplement section.

Standards & Certifications

The A Series toggles have not been tested for UL recognition or CSA certification.
These switches are designed for use in a low-voltage, low-current, logic-level circuit.
When used as intended in a logic-level circuit, the results do not produce hazardous energy.

Distinctive Characteristics

Subminiature size saves space on PC boards.

Specifically developed for logic-level applications.

Totally sealed body construction prevents contact contamination and allows time- and money-saving automated soldering and cleaning.


Award-winning STC contact mechanism with benefits unavailable in conventional mechanisms: smoother, positive detent actuation, increased contact stability and unparalleled logic-level reliability. (Additional STC details in Terms & Acronyms; see Supplement contents.)

Molded-in, epoxy sealed or ultrasonically welded terminals lock out flux, solvents, and other contaminants.


.100" x .100" (2.54mm x 2.54mm) terminal spacing conforms to standard PC board grid spacing.

Toggle option in antistatic material available for dissipating electrostatic discharges.


Matching indicators available.



Actual Size




TYPICAL SWITCH ORDERING EXAMPLE




DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

A12JV







Process Sealed Subminiature Toggles

POLES & CIRCUITS

		Toggle Position () = Momentary			Connected Terminals			Throw & Schematics	
Pole	Model	Up 	Center 	Down 	Up 	Center 	Down 	Note: Terminal numbers are not actually on the switch.	
SP	A11	OFF	NONE	ON	OPEN	OPEN	3-1	SPST	
SP	A12	ON	NONE	ON	2-3	OPEN	2-1	SPDT	
	A13	ON	OFF	ON					
	A15	ON	NONE	(ON)					
	A1R	(ON)	NONE	ON					
	A18	(ON)	OFF	(ON)					
	A19	ON	OFF	(ON)					
	A1S	(ON)	OFF	ON					
DP	A22	ON	NONE	ON	2-3 5-6	OPEN	2-1 5-4	DPDT	
	A23	ON	OFF	ON					
	A25	ON	NONE	(ON)					
	A2R	(ON)	NONE	ON					
	A28	(ON)	OFF	(ON)					
	A29	ON	OFF	(ON)					
	A2S	(ON)	OFF	ON					


For 3 Throw (3-on)

Connected Terminals & Schematics					External Connection
Pole	Model	Up	Center	Down	
SP	A24	ON	ON	ON	The SP3T model utilizes a double pole base. External connections must be made during field installation. 
	A26	(ON)	ON	(ON)	
	A27	ON	ON	(ON)	
					


TOGGLES

Standard Material & Finish: Brass with Bright Nickel Material & Finish for J2: Matte finish black glass fiber reinforced polyamide

A .394" (10.0mm) Bat




J .248" (6.3mm) Bat




J2 .248" (6.3mm) Antistatic Bat

Dissipating 20Kv ESD: Straight PC


Dissipating 10Kv ESD: Straight PC with Bracket, Right Angle, & Vertical




E .394" (10.0mm) Flatted



H .248" (6.3mm) Flatted



K Snap Top for Paddles




PC TERMINALS

Use of a support bracket is recommended to increase PCB mounting strength and stability.


P

Straight




B

Straight with Bracket




B1

**Straight with Inline Bracket
Single Pole only**




H

**Right Angle
with Bracket**




V

Vertical with Bracket



V1

**Vertical with Inline Bracket
Single Pole only**




CAPS & PADDLES

G

**AT4003
.394" (10.0mm) Bat Lever Cap**


Material: PVC
Colors Available:
A, B, C



J

**AT4064
.248" (6.3mm) Bat Lever Cap**


Material: PVC
Colors Available:
A, B, C



A

**AT467
Short Paddle**


Material: Polyamide
Colors Available:
A, B, C, E, F, G, H



B

**AT468
Long Paddle**

Material: Polyamide
Colors Available:
A, B, C, E, F, G, H



Color Codes:

A

Black

B

White

C

Red

E

Yellow

F

Green

G

Blue





H

Gray

TYPICAL SWITCH DIMENSIONS

Single Pole

Straight PC







A11 models do not have Terminal 2

A12AP

Double Pole






Straight PC



A22AP

Single Pole

Straight PC • Bracket







B Terminals

B1 Terminals

A12AB

Double Pole

Straight PC • Bracket







A22AB

A	Toggles
	Rockers
	Pushbuttons
	Illuminated PB
	Programmable
	Keylocks
	Rotaries
	Slides
	Tactiles
	Tilt
	Touch
	Indicators
	Accessories
	Supplement

TYPICAL SWITCH DIMENSIONS

Right Angle PC





Single Pole



A12AH

Right Angle PC






Double Pole



A22AH

Vertical PC

Single Pole







A12AV

V Terminals

V1 Terminals

Vertical PC

Double Pole



A22AV