
## SMD ONE PORT 315.0 MHz SAW RESONATOR

ASR315S2





#### > STANDARD SPECIFICATIONS:

CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.
Center Frequency Fo			MHz	314.925	315.000	315.075
Tolerance from Fo			KHz		±75	
Insertion Loss			dB	-	1.7	2.4
Quality Factor	Unloaded		-		12,200	
	50Ω loaded				1,500	
Temperature Stability	Turnover Temperature		°C	20	35	50
	Turnover Frequency		KHz		Fc	
	Freq. Temp. Coefficient		ppm/°C <sup>2</sup>		0.032	
Frequency Aging			ppm/year		±10	
DC Insulation Resistance			MΩ	1.0		
RF Equivalent RLC Model	Motional Resistance R <sub>1</sub>		Ω		14	25
	Motional Inductance L <sub>1</sub>		μΗ		86	
	Motional Capacitance C <sub>1</sub>		fF		2.95	
	Shunt Capacitance C <sub>0</sub>		pF		2.4	
Operating temp.	°C			-45°C to +85°C		
Storage temp.	°C			-45°C to +85°C		
Max. Rating	DC voltage V			±10V		
RF Power Dissipation		dBm		(	)	

(\*) Option 75 for ± 0.075MHz

Data measured with: Source Impedance: Zs=50Ω, Load Impedance: ZL=50Ω, TA=25°C

Electrostatic Sensitive Device. Handle with precaution.

#### > MARKING:

- 315R - A ZYX (315.0 Frequency in MHz) (ZY: Date code Z for month from A to L; Y for year,

I.e. 4 for 2004


> FREQUENCY RESPONSE

X: Traceability code)

PIN NO.	CONNECTIONS		
1	Input/Output		
2	GND		
3	Output/Input		
4	GND		

### > TEST CIRCUIT:

# > OUTLINE DRAWING:



ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.



