

### 325/326 Series Lead-Free 3AB, Slo-Blo® Fuse



#### Agency Approvals

| Agency                                                                              | Agency File Number                                                                                                                                                                                    | Ampere Range                                                                         |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|    | E10480                                                                                                                                                                                                | 0.250A - 10A                                                                         |
|    | E10480                                                                                                                                                                                                | 12A - 30A                                                                            |
|    | 29862                                                                                                                                                                                                 | 0.250A - 30A                                                                         |
|  | Cartridge:<br>NBK 030805-E10480A<br>NBK 030805-E10480C<br>NBK 030805-E10480E<br>NBK 260106-JP1021A<br>Leaded:<br>NBK 030805-E10480B<br>NBK 030805-E10480D<br>NBK 030805-E10480F<br>NBK 260106-JP1021B | 1A-3.2A<br>4A-5A<br>6.25A-15A<br>20A-30A<br>1A-3.2A<br>4A-5A<br>6.25A-15A<br>20A-30A |
|  | SU05001-5010<br>SU05001-5011<br>SU05001-5012<br>SU05001-6006<br>SU05001-6007                                                                                                                          | 7-10A<br>12A, 15A<br>20A<br>2.8A-3.2A<br>2.5A                                        |
|  | T 50239752 01                                                                                                                                                                                         | *12A/*15A/*20A                                                                       |
|  | N/A                                                                                                                                                                                                   | 0.010A - 30A                                                                         |

\* Approved for cartridge version only

#### Description

The 3AB Slo-Blo® Fuse with ceramic body construction permits higher interrupting ratings and voltage ratings. Ideal for applications where high current loads are expected.

#### Features

- In accordance with UL Standard 248-14
- RoHS compliant and Lead-free
- Available in cartridge and axial lead format and with various forming dimensions

#### Applications

Used as supplementary protection in appliance or utilization equipment to provide individual protection for components or internal circuits.

#### Electrical Characteristics for Series

| % of Ampere Rating | Ampere Rating | Opening Time                |
|--------------------|---------------|-----------------------------|
| 100%               | 0.010A – 30A  | 4 hours, Minimum            |
| 135%               | 0.010A – 30A  | 1 hour, Maximum             |
| 200%               | 0.010A – 3.2A | 5 sec., Min., 30 sec., Max. |
|                    | 4A – 30A      | 5 sec., Min., 60 sec., Max. |

#### Additional Information



**Datasheet  
325 Series**



**Resources  
325 Series**



**Samples  
325 Series**



**Accessories  
325 Series**



**Datasheet  
326 Series**



**Resources  
326 Series**



**Samples  
326 Series**



**Accessories  
326 Series**

For recommended fuse accessories for this product series, see '[Recommended Accessories](#)' section.

### Electrical Characteristic Specifications by Item

| Amp Code | Ampere Rating (A) | Voltage Rating (V) | Interrupting Rating                       | Nominal Cold Resistance (Ohms) | Nominal Melting I <sup>2</sup> t (A <sup>2</sup> sec) | Agency Approvals |    |    |    |    |      |   |
|----------|-------------------|--------------------|-------------------------------------------|--------------------------------|-------------------------------------------------------|------------------|----|----|----|----|------|---|
|          |                   |                    |                                           |                                |                                                       | PS E             | UL | SP | UL | CE | △    | Ⓚ |
| .010     | 0.01              | 250                | 100A@250Vac                               | 3324.8000                      | 0.00013                                               |                  |    |    |    | x  |      |   |
| .031     | 0.031             | 250                |                                           | 332.5000                       | 0.0110                                                |                  |    |    |    | x  |      |   |
| .062     | 0.062             | 250                |                                           | 91.7000                        | 0.0276                                                |                  |    |    |    | x  |      |   |
| .100     | 0.1               | 250                |                                           | 33.5500                        | 0.0870                                                |                  |    |    |    | x  |      |   |
| .125     | 0.125             | 250                |                                           | 22.4500                        | 0.100                                                 |                  |    |    |    | x  |      |   |
| .150     | 0.15              | 250                |                                           | 15.4500                        | 0.143                                                 |                  |    |    |    | x  |      |   |
| .175     | 0.175             | 250                |                                           | 8.9200                         | 0.350                                                 |                  |    |    |    | x  |      |   |
| .187     | 0.187             | 250                |                                           | 7.7250                         | 0.330                                                 |                  |    |    |    | x  |      |   |
| .200     | 0.2               | 250                |                                           | 6.7700                         | 0.316                                                 |                  |    |    |    | x  |      |   |
| .250     | 0.25              | 250                | 100A@250Vac<br>10KA@125Vac<br>10KA@125Vdc | 4.4300                         | 0.804                                                 |                  |    | x  | x  | x  |      |   |
| .300     | 0.3               | 250                |                                           | 3.2200                         | 1.230                                                 |                  |    | x  | x  | x  |      |   |
| .375     | 0.375             | 250                |                                           | 2.1550                         | 1.20                                                  |                  |    | x  | x  | x  |      |   |
| .400     | 0.4               | 250                |                                           | 1.9350                         | 1.33                                                  |                  |    | x  | x  | x  |      |   |
| .500     | 0.5               | 250                |                                           | 1.3000                         | 4.80                                                  |                  |    | x  | x  | x  |      |   |
| .600     | 0.6               | 250                |                                           | 0.9495                         | 3.90                                                  |                  |    | x  | x  | x  |      |   |
| .700     | 0.7               | 250                |                                           | 0.7215                         | 6.42                                                  |                  |    | x  | x  | x  |      |   |
| .750     | 0.75              | 250                |                                           | 0.6410                         | 13.00                                                 |                  |    | x  | x  | x  |      |   |
| .800     | 0.8               | 250                |                                           | 0.5725                         | 8.20                                                  |                  |    | x  | x  | x  |      |   |
| 001.     | 1                 | 250                |                                           | 0.3890                         | 16.3                                                  | x                |    | x  | x  | x  |      |   |
| 01.2     | 1.2               | 250                |                                           | 0.2860                         | 22.0                                                  | x                |    | x  | x  | x  |      |   |
| 1.25     | 1.25              | 250                |                                           | 0.2680                         | 40.0                                                  | x                |    | x  | x  | x  |      |   |
| 01.5     | 1.5               | 250                |                                           | 0.1975                         | 59.7                                                  | x                |    | x  | x  | x  |      |   |
| 01.6     | 1.6               | 250                |                                           | 0.1760                         | 66.0                                                  | x                |    | x  | x  | x  |      |   |
| 002.     | 2                 | 250                |                                           | 0.1210                         | 118.0                                                 | x                |    | x  | x  | x  |      |   |
| 02.5     | 2.5               | 250                |                                           | 0.0835                         | 185.0                                                 | x                |    | x  | x  | x  |      | x |
| 02.8     | 2.8               | 250                |                                           | 0.0695                         | 232.0                                                 | x                |    | x  | x  | x  |      | x |
| 003.     | 3                 | 250                |                                           | 0.0605                         | 200.0                                                 | x                |    | x  | x  | x  |      | x |
| 03.2     | 3.2               | 250                | 100A@250Vac<br>10KA@125Vac                | 0.0539                         | 214.0                                                 | x                |    | x  | x  | x  |      | x |
| 004.     | 4                 | 250                | 400A@250Vac<br>10KA@125Vac<br>10KA@125Vdc | 0.0761                         | 9.71                                                  | x                |    | x  | x  | x  |      |   |
| 005.     | 5                 | 250                |                                           | 0.0522                         | 25.0                                                  | x                |    | x  | x  | x  |      |   |
| 6.25     | 6.25              | 250                |                                           | 0.0346                         | 60.4                                                  | x                |    | x  | x  | x  |      |   |
| 007.     | 7                 | 250                |                                           | 0.0227                         | 47.3                                                  | x                |    | x  | x  | x  |      | x |
| 008.     | 8                 | 250                |                                           | 0.0193                         | 67.1                                                  | x                |    | x  | x  | x  |      | x |
| 010.     | 10                | 250                |                                           | 0.0132                         | 137                                                   | x                |    | x  | x  | x  |      | x |
| 012.     | 12                | 250                | 400A@250Vac<br>10KA@125Vac<br>600A@125Vdc | 0.0067                         | 129                                                   | x                | x  | x  |    | x  | x*** | x |
| 012.*    | 12                | 250                | 1500A@250Vac                              | 0.0011                         | 618                                                   |                  | x  | x  |    | x  |      |   |
| 015.     | 15                | 250                | 400A@250Vac<br>10KA@125Vac<br>600A@125Vdc | 0.0050                         | 245                                                   | x                | x  | x  |    | x  | x*** | x |
| 015.*    | 15                | 250                | 1500A@250Vac                              | 0.0083                         | 760                                                   |                  | x  | x  |    | x  |      |   |
| 020.     | 20                | 250                | 400A@250Vac<br>10KA@125Vac<br>600A@125Vdc | 0.0034                         | 575                                                   | x                | x  | x  |    | x  | x*** | x |
| 020.*    | 20                | 250                | 1500A@250Vac                              | 0.0042                         | 2500                                                  |                  | x  | x  |    | x  |      |   |
| 025.**   | 25                | 250                | 1500A@250Vac                              | 0.0032                         | 4682                                                  |                  | x  |    |    | x  |      |   |
| 025.     | 25                | 250                | 400A@250Vac<br>10KA@60Vdc                 | 0.0024                         | 1030                                                  | x                | x  | x  |    | x  |      |   |
| 030.     | 30                | 250                | 600A@125Vdc                               | 0.0019                         | 1690                                                  | x                | x  | x  |    | x  |      |   |


\*Higher I<sup>2</sup>t version available. Please add suffix "D" to part numbers. For instance, 0325020.MXDP, 0326020.MXDP

I<sup>2</sup>t test at 10x rated current.

\*\*Higher I<sup>2</sup>t version available. Please add suffix "W" to part numbers. For instance, 0325025.MXWP


\*\*\*Approved for cartridge versions only, and interrupting rating is 400A@125Vac and 400A@250Vac

### Temperature Re-rating Curve




Note:  
Derating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

### Average Time Current Curves



### Soldering Parameters - Wave Soldering



### Recommended Process Parameters:

| Wave Parameter                                       | Lead-Free Recommendation          |
|------------------------------------------------------|-----------------------------------|
| Preheat:<br>(Depends on Flux Activation Temperature) | (Typical Industry Recommendation) |
| Temperature Minimum:                                 | 100°C                             |
| Temperature Maximum:                                 | 150°C                             |
| Preheat Time:                                        | 60-180 seconds                    |
| Solder Pot Temperature:                              | 260°C Maximum                     |
| Solder Dwell Time:                                   | 2-5 seconds                       |

### Recommended Hand-Solder Parameters:

Solder Iron Temperature: 350°C +/- 5°C  
Heating Time: 5 seconds max.

**Note:** These devices are not recommended for IR or Convection Reflow process.


### Product Characteristics

|                          |                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------|
| <b>Materials</b>         | Body: Ceramic<br>Cap: Nickel-plated brass<br>Leads: Tin-plated Copper                   |
| <b>Terminal Strength</b> | MIL-STD-202, Method 211, Test Condition A                                               |
| <b>Solderability</b>     | MIL-STD-202 Method 208                                                                  |
| <b>Product Marking</b>   | Cap1: Brand logo, current and voltage ratings<br>Cap2: Series and agency approval marks |


|                              |                                                                                                        |
|------------------------------|--------------------------------------------------------------------------------------------------------|
| <b>Operating Temperature</b> | -55°C to +125°C                                                                                        |
| <b>Thermal Shock</b>         | MIL-STD-202, Method 107, Test Condition B: (5 cycles - 65°C to 125°C)                                  |
| <b>Vibration:</b>            | MIL-STD-202, Method 201                                                                                |
| <b>Humidity</b>              | MIL-STD-202, Method 103, Test Condition A: High RH (95%) and Elevated temperature (40°C) for 240 hours |
| <b>Salt Spray</b>            | MIL-STD-202, Method 101, Test Condition B                                                              |

### Dimensions

Measurements displayed in millimeters (inches)



### Part Numbering System



### Packaging

| Packaging Option  | Packaging Specification | Quantity | Quantity & Packaging Code | Taping Width |
|-------------------|-------------------------|----------|---------------------------|--------------|
| <b>325 Series</b> |                         |          |                           |              |
| Bulk              | N/A                     | 5        | VX                        | N/A          |
| Bulk              | N/A                     | 100      | HX                        | N/A          |
| Bulk              | N/A                     | 1000     | MX                        | N/A          |
| Bulk              | N/A                     | 1000     | MX52 (long lead)          | N/A          |
| Bulk              | N/A                     | 1000     | MX52L (long lead)         | N/A          |
| Bulk              | N/A                     | 1000     | MXD                       | N/A          |
| Bulk              | N/A                     | 1000     | MXF31                     | N/A          |
| Bulk              | N/A                     | 1000     | MXW                       | N/A          |
| <b>326 Series</b> |                         |          |                           |              |
| Bulk              | N/A                     | 5        | VX                        | N/A          |
| Bulk              | N/A                     | 100      | HX                        | N/A          |
| Bulk              | N/A                     | 1000     | MX                        | N/A          |
| Bulk              | N/A                     | 1000     | MXCC                      | N/A          |
| Bulk              | N/A                     | 1000     | MXD                       | N/A          |

### Recommended Accessories

| Accessory Type | Series                 | Description                                                               | Max Application Voltage | Max Application Amperage |
|----------------|------------------------|---------------------------------------------------------------------------|-------------------------|--------------------------|
| Holder         | <a href="#">155100</a> | Twist-Lock In-Line Fuseholder                                             | 32                      | 20                       |
|                | <a href="#">342</a>    | Traditional Panel Mount Fuseholder                                        | 250                     | 20                       |
|                | <a href="#">346</a>    | Panel Mount Flip-Top Shock-Safe Fuseholder                                | 250                     | 15                       |
|                | <a href="#">345</a>    | Shock-Safe Fuseholder with PC Mount, Solder Mount and Panel Mount options | 250                     | 20                       |
| Block          | <a href="#">354</a>    | Low Profile OMNI-BLOK® Fuse Block                                         | 600                     | 30                       |
|                | <a href="#">359</a>    | High Current Screw Terminal Fuse Block                                    |                         | 30                       |
| Clip           | <a href="#">122</a>    | High Current Traditional PC Board Fuse Clip                               | 1000                    | 30                       |
|                | <a href="#">101</a>    | Rivet/Eyelet Type Fuse Clip                                               | 1000                    | 15                       |

**Notes:**

1. Do not use in applications above rating.
2. Please refer to fuseholder data sheet for specific re-rating information.
3. Please contact Littelfuse for applications greater than the max voltage and amperage shown.

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Littelfuse:

[325010](#) [325030](#) [326002](#) [326015](#) [325005](#) [326008](#) [326.500](#) [326001](#) [326005](#) [326010](#) [326012](#) [326020](#)  
[032602.8HXP](#) [0326025.HXP](#) [0325.031HXP](#) [0326.200H](#) [0326.400MXP](#) [032603.2H](#) [0325.031M](#) [0326.250HXP](#)  
[0326.700HXP](#) [0326007.MXP](#) [0325001.H](#) [0325002.MXP](#) [0326.750HXP](#) [0326010.HXP](#) [0326020.H](#) [0325.100MXP](#)  
[032502.8H](#) [0325020.H](#) [0325.150MXP](#) [032501.2HXP](#) [0325.375MXP](#) [0325003.HXP](#) [0325005.M](#) [032501.5H](#)  
[0326.150MXP](#) [0326020.HXP](#) [0325.700M](#) [0325.750MXP](#) [032601.6MXP](#) [0326030.M](#) [0326001.HXP](#) [0326.500HXP](#)  
[0326.500MXP](#) [0325.062M](#) [0325.125H](#) [0325.187M](#) [032502.8M](#) [0326.175M](#) [0326005.HXP](#) [0325.031MXP](#)  
[032503.2MXP](#) [0326.400HXP](#) [0326.800HXP](#) [0325.700HXP](#) [0325030.H](#) [0325.100M](#) [032502.5HXP](#) [0326.400M](#)  
[0326007.HXP](#) [032502.5H](#) [0325.010HXP](#) [0326.125H](#) [0326.375MXP](#) [0326015.MXP](#) [0325.100H](#) [0325.187MXP](#)  
[0325.600MXP](#) [0325004.H](#) [032501.6HXP](#) [0325015.HXP](#) [032503.2HXP](#) [0326004.H](#) [032601.5M](#) [0326001.H](#)  
[0326020.M](#) [0325.062H](#) [0326.375H](#) [0326002.HXP](#) [0325004.HXP](#) [0325008.H](#) [0326.125M](#) [03261.25MXP](#)  
[0326030.HXP](#) [032501.5M](#) [0326.031M](#) [0326.062M](#) [0326.125HXP](#) [0326005.M](#) [0325004.MXP](#) [0325012.MXP](#)  
[0326.010HXP](#) [0325.375H](#) [0325012.HXP](#) [032602.8M](#) [0325015.MXP](#) [0326.700M](#) [0325.400M](#) [032503.2H](#)