

TLV2217-33 LOW-DROPOUT 3.3-V FIXED-VOLTAGE REGULATORS

SLVS067G – MARCH 1992 – REVISED JULY 1999


- Fixed 3.3-V Output
- $\pm 1\%$ Maximum Output Voltage Tolerance at $T_J = 25^\circ\text{C}$
- 500-mV Maximum Dropout Voltage at 500 mA
- 500-mA Dropout Current
- $\pm 2\%$ Absolute Output Voltage Variation
- Internal Overcurrent Limiting
- Internal Thermal-Overload Protection
- Internal Overvoltage Protection
- Package Options Include Plastic Flange Mounted (KTP), Power (KC), and Thin Shrink Small-Outline (PW) Packages

description


The TLV2217-33 is a low-dropout 3.3-V fixed-voltage regulator. The regulator is capable of sourcing 500 mA of current with an input-output differential of 0.5 V, or less. The TLV2217-33 provides internal overcurrent limiting, thermal-overload protection, and overvoltage protection.

The 0.5-V dropout for the TLV2217-33 makes it ideal for battery applications in 3.3-V logic systems. For example, battery input voltage to the regulator can drop as low as 3.8 V, and the TLV2217-33 can continue to regulate the system. For higher voltage systems, the TLV2217-33 can be operated with a continuous input voltage of 12 V.


The TLV2217-33 regulators are characterized for virtual junction temperature operation from 0°C to 125°C .



HEAT SINK – These terminals have an internal resistive connection to ground and should be grounded or electrically isolated.



The GND terminal is in electrical contact with the mounting base.



The GND terminal is in electrical contact with the mounting base.

AVAILABLE OPTIONS

T_J	PACKAGED DEVICES			CHIP FORM (Y)
	PLASTIC POWER (KC)	SURFACE MOUNT (PW)	PLASTIC FLANGE MOUNT (KTP)	
0°C to 125°C	TLV2217-33KC	TLV2217-33PW	TLV2217-33KTP	TLV2217-33Y

The KTP and PW packages are available taped and reeled only. Add R suffix to device type (e.g., TLV2212-33PWR). Chip forms are tested at 25°C .



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1999, Texas Instruments Incorporated

TLV2217-33

LOW-DROPOUT 3.3-V FIXED-VOLTAGE REGULATORS

SLVS067G – MARCH 1992 – REVISED JULY 1999

absolute maximum ratings over operating virtual junction temperature range (unless otherwise noted)[†]

Continuous input voltage, V_I	16 V
Package thermal impedance, θ_{JA} (see Notes 1 and 2):	
KC package	22°C/W
KTP package	28°C/W
PW package	83°C/W
Storage temperature range, T_{stg}	-65°C to 150°C

[†] Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. Maximum power dissipation is a function of $T_J(\max)$, θ_{JA} , and T_A . The maximum allowable power dissipation at any allowable ambient temperature is $P_D = (T_J(\max) - T_A)/\theta_{JA}$. Operating at the absolute maximum T_J of 150°C can impact reliability. Due to variation in individual device electrical characteristics and thermal resistance, the built-in thermal overload protection may be activated at power levels slightly above or below the rated dissipation.
2. The package thermal impedance is calculated in accordance with JESD 51, except for through-hole packages, which use a trace length of zero.

recommended operating conditions

	MIN	MAX	UNIT
Input voltage, V_I	3.8	12	V
Output current, I_O	0	500	mA
Operating virtual junction temperature range, T_J	0	125	°C

electrical characteristics at $V_I = 4.5$ V, $I_O = 500$ mA, $T_J = 25$ °C (unless otherwise noted)

PARAMETER	TEST CONDITIONS [‡]	TLV2217-33			UNIT	
		MIN	TYP	MAX	UNIT	
Output voltage	$I_O = 20$ mA to 500 mA, $V_I = 3.8$ V to 5.5 V	$T_J = 25$ °C	3.267	3.30	3.333	V
		$T_J = 0$ °C to 125°C	3.234		3.366	
Input voltage regulation	$V_I = 3.8$ V to 5.5 V		5	15	mV	
Ripple rejection	$f = 120$ Hz, $V_{ripple} = 1$ V _{PP}		-62		dB	
Output voltage regulation	$I_O = 20$ mA to 500 mA		5	30	mV	
Output noise voltage	$f = 10$ Hz to 100 kHz		500		μV	
Dropout voltage	$I_O = 250$ mA			400	mV	
	$I_O = 500$ mA			500		
Bias current	$I_O = 0$		2	5	mA	
	$I_O = 500$ mA		19	49		

[‡] Pulse-testing techniques are used to maintain the virtual junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.1-μF capacitor across the input and a 22-μF tantalum capacitor with equivalent series resistance of 1.5 Ω on the output.



TLV2217-33

LOW-DROPOUT 3.3-V FIXED-VOLTAGE REGULATORS

SLVS067G – MARCH 1992 – REVISED JULY 1999

electrical characteristics at $V_I = 4.5\text{ V}$, $I_O = 500\text{ mA}$, $T_J = 25^\circ\text{C}$ (unless otherwise noted)

PARAMETER	TEST CONDITION [†]	TLV2217-33Y			UNIT
		MIN	TYP	MAX	
Output voltage	$I_O = 20\text{ mA to }500\text{ mA}$, $V_I = 3.8\text{ V to }5.5\text{ V}$	3.267	3.30	3.333	V
Input voltage regulation	$V_I = 3.8\text{ V to }5.5\text{ V}$		5	15	mV
Ripple rejection	$f = 120\text{ Hz}$, $V_{\text{ripple}} = 1\text{ V}_{\text{PP}}$		-62		dB
Output voltage regulation	$I_O = 20\text{ mA to }500\text{ mA}$		5	30	mV
Output noise voltage	$f = 10\text{ Hz to }100\text{ kHz}$		500		μV
Dropout voltage	$I_O = 250\text{ mA}$			400	mV
	$I_O = 500\text{ mA}$			500	
Bias current	$I_O = 0$		2	5	mA
	$I_O = 500\text{ mA}$		19	49	

[†] Pulse-testing techniques are used to maintain the virtual junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.1- μF capacitor across the input and a 22- μF tantalum capacitor with equivalent series resistance of 1.5 Ω on the output.

TLV2217-33 LOW-DROPOUT 3.3-V FIXED-VOLTAGE REGULATORS

SLVS067G – MARCH 1992 – REVISED JULY 1999

COMPENSATION-CAPACITOR SELECTION INFORMATION

The TLV2217-33 is a low-dropout regulator. This means that the capacitance loading is important to the performance of the regulator because it is a vital part of the control loop. The capacitor value and the equivalent series resistance (ESR) both affect the control loop and must be defined for the load range and the temperature range. Figures 1 and 2 can be used to establish the capacitance value and ESR range for best regulator performance.





Figure 2




Figure 1

APPLICATION INFORMATION

application schematic




Figure 3

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.