

Home > Search Engine > Catalog: CSTCE12M5G55A-R0

Resonators > CERALOCK (MHz) > Part Number

How to check EU RoHS Compliance of Our Products is here.

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specifications

Global Part Number	CSTCE12M5G55A-R0
Previous Part Number	
Nominal Frequency	12.500MHz
Initial Tolerance	±0.5%
Resonant Frequency	30ohm
Temp. Stability	±0.2%
Operating Temperature Range	-40 to +125°C
Frequency Aging	±0.1%
Wash	Available
Ultrasonic Wash	Available
Built-in Load Capacitance	33pF
Use	For automotive electronics

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	3000
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	
Ammo Pack	
320Reel	
Magazine	

Details

- Part Numbering
- Appearance
- Dimensions
- Features and Applications
- Temperature_Characteristics
- Basic Oscillation Circuit
- <u>III</u> Standard_Land_Pattern
- Motice_

(Storage_and_Operating_Conditions)

- Notice_(Rating)
- Notice (Soldering and Mounting)
- Notice_(Handling)
- Packaging
- Minimum_Quantity

Please approve our product specifications or to transact the approval sheet for product specifications before ordering.

Please read rating and !Cautions first.

Product specifications in this catalog are as of March 2010

Please make sure to read the Murata's Product Policy, too.

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP .

| Site Map | History | Terms of use | Privacy Policy |

All Rights Reserved, Copyright© Murata Manufacturing Co., Ltd.