



Ty-Rap®

T&B Catalog Number: WT3D
UPC Number: 78621083503
Description: Cable Tie Manual Installation Hand Tool-Deltec

Status: Active

Features

Tensioning tool with manual cutting. Designed for both self-locking and lashing ties.

General

For Cable Ties 50 to 120 lbs.
 Tooling Functionality Fastening
 For Tie Width (inches) .184 - .500

Dimension Information

Length (inches) 7.01
 Width (inches) 4.41

Specifications

Tension Setting Basic
 Cutting Mechanism Manual

Tooling

Tool Service Site Available on Website
 On-Line Warranty Registration Available on Website
 Exploded View/Parts List Available on Website

Packaging

T&B Order Multiple 1
 T&B Inner Pack 1
 Package in Units 10
 T&B Sold in UOM Each
 T&B Weight Per UOM 67 lbs. per 100

Application Support

T&B Instruction Sheets ta00646-tb2

Certifications

RoHS Compliance No

Ty-Rap® Cable Installation Tools

Lightweight. Economical. Durable.
Perfect for spot-tying!

Ty-Rap® Cable Tie Installation Tool — Light Duty

- Installs Ty-Rap cable ties up to .301" wide by .080" thick
- Designed for use by both left- and right-handed operators
- Lightweight, high-impact polymer and steel components

They cinch up the tie with a squeeze action, and cut away the excess tail when twisted 180°. A specially designed pawl cuts away the tail if the tension limit is exceeded, thereby preventing the cable tie from being over-tightened.



STD. PKG. CAT. NO.	DESCRIPTION	TIE BODY WIDTH IN./MM.	STD. PKG. QTY.
WT1-TB	Cable Tie Installation Tool, 18–50 lbs. (80–222.4 N)	.09–.18/2.39–4.67	1
WT2-TB	Cable Tie Installation Tool, 50–120 lbs. (222.4–533.8 N)	.18–.30/4.67–7.65	1

Cuts tail off — flush.

Ty-Rap® Cable Ties Installation Tool — Metallic

- Installs Ty-Rap® cable ties
- Rugged metallic construction
- Pistol-grip installation tool
- Easy tension adjustment
- Tensions and cuts tie tail off flush



STD. PKG. CAT. NO.	DESCRIPTION	TIE BODY WIDTH IN./MM.	STD. PKG. QTY.
WT193A	Cable Tie Installation Tool, 18–50 lbs. (80–222.4 N)	.09–.18/2.39–4.67	1

Get the job
done right!

Ty-Rap® Heavy-Duty Installation Tool — Stainless Steel

- Installs Ty-Rap® stainless steel cable ties
- Rugged stainless steel construction
- Pistol-type installation tool
- Adjustable tension settings



STD. PKG. CAT. NO.	DESCRIPTION	TIE BODY WIDTH IN./MM.	STD. PKG. QTY.
DA5250	Stainless Steel Installation Tool	Up to .31/7.87	1

Easy tension
adjustment!

Ty-Rap Heavy-Duty Installation Tool — Mil Spec Approved

- Installs Ty-Rap® cable ties
- Rugged metallic construction
- Pistol-grip installation tool
- Tensions and cut cable tie tail off flush



STD. PKG. CAT. NO.	DESCRIPTION	TIE BODY WIDTH IN./MM.	STD. PKG. QTY.
WT199	Installation Tool, 18–50 lbs. (80–222.4 N)	.09–.18/2.39–4.67	1
WT197	Installation Tool, 50–120 lbs. (222.4–533.8 N)	.18–.30/4.67–7.65	1

* Mil Spec Approved (WT199 — NSN3387-1, WT197 — MS90387-2)

Makes tie installation easy!

Ty-Rap® Installation Tool — Delfec & Stainless Steel

WT3D

- Installs both self-locking Ty-Rap® cable ties and lashing ties

WT3S

- Installs stainless steel ties



STD. PKG. CAT. NO.	DESCRIPTION	TIE BODY WIDTH IN./MM.	STD. PKG. QTY.
WT3D	Delfec Installation Tool	.18–.50/4.67–12.70	1
WT3S	Stainless Steel Installation Tool	up to .50/12.70	1

NOTE: Tensions only