



### TRI-BAND: 880-960, 1710-1880 AND 1920-2170 MHz CEILING MOUNT OMNI-DIRECTIONAL PANEL ANTENNA

The Laird Technologies SL80173WP is a tri-band, linearly polarized 3 dBi omnidirectional panel antenna. Specifically shaped for optimal performance from a ceiling mount location, the pattern is optimized for indoor coverage requirements at 880-960, 1710-1880, and 1920-2170 MHz for the GSM, DCS, and UMTS frequency bands. The antenna is also uniform and symmetrical, allowing systems integrators the ability to precisely determine cell size—a major benefit in determining cell overlap and density for in-building systems.

With a small footprint and slim silhouette, the antenna is ideal for any office or retail space where a premium is placed on complementary, unobtrusive aesthetics. Standard with three integrated plenum-rated coax pigtails and N female connectors, the SL80173WP also accommodates alternative coax and connector implementations.


#### FEATURES

- Wide-band frequency coverage for GSM, DCS, and UMTS
- Tri-port design eliminates costly diplexers
- Neutral color and diminutive profile


#### MARKETS

- Corporate offices
- Shopping malls
- Transportation centers


PARAMETER	SPECIFICATION
Frequency Range (MHz)	880-960, 1710-1880 1920-2170
Gain (dBi)	3 (nominal)
E-Plane Beamwidth	70° / 60° / 60°
H-Plane Beamwidth	Omnidirectional
Polarization	Linear
Weight (Ant. Only) lb. (kg)	0.75 (0.34)
VSWR	2.0:1
Mount Style	Ceiling mount
Dimensions (in)	6" x 6" x 1.25"
Pigtail	12"
Enclosure	ABS
Power (Watts)	2
RF Connectors	N (f)




920 MHz



1795 MHz



2045 MHz



Americas: +1.847.839.6925  
IAS-AmericasSales@lairdtech.com

Europe: +44.1628.858941  
IAS-EUSales@lairdtech.com

Asia:  
IAS-AsiaSales@lairdtech.com

Middle East & Africa: +44.1628.858941  
IAS-MEASales@lairdtech.com  
[www.lairdtech.com](http://www.lairdtech.com)

#### ANT-DS-SL80173WP 0317

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request. All Laird Technologies' products are sold pursuant to the Laird Technologies' terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.