


# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

- Rail-to-Rail Output Swing
- Gain Bandwidth Product . . . 6.4 MHz
- $\pm 80$  mA Output Drive Capability
- Supply Current . . . 500  $\mu$ A/channel
- Input Offset Voltage . . . 100  $\mu$ V
- Input Noise Voltage . . . 11 nV/ $\sqrt{\text{Hz}}$
- Slew Rate . . . 1.6 V/ $\mu$ s
- Micropower Shutdown Mode (TLV2460/3/5) . . . 0.3  $\mu$ A/Channel
- Universal Operational Amplifier EVM
- Available in Q-Temp Automotive HighRel Automotive Applications Configuration Control/Print Support Qualification to Automotive Standards



### description

The TLV246x is a family of low-power rail-to-rail input/output operational amplifiers specifically designed for portable applications. The input common-mode voltage range extends beyond the supply rails for maximum dynamic range in low-voltage systems. The amplifier output has rail-to-rail performance with high-output-drive capability, solving one of the limitations of older rail-to-rail input/output operational amplifiers. This rail-to-rail dynamic range and high output drive make the TLV246x ideal for buffering analog-to-digital converters.

The operational amplifier has 6.4 MHz of bandwidth and 1.6 V/ $\mu$ s of slew rate with only 500  $\mu$ A of supply current, providing good ac performance with low power consumption. Three members of the family offer a shutdown terminal, which places the amplifier in an ultralow supply current mode ( $I_{DD} = 0.3$   $\mu$ A/ch). While in shutdown, the operational-amplifier output is placed in a high-impedance state. DC applications are also well served with an input noise voltage of 11 nV/ $\sqrt{\text{Hz}}$  and input offset voltage of 100  $\mu$ V.

This family is available in the low-profile SOT23, MSOP, and TSSOP packages. The TLV2460 is the first rail-to-rail input/output operational amplifier with shutdown available in the 6-pin SOT23, making it perfect for high-density circuits. The family is specified over an expanded temperature range ( $T_A = -40^\circ\text{C}$  to  $125^\circ\text{C}$ ) for use in industrial control and automotive systems, and over the military temperature range ( $T_A = -55^\circ\text{C}$  to  $125^\circ\text{C}$ ) for use in military systems.

### SELECTION GUIDE

| DEVICE     | V <sub>DD</sub><br>[V] | V <sub>IO</sub><br>[ $\mu$ V] | I <sub>DD</sub> /ch<br>[ $\mu$ A] | I <sub>B</sub><br>[pA] | GBW<br>[MHz] | SLEW RATE<br>[V/ $\mu$ s] | V <sub>n</sub> , 1 kHz<br>[nV/ $\sqrt{\text{Hz}}$ ] | I <sub>O</sub><br>[mA] | SHUTDOWN | RAIL-RAIL |
|------------|------------------------|-------------------------------|-----------------------------------|------------------------|--------------|---------------------------|-----------------------------------------------------|------------------------|----------|-----------|
| TLV246x(A) | 2.7–6                  | 150                           | 550                               | 1300                   | 6.4          | 1.6                       | 11                                                  | 25                     | Y        | I/O       |
| TLV277x(A) | 2.5–5.5                | 360                           | 1000                              | 2                      | 5.1          | 10.5                      | 17                                                  | 6                      | Y        | O         |
| TLV247x(A) | 2.7–6                  | 250                           | 600                               | 2.5                    | 2.8          | 1.5                       | 15                                                  | 20                     | Y        | I/O       |
| TLV245x(A) | 2.7–6                  | 20                            | 23                                | 500                    | 0.22         | 0.11                      | 52                                                  | 10                     | Y        | I/O       |
| TLV225x(A) | 2.7–8                  | 200                           | 35                                | 1                      | 0.2          | 0.12                      | 19                                                  | 3                      | —        | —         |
| TLV226x(A) | 2.7–8                  | 300                           | 200                               | 1                      | 0.71         | 0.55                      | 12                                                  | 3                      | —        | —         |



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

 **TEXAS  
INSTRUMENTS**  
WWW.TI.COM

Copyright © 1998–2004, Texas Instruments Incorporated  
On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

## OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

TLV2460C//AI and TLV2461C//AI AVAILABLE OPTIONS

| T <sub>A</sub> | V <sub>IOmax</sub><br>AT 25°C | PACKAGED DEVICES         |                              |              |                          |
|----------------|-------------------------------|--------------------------|------------------------------|--------------|--------------------------|
|                |                               | SMALL OUTLINE<br>(D)     | SOT-23 <sup>†</sup><br>(DBV) | SYMBOL       | PLASTIC DIP<br>(P)       |
| 0°C to 70°C    | 2000 µV                       | TLV2460CD<br>TLV2461CD   | TLV2460CDBV<br>TLV2461CDBV   | VAOC<br>VAPC | TLV2460CP<br>TLV2461CP   |
| –40°C to 125°C | 2000 µV                       | TLV2460ID<br>TLV2461ID   | TLV2460IDBV<br>TLV2461IDBV   | VAOI<br>VAPI | TLV2460IP<br>TLV2461IP   |
|                | 1500 µV                       | TLV2460AID<br>TLV2461AID | —<br>—                       | —<br>—       | TLV2460AIP<br>TLV2461AIP |

<sup>†</sup> This package is available taped and reeled. To order this packaging option, add an R suffix to the part number (e.g., TLV2460CDR).

<sup>‡</sup> Chip forms are tested at T<sub>A</sub> = 25°C only.

TLV2460M//AM/Q/AQ and TLV2461M//AM/Q/AQ AVAILABLE OPTIONS

| T <sub>A</sub> | V <sub>IOmax</sub><br>AT 25°C | PACKAGED DEVICES                     |                                       |                            |                            |                            |
|----------------|-------------------------------|--------------------------------------|---------------------------------------|----------------------------|----------------------------|----------------------------|
|                |                               | SMALL<br>OUTLINE <sup>†</sup><br>(D) | SMALL<br>OUTLINE <sup>†</sup><br>(PW) | CERAMIC DIP<br>(JG)        | CERAMIC<br>FLATPACK<br>(U) | CHIP CARRIER<br>(FK)       |
| –40°C to 125°C | 2000 µV                       | TLV2460QD<br>TLV2461QD               | TLV2460QPW<br>TLV2461QPW              | —<br>—                     | —<br>—                     | —<br>—                     |
|                | 1500 µV                       | TLV2460AQD<br>TLV2461AQD             | TLV2460AQPW<br>TLV2461AQPW            | —<br>—                     | —<br>—                     | —<br>—                     |
| –55°C to 125°C | 2000 µV                       | —<br>—                               | —<br>—                                | TLV2460MJG<br>TLV2461MJG   | TLV2460MU<br>TLV2461MU     | TLV2460MFK<br>TLV2461MFK   |
|                | 1500 µV                       | —<br>—                               | —<br>—                                | TLV2460AMJG<br>TLV2461AMJG | TLV2460AMU<br>TLV2461AMU   | TLV2460AMFK<br>TLV2461AMFK |

<sup>†</sup> This package is available taped and reeled. To order this packaging option, add an R suffix to the part number (e.g., TLV2460QDR).

TLV2462C//AI and TLV2463C//AI AVAILABLE OPTIONS

| T <sub>A</sub>    | V <sub>IOmax</sub><br>AT 25°C | PACKAGED DEVICES                     |                  |         |                            |              |                    |                    |
|-------------------|-------------------------------|--------------------------------------|------------------|---------|----------------------------|--------------|--------------------|--------------------|
|                   |                               | SMALL<br>OUTLINE <sup>†</sup><br>(D) | MSOP<br>(DGK)    | SYMBOL  | MSOP <sup>†</sup><br>(DGS) | SYMBOL       | PLASTIC DIP<br>(N) | PLASTIC DIP<br>(P) |
| 0°C to 70°C       | 2000 µV                       | TLV2462CD<br>TLV2463CD               | TLV2462CDGK<br>— | xxTIAAI | —<br>TLV2463CDGS           | —<br>xxTIAAK | —<br>TLV2463CN     | TLV2462CP<br>—     |
| –40°C to<br>125°C | 2000 µV                       | TLV2462ID<br>TLV2463ID               | TLV2462IDGK<br>— | xxTIAAJ | —<br>TLV2463IDGS           | —<br>xxTIAAL | —<br>TLV2463IN     | TLV2462IP<br>—     |
|                   | 1500 µV                       | TLV2462AID<br>TLV2463AID             | —<br>—           | —<br>—  | —<br>—                     | —<br>—       | —<br>TLV2463AIN    | TLV2462AIP<br>—    |

<sup>†</sup> This package is available taped and reeled. To order this packaging option, add an R suffix to the part number (e.g., TLV2462CDR).

<sup>‡</sup> Chip forms are tested at T<sub>A</sub> = 25°C only.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TLV2462M/AM/Q/AQ and TLV2463M/AM/Q/AQ AVAILABLE OPTIONS

| T <sub>A</sub> | V <sub>IO</sub> max<br>AT 25°C | PACKAGED DEVICES         |                            |                     |                       |                            |                            |
|----------------|--------------------------------|--------------------------|----------------------------|---------------------|-----------------------|----------------------------|----------------------------|
|                |                                | SMALL<br>OUTLINE†<br>(D) | SMALL<br>OUTLINE†<br>(PW)  | CERAMIC DIP<br>(JG) | CERAMIC<br>DIP<br>(J) | CERAMIC<br>FLATPACK<br>(U) | CHIP CAR-<br>RIER<br>(FK)  |
| –40°C to 125°C | 2000 µV                        | TLV2462QD<br>TLV2463QD   | TLV2462QPW<br>TLV2463QPW   | —<br>—              | —<br>—                | —<br>—                     | —<br>—                     |
|                | 1500 µV                        | TLV2462AQD<br>TLV2463AQD | TLV2462AQPW<br>TLV2463AQPW | —<br>—              | —<br>—                | —<br>—                     | —<br>—                     |
| –55°C to 125°C | 2000 µV                        | —<br>—                   | —<br>—                     | TLV2462MJG<br>—     | —<br>TLV2463MJ        | TLV2462MU                  | TLV2462MFK<br>TLV2463MFK   |
|                | 1500 µV                        | —<br>—                   | —<br>—                     | TLV2462AMJG<br>—    | —<br>TLV2463AMJ       | TLV2462AMU                 | TLV2462AMFK<br>TLV2463AMFK |

† This package is available taped and reeled. To order this packaging option, add an R suffix to the part number (e.g., TLV2462QDR).

### TLV2464C//AI and TLV2465C//AI AVAILABLE OPTIONS

| T <sub>A</sub> | V <sub>IO</sub> max<br>AT 25°C | PACKAGED DEVICES         |                          |                            |
|----------------|--------------------------------|--------------------------|--------------------------|----------------------------|
|                |                                | SMALL OUTLINE<br>(D)     | PLASTIC DIP<br>(N)       | TSSOP<br>(PW)              |
| 0°C to 70°C    | 2000 µV                        | TLV2464CD<br>TLV2465CD   | TLV2464CN<br>TLV2465CN   | TLV2464CPW<br>TLV2465CPW   |
| –40°C to 125°C | 2000 µV                        | TLV2464ID<br>TLV2465ID   | TLV2464IN<br>TLV2465IN   | TLV2464IPW<br>TLV2465IPW   |
|                | 1500 µV                        | TLV2464AID<br>TLV2465AID | TLV2464AIN<br>TLV2465AIN | TLV2464AIPW<br>TLV2465AIPW |

† This package is available taped and reeled. To order this packaging option, add an R suffix to the part number (e.g., TLV2464CDR).

‡ Chip forms are tested at T<sub>A</sub> = 25°C only.

### TLV2464M/AM/Q/AQ and TLV2465M/AM/Q/AQ AVAILABLE OPTIONS

| T <sub>A</sub> | V <sub>IO</sub> max<br>AT 25°C | PACKAGED DEVICES         |                            |                          |                            |
|----------------|--------------------------------|--------------------------|----------------------------|--------------------------|----------------------------|
|                |                                | SMALL<br>OUTLINE†<br>(D) | SMALL<br>OUTLINE†<br>(PW)  | CERAMIC DIP<br>(J)       | CHIP CARRIER<br>(FK)       |
| –40°C to 125°C | 2000 µV                        | TLV2464QD<br>TLV2465QD   | TLV2464QPW<br>TLV2465QPW   | —<br>—                   | —<br>—                     |
|                | 1500 µV                        | TLV2464AQD<br>TLV2465AQD | TLV2464AQPW<br>TLV2465AQPW | —<br>—                   | —<br>—                     |
| –55°C to 125°C | 2000 µV                        | —<br>—                   | —<br>—                     | TLV2464MJ<br>TLV2465MJ   | TLV2464MFK<br>TLV2465MFK   |
|                | 1500 µV                        | —<br>—                   | —<br>—                     | TLV2464AMJ<br>TLV2465AMJ | TLV2464AMFK<br>TLV2465AMFK |

† This package is available taped and reeled. To order this packaging option, add an R suffix to the part number (e.g., TLV2464QDR).










# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

### OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004


#### TLV246x PACKAGE PINOUTS(1)



NC – No internal connection

(1) SOT-23 may or may not be indicated

#### TYPICAL PIN 1 INDICATORS












# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

## OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TLV246x PACKAGE PINOUTS (continued)(1)



NC – No internal connection

(1) SOT-23 may or may not be indicated

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

### OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

#### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

|                                                              |                              |
|--------------------------------------------------------------|------------------------------|
| Supply voltage, $V_{DD}$ (see Note 1)                        | 6 V                          |
| Differential input voltage, $V_{ID}$                         | – 0.2 V to $V_{DD} + 0.2$ V  |
| Input current, $I_I$ (any input)                             | ± 200 mA                     |
| Output current, $I_O$                                        | ± 175 mA                     |
| Total input current, $I_I$ (into $V_{DD+}$ )                 | 175 mA                       |
| Total output current, $I_O$ (out of GND)                     | 175 mA                       |
| Continuous total power dissipation                           | See Dissipation Rating Table |
| Operating free-air temperature range, $T_A$ : C suffix       | 0°C to 70°C                  |
| I and Q suffix                                               | –40°C to 125°C               |
| M suffix                                                     | –55°C to 125°C               |
| Maximum junction temperature, $T_J$                          | 150°C                        |
| Storage temperature range, $T_{stg}$                         | –65°C to 150°C               |
| Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds | 260°C                        |

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltage values, except differential voltages, are with respect to GND.

DISSIPATION RATING TABLE FOR C and I SUFFIX

| PACKAGE    | $\theta_{JC}$<br>(°C/W) | $\theta_{JA}$<br>(°C/W) | $T_A \leq 25^\circ\text{C}$<br>POWER RATING | $T_A < 125^\circ\text{C}$<br>POWER RATING |
|------------|-------------------------|-------------------------|---------------------------------------------|-------------------------------------------|
| D (8)      | 38.3                    | 176                     | 710 mW                                      | 142 mW                                    |
| D (14)     | 26.9                    | 122.6                   | 1022 mW                                     | 204.4 mW                                  |
| D (16)     | 25.7                    | 114.7                   | 1090 mW                                     | 218 mW                                    |
| DBV (5)    | 55                      | 324.1                   | 385 mW                                      | 77.1 mW                                   |
| DBV (6)    | 55                      | 294.3                   | 425 mW                                      | 84.9 mW                                   |
| DGK        | 54.2                    | 259.9                   | 481 mW                                      | 96.2 mW                                   |
| DGS        | 54.1                    | 257.7                   | 485 mW                                      | 97 mW                                     |
| N (14, 16) | 32                      | 78                      | 1600 mW                                     | 320.5 mW                                  |
| P (8)      | 41                      | 104                     | 1200 mW                                     | 240.4 mW                                  |
| PW (14)    | 29.3                    | 173.6                   | 720 mW                                      | 144 mW                                    |
| PW (16)    | 28.7                    | 161.4                   | 774 mW                                      | 154.9 mW                                  |

NOTE: Thermal resistances are not production tested and are for informational purposes only.

DISSIPATION RATING TABLE FOR Q and M SUFFIX

| PACKAGE | $T_A \leq 25^\circ\text{C}$<br>POWER RATING | DERATING FACTOR<br>ABOVE $T_A = 25^\circ\text{C}^\ddagger$ | $T_A = 70^\circ\text{C}$<br>POWER RATING | $T_A = 85^\circ\text{C}$<br>POWER RATING | $T_A = 125^\circ\text{C}$<br>POWER RATING |
|---------|---------------------------------------------|------------------------------------------------------------|------------------------------------------|------------------------------------------|-------------------------------------------|
| FK      | 1375 mW                                     | 11.0 mW/°C                                                 | 880 mW                                   | 715 mW                                   | 275 mW                                    |
| JG      | 1050 mW                                     | 8.4 mW/°C                                                  | 672 mW                                   | 546 mW                                   | 210 mW                                    |
| U       | 675 mW                                      | 5.4 mW/°C                                                  | 432 mW                                   | 350 mW                                   | 135 mW                                    |

<sup>‡</sup> This is the inverse of the traditional junction-to-ambient thermal resistance ( $R\theta_{JA}$ ). Thermal resistances are not production tested and are for informational purposes only.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### recommended operating conditions

|                                            |                       | MIN        | MAX      | UNIT               |
|--------------------------------------------|-----------------------|------------|----------|--------------------|
| Supply voltage, $V_{DD}$                   | Single supply         | 2.7        | 6        | V                  |
|                                            | Split supply          | $\pm 1.35$ | $\pm 3$  |                    |
| Common-mode input voltage range, $V_{ICR}$ |                       | 0          | $V_{DD}$ | V                  |
| Operating free-air temperature, $T_A$      | C-suffix              | 0          | 70       | $^{\circ}\text{C}$ |
|                                            | I-suffix and Q-suffix | -40        | 125      |                    |
|                                            | M-suffix              | -55        | 125      |                    |
| Shutdown on/off voltage level <sup>‡</sup> | $V_{IH}$              | 2          |          | V                  |
|                                            | $V_{IL}$              |            | 0.7      |                    |

<sup>‡</sup> Relative to voltage on the GND terminal of the device.

### electrical characteristics at specified free-air temperature, $V_{DD} = 3\text{ V}$ (unless otherwise noted)

| PARAMETER                                                      | TEST CONDITIONS                                                                                      | $T_A^{\dagger}$       | MIN | TYP      | MAX  | UNIT                           |
|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------|-----------------------|-----|----------|------|--------------------------------|
| $V_{IO}$ Input offset voltage                                  | $V_{DD} = 3\text{ V}$ ,<br>$V_{IC} = 1.5\text{ V}$ ,<br>$V_O = 1.5\text{ V}$ ,<br>$R_S = 50\ \Omega$ | 25 $^{\circ}\text{C}$ |     | 500      | 2000 | $\mu\text{V}$                  |
|                                                                |                                                                                                      | Full range            |     |          | 2200 |                                |
|                                                                |                                                                                                      | 25 $^{\circ}\text{C}$ |     | 500      | 1500 |                                |
|                                                                |                                                                                                      | Full range            |     |          | 1700 |                                |
| $\alpha_{VIO}$ Temperature coefficient of input offset voltage |                                                                                                      |                       |     | 2        |      | $\mu\text{V}/^{\circ}\text{C}$ |
| $I_{IO}$ Input offset current                                  | $V_{DD} = 3\text{ V}$ ,<br>$V_{IC} = 1.5\text{ V}$ ,<br>$V_O = 1.5\text{ V}$ ,<br>$R_S = 50\ \Omega$ | 25 $^{\circ}\text{C}$ |     | 2.8      | 7    | nA                             |
|                                                                |                                                                                                      | Full range            |     |          | 20   |                                |
| $I_{IB}$ Input bias current                                    | $V_{DD} = 3\text{ V}$ ,<br>$V_{IC} = 1.5\text{ V}$ ,<br>$V_O = 1.5\text{ V}$ ,<br>$R_S = 50\ \Omega$ | 25 $^{\circ}\text{C}$ |     | 4.4      | 14   | nA                             |
|                                                                |                                                                                                      | Full range            |     |          | 25   |                                |
|                                                                |                                                                                                      | Full range            |     |          | 75   |                                |
|                                                                |                                                                                                      | Full range            |     |          | 75   |                                |
| $V_{OH}$ High-level output voltage                             | $I_{OH} = -2.5\text{ mA}$                                                                            | 25 $^{\circ}\text{C}$ |     | 2.9      |      | V                              |
|                                                                |                                                                                                      | Full range            | 2.8 |          |      |                                |
|                                                                | $I_{OH} = -10\text{ mA}$                                                                             | 25 $^{\circ}\text{C}$ |     | 2.7      |      |                                |
|                                                                |                                                                                                      | Full range            | 2.5 |          |      |                                |
| $V_{OL}$ Low-level output voltage                              | $V_{IC} = 1.5\text{ V}$ , $I_{OL} = 2.5\text{ mA}$                                                   | 25 $^{\circ}\text{C}$ |     | 0.1      |      | V                              |
|                                                                |                                                                                                      | Full range            |     |          | 0.2  |                                |
|                                                                | $V_{IC} = 1.5\text{ V}$ , $I_{OL} = 10\text{ mA}$                                                    | 25 $^{\circ}\text{C}$ |     | 0.3      |      |                                |
|                                                                |                                                                                                      | Full range            |     |          | 0.5  |                                |
| $I_{OS}$ Short-circuit output current                          | Sourcing                                                                                             | 25 $^{\circ}\text{C}$ |     | 50       |      | mA                             |
|                                                                |                                                                                                      | Full range            | 20  |          |      |                                |
|                                                                | Sinking                                                                                              | 25 $^{\circ}\text{C}$ |     | 40       |      |                                |
|                                                                |                                                                                                      | Full range            | 20  |          |      |                                |
| $I_O$ Output current                                           | Measured 1 V from rail                                                                               | 25 $^{\circ}\text{C}$ |     | $\pm 40$ |      | mA                             |
| $A_{VD}$ Large-signal differential voltage amplification       | $R_L = 10\text{ k}\Omega$ , $V_{O(PP)} = 1\text{ V}$                                                 | 25 $^{\circ}\text{C}$ | 90  | 105      |      | dB                             |
|                                                                |                                                                                                      | Full range            | 89  |          |      |                                |
| $r_{i(d)}$ Differential input resistance                       |                                                                                                      | 25 $^{\circ}\text{C}$ |     | $10^9$   |      | $\Omega$                       |

<sup>†</sup> Full range is 0 $^{\circ}\text{C}$  to 70 $^{\circ}\text{C}$  for the C suffix, -40 $^{\circ}\text{C}$  to 125 $^{\circ}\text{C}$  for the I and Q suffixes, and -55 $^{\circ}\text{C}$  to 125 $^{\circ}\text{C}$  for the M suffix.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

electrical characteristics at specified free-air temperature,  $V_{DD} = 3\text{ V}$  (unless otherwise noted)  
(continued)

| PARAMETER      |                                                                       | TEST CONDITIONS                                               | $T_A^\dagger$                               | MIN        | TYP | MAX   | UNIT          |
|----------------|-----------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------|------------|-----|-------|---------------|
| $C_i(c)$       | Common-mode input capacitance                                         | $f = 10\text{ kHz}$                                           | $25^\circ\text{C}$                          |            | 7   |       | pF            |
| $z_o$          | Closed-loop output impedance                                          | $f = 100\text{ kHz}$ , $A_V = 10$                             | $25^\circ\text{C}$                          |            | 33  |       | $\Omega$      |
| CMRR           | Common-mode rejection ratio                                           | $V_{ICR} = 0\text{ to }3\text{ V}$ ,<br>$R_S = 50\ \Omega$    | $25^\circ\text{C}$                          | 66         | 80  |       | dB            |
|                |                                                                       |                                                               | TLV246xC                                    | Full range | 64  |       |               |
|                |                                                                       |                                                               | TLV246xI/Q/M                                | Full range | 60  |       |               |
| $k_{SVR}$      | Supply voltage rejection ratio<br>( $\Delta V_{DD} / \Delta V_{IO}$ ) | $V_{DD} = 2.7\text{ V to }6\text{ V}$ ,<br>No load            | $V_{IC} = V_{DD}/2$ ,<br>$25^\circ\text{C}$ | 80         | 85  |       | dB            |
|                |                                                                       |                                                               | Full range                                  | 75         |     |       |               |
|                |                                                                       | $V_{DD} = 3\text{ V to }5\text{ V}$ ,<br>No load              | $V_{IC} = V_{DD}/2$ ,<br>$25^\circ\text{C}$ | 85         | 95  |       |               |
|                |                                                                       |                                                               | Full range                                  | 80         |     |       |               |
| $I_{DD}$       | Supply current (per channels)                                         | $V_O = 1.5\text{ V}$ ,<br>No load                             | $25^\circ\text{C}$                          |            | 0.5 | 0.575 | mA            |
|                |                                                                       |                                                               | Full range                                  |            |     | 0.9   |               |
| $I_{DD}(SHDN)$ | Supply current in shutdown<br>(TLV2460, TLV2463, TLV2465)             | $\overline{SHDN} < 0.7\text{ V}$ ,<br>Per channel in shutdown | $25^\circ\text{C}$                          |            | 0.3 |       | $\mu\text{A}$ |
|                |                                                                       |                                                               | Full range                                  |            |     | 2.5   |               |

$^\dagger$  Full range is  $0^\circ\text{C}$  to  $70^\circ\text{C}$  for the C suffix,  $-40^\circ\text{C}$  to  $125^\circ\text{C}$  for the I and Q suffixes, and  $-55^\circ\text{C}$  to  $125^\circ\text{C}$  for the M suffix.

operating characteristics at specified free-air temperature,  $V_{DD} = 3\text{ V}$  (unless otherwise noted)

| PARAMETER              |                                      | TEST CONDITIONS                                                                                        |                                 | T <sub>A</sub> <sup>†</sup> | MIN    | TYP | MAX | UNIT   |
|------------------------|--------------------------------------|--------------------------------------------------------------------------------------------------------|---------------------------------|-----------------------------|--------|-----|-----|--------|
| SR                     | Slew rate at unity gain              | V <sub>O(PP)</sub> = 0.8 V,<br>R <sub>L</sub> = 10 kΩ                                                  |                                 | 25°C                        | 0.9    | 1.6 |     | V/μs   |
|                        |                                      |                                                                                                        |                                 | Full range                  | 0.8    |     |     |        |
| V <sub>n</sub>         | Equivalent input noise voltage       | f = 100 Hz                                                                                             |                                 | 25°C                        | 16     |     |     | nV/√Hz |
|                        |                                      | f = 1 kHz                                                                                              |                                 | 25°C                        | 11     |     |     |        |
| I <sub>n</sub>         | Equivalent input noise current       | f = 1 kHz                                                                                              |                                 | 25°C                        | 0.13   |     |     | pA/√Hz |
| THD + N                | Total harmonic distortion plus noise | V <sub>O(PP)</sub> = 2 V,<br>R <sub>L</sub> = 10 kΩ, f = 1 kHz                                         | A <sub>V</sub> = 1              | 25°C                        | 0.006% |     |     |        |
|                        |                                      |                                                                                                        | A <sub>V</sub> = 10             |                             | 0.02%  |     |     |        |
|                        |                                      |                                                                                                        | A <sub>V</sub> = 100            |                             | 0.08%  |     |     |        |
| t <sub>(on)</sub>      | Amplifier turnon time                | A <sub>V</sub> = 1, R <sub>L</sub> = 10 kΩ                                                             | Both channels                   | 25°C                        | 7.6    |     |     | μs     |
|                        |                                      |                                                                                                        | Channel 1 only,<br>Channel 2 on |                             | 7.65   |     |     |        |
| t <sub>(off)</sub>     | Amplifier turnoff time               | A <sub>V</sub> = 1, R <sub>L</sub> = 10 kΩ                                                             | Both channels                   | 25°C                        | 333    |     |     | ns     |
|                        |                                      |                                                                                                        | Channel 1 only,<br>Channel 2 on |                             | 328    |     |     |        |
|                        |                                      |                                                                                                        | Channel 2 only,<br>Channel 1 on |                             | 329    |     |     |        |
| Gain-bandwidth product |                                      | f = 10 kHz, C <sub>L</sub> = 160 pF                                                                    | R <sub>L</sub> = 10 kΩ,         | 25°C                        | 5.2    |     |     | MHz    |
| t <sub>s</sub>         | Settling time                        | V <sub>(STEP)PP</sub> = 2 V,<br>A <sub>V</sub> = -1, C <sub>L</sub> = 10 pF,<br>R <sub>L</sub> = 10 kΩ | 0.1%                            | 25°C                        | 1.47   |     |     | μs     |
|                        |                                      |                                                                                                        | 0.01%                           |                             | 1.78   |     |     |        |
|                        |                                      | V <sub>(STEP)PP</sub> = 2 V,<br>A <sub>V</sub> = -1, C <sub>L</sub> = 56 pF,<br>R <sub>L</sub> = 10 kΩ | 0.1%                            |                             | 1.77   |     |     |        |
|                        |                                      |                                                                                                        | 0.01%                           |                             | 1.98   |     |     |        |
| φ <sub>m</sub>         | Phase margin at unity gain           | R <sub>L</sub> = 10 kΩ, C <sub>L</sub> = 160 pF                                                        |                                 | 25°C                        | 44°    |     |     |        |
| Gain margin            |                                      |                                                                                                        |                                 | 25°C                        | 7      |     |     | dB     |

$^\dagger$  Full range is  $0^\circ\text{C}$  to  $70^\circ\text{C}$  for the C suffix,  $-40^\circ\text{C}$  to  $125^\circ\text{C}$  for the I and Q suffixes, and  $-55^\circ\text{C}$  to  $125^\circ\text{C}$  for the M suffix.



# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

electrical characteristics at specified free-air temperature,  $V_{DD} = 5\text{ V}$  (unless otherwise noted)

| PARAMETER                                                                    | TEST CONDITIONS                                                                                      | $T_A^\dagger$           | MIN | TYP      | MAX  | UNIT                         |
|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|-------------------------|-----|----------|------|------------------------------|
| $V_{IO}$ Input offset voltage                                                | $V_{DD} = 5\text{ V}$ ,<br>$V_{IC} = 2.5\text{ V}$ ,<br>$V_O = 2.5\text{ V}$ ,<br>$R_S = 50\ \Omega$ | 25°C                    |     | 500      | 2000 | $\mu\text{V}$                |
|                                                                              |                                                                                                      | Full range              |     |          | 2200 |                              |
|                                                                              |                                                                                                      | 25°C                    |     | 500      | 1500 |                              |
|                                                                              |                                                                                                      | Full range              |     |          | 1700 |                              |
| $\alpha_{VIO}$ Temperature coefficient of input offset voltage               |                                                                                                      | 25°C                    |     | 2        |      | $\mu\text{V}/^\circ\text{C}$ |
| $I_{IO}$ Input offset current                                                | $V_{DD} = 5\text{ V}$ ,<br>$V_{IC} = 2.5\text{ V}$ ,<br>$V_O = 2.5\text{ V}$ ,<br>$R_S = 50\ \Omega$ | 25°C                    |     | 0.3      | 7    | nA                           |
|                                                                              |                                                                                                      | TLV246xC Full range     |     |          | 15   |                              |
|                                                                              |                                                                                                      | TLV246xI/Q/M Full range |     |          | 60   |                              |
| $I_{IB}$ Input bias current                                                  | $V_{DD} = 5\text{ V}$ ,<br>$V_{IC} = 2.5\text{ V}$ ,<br>$V_O = 2.5\text{ V}$ ,<br>$R_S = 50\ \Omega$ | 25°C                    |     | 1.3      | 14   | nA                           |
|                                                                              |                                                                                                      | TLV246xC Full range     |     |          | 30   |                              |
|                                                                              |                                                                                                      | TLV246xI/Q/M Full range |     |          | 60   |                              |
| $V_{OH}$ High-level output voltage                                           | $I_{OH} = -2.5\text{ mA}$                                                                            | 25°C                    |     | 4.9      |      | V                            |
|                                                                              |                                                                                                      | Full range              | 4.8 |          |      |                              |
|                                                                              | $I_{OH} = -10\text{ mA}$                                                                             | 25°C                    |     | 4.8      |      |                              |
|                                                                              |                                                                                                      | Full range              | 4.7 |          |      |                              |
| $V_{OL}$ Low-level output voltage                                            | $V_{IC} = 2.5\text{ V}$ , $I_{OL} = 2.5\text{ mA}$                                                   | 25°C                    |     | 0.1      |      | V                            |
|                                                                              |                                                                                                      | Full range              |     |          | 0.2  |                              |
|                                                                              | $V_{IC} = 2.5\text{ V}$ , $I_{OL} = 10\text{ mA}$                                                    | 25°C                    |     | 0.2      |      |                              |
|                                                                              |                                                                                                      | Full range              |     |          | 0.3  |                              |
| $I_{OS}$ Short-circuit output current                                        | Sourcing                                                                                             | 25°C                    |     | 145      |      | mA                           |
|                                                                              |                                                                                                      | Full range              | 60  |          |      |                              |
|                                                                              | Sinking                                                                                              | 25°C                    |     | 100      |      |                              |
|                                                                              |                                                                                                      | Full range              | 60  |          |      |                              |
| $I_O$ Output current                                                         | Measured at 1 V from rail                                                                            | 25°C                    |     | $\pm 80$ |      | mA                           |
| $A_{VD}$ Large-signal differential voltage amplification                     | $V_{IC} = 2.5\text{ V}$ , $R_L = 10\text{ k}\Omega$ ,<br>$V_O = 1\text{ V to }4\text{ V}$            | 25°C                    | 92  | 109      |      | dB                           |
|                                                                              |                                                                                                      | Full range              | 90  |          |      |                              |
| $r_{i(d)}$ Differential input resistance                                     |                                                                                                      | 25°C                    |     | $10^9$   |      | $\Omega$                     |
| $c_{i(c)}$ Common-mode input capacitance                                     | $f = 10\text{ kHz}$                                                                                  | 25°C                    |     | 7        |      | pF                           |
| $z_o$ Closed-loop output impedance                                           | $f = 100\text{ kHz}$ , $A_V = 10$                                                                    | 25°C                    |     | 29       |      | $\Omega$                     |
| CMRR Common-mode rejection ratio                                             | $V_{ICR} = 0\text{ V to }5\text{ V}$ ,<br>$R_S = 50\ \Omega$                                         | 25°C                    | 71  | 85       |      | dB                           |
|                                                                              |                                                                                                      | TLV246xC Full range     | 69  |          |      |                              |
|                                                                              |                                                                                                      | TLV246xI/Q/M Full range | 60  |          |      |                              |
| $k_{SVR}$ Supply voltage rejection ratio ( $\Delta V_{DD} / \Delta V_{IO}$ ) | $V_{DD} = 2.7\text{ V to }6\text{ V}$ ,<br>No load                                                   | 25°C                    | 80  | 85       |      | dB                           |
|                                                                              |                                                                                                      | Full range              | 75  |          |      |                              |
|                                                                              | $V_{DD} = 3\text{ V to }5\text{ V}$ ,<br>No load                                                     | 25°C                    | 85  | 95       |      | dB                           |
|                                                                              |                                                                                                      | Full range              | 80  |          |      |                              |
| $I_{DD}$ Supply current (per channel)                                        | $V_O = 2.5\text{ V}$ , No load,                                                                      | 25°C                    |     | 0.55     | 0.65 | mA                           |
|                                                                              |                                                                                                      | Full range              |     |          | 1    |                              |
| $I_{DD(SHDN)}$ Supply current in shutdown (TLV2460, TLV2463, TLV2465)        | $\overline{\text{SHDN}} < 0.7\text{ V}$ , Per channels in shutdown                                   | 25°C                    |     | 1        |      | $\mu\text{A}$                |
|                                                                              |                                                                                                      | Full range              |     |          | 3    |                              |

 $^\dagger$  Full range is 0°C to 70°C for the C suffix, -40°C to 125°C for the I and Q suffixes, and -55°C to 125°C for the M suffix.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

### OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

operating characteristics at specified free-air temperature,  $V_{DD} = 5\text{ V}$  (unless otherwise noted)

| PARAMETER              |                                      | TEST CONDITIONS                                                                               |                                 | T <sub>A</sub> <sup>†</sup> | MIN        | TYP | MAX | UNIT   |
|------------------------|--------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------------|-----------------------------|------------|-----|-----|--------|
| SR                     | Slew rate at unity gain              | V <sub>O(PP)</sub> = 2 V,<br>R <sub>L</sub> = 10 kΩ                                           |                                 | C <sub>L</sub> = 160 pF,    | 25°C       | 0.9 | 1.6 | V/μs   |
|                        |                                      |                                                                                               |                                 |                             | Full range | 0.8 |     |        |
| V <sub>n</sub>         | Equivalent input noise voltage       | f = 100 Hz                                                                                    |                                 | 25°C                        | 14         |     |     | nV/√Hz |
|                        |                                      | f = 1 kHz                                                                                     |                                 | 25°C                        | 11         |     |     |        |
| I <sub>n</sub>         | Equivalent input noise current       | f = 100 Hz                                                                                    |                                 | 25°C                        | 0.13       |     |     | pA/√Hz |
| THD + N                | Total harmonic distortion plus noise | V <sub>O(PP)</sub> = 4 V,<br>R <sub>L</sub> = 10 kΩ,<br>f = 10 kHz                            | A <sub>V</sub> = 1              | 25°C                        | 0.004%     |     |     |        |
|                        |                                      |                                                                                               | A <sub>V</sub> = 10             |                             | 0.01%      |     |     |        |
|                        |                                      |                                                                                               | A <sub>V</sub> = 100            |                             | 0.04%      |     |     |        |
| t <sub>(on)</sub>      | Amplifier turnon time                | A <sub>V</sub> = 1, R <sub>L</sub> = 10 kΩ                                                    | Both channels                   | 25°C                        | 7.6        |     |     | μs     |
|                        |                                      |                                                                                               | Channel 1 only,<br>Channel 2 on |                             | 7.65       |     |     |        |
|                        |                                      |                                                                                               | Channel 2 only,<br>Channel 1 on |                             | 7.25       |     |     |        |
| t <sub>(off)</sub>     | Amplifier turnoff time               | A <sub>V</sub> = 1, R <sub>L</sub> = 10 kΩ                                                    | Both channels                   | 25°C                        | 333        |     |     | ns     |
|                        |                                      |                                                                                               | Channel 1 only,<br>Channel 2 on |                             | 328        |     |     |        |
|                        |                                      |                                                                                               | Channel 2 only,<br>Channel 1 on |                             | 329        |     |     |        |
| Gain-bandwidth product |                                      | f = 10 kHz,<br>C <sub>L</sub> = 160 pF                                                        | R <sub>L</sub> = 10 kΩ,         | 25°C                        | 6.4        |     |     | MHz    |
| t <sub>s</sub>         | Settling time                        | V(STEP)PP = 2 V,<br>A <sub>V</sub> = -1,<br>C <sub>L</sub> = 10 pF,<br>R <sub>L</sub> = 10 kΩ | 0.1%                            | 25°C                        | 1.53       |     |     | μs     |
|                        |                                      |                                                                                               | 0.01%                           |                             | 1.83       |     |     |        |
|                        |                                      | V(STEP)PP = 2 V,<br>A <sub>V</sub> = -1,<br>C <sub>L</sub> = 56 pF,<br>R <sub>L</sub> = 10 kΩ | 0.1%                            |                             | 3.13       |     |     |        |
|                        |                                      |                                                                                               | 0.01%                           |                             | 3.33       |     |     |        |
| φ <sub>m</sub>         | Phase margin at unity gain           | R <sub>L</sub> = 10 kΩ,<br>C <sub>L</sub> = 160 pF                                            |                                 | 25°C                        | 45°        |     |     |        |
|                        | Gain margin                          |                                                                                               |                                 | 25°C                        | 7          |     |     | dB     |

<sup>†</sup> Full range is 0°C to 70°C for the C suffix, -40°C to 125°C for the I and Q suffixes, and -55°C to 125°C for the M suffix.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS

Table of Graphs

|             |                                      |                                  | FIGURE |
|-------------|--------------------------------------|----------------------------------|--------|
| $V_{IO}$    | Input offset voltage                 | vs Common-mode input voltage     | 1, 2   |
| $I_{IB}$    | Input bias current                   | vs Free-air temperature          | 3, 4   |
| $I_{IO}$    | Input offset current                 | vs Free-air temperature          | 3, 4   |
| $V_{OH}$    | High-level output voltage            | vs High-level output current     | 5, 6   |
| $V_{OL}$    | Low-level output voltage             | vs Low-level output current      | 7, 8   |
| $V_{O(PP)}$ | Peak-to-peak output voltage          | vs Frequency                     | 9, 10  |
|             | Open-loop gain                       | vs Frequency                     | 11, 12 |
|             | Phase                                | vs Frequency                     | 11, 12 |
| $A_{VD}$    | Differential voltage amplification   | vs Load resistance               | 13     |
|             | Capacitive load                      | vs Load resistance               | 14     |
| $Z_o$       | Output impedance                     | vs Frequency                     | 15, 16 |
| CMRR        | Common-mode rejection ratio          | vs Frequency                     | 17     |
| $k_{SVR}$   | Supply-voltage rejection ratio       | vs Frequency                     | 18, 19 |
| $I_{DD}$    | Supply current                       | vs Supply voltage                | 20     |
|             |                                      | vs Free-air temperature          | 21     |
|             | Amplifier turnon characteristics     |                                  | 22     |
|             | Amplifier turnoff characteristics    |                                  | 23     |
|             | Supply current turnon                |                                  | 24     |
|             | Supply current turnoff               |                                  | 25     |
|             | Shutdown supply current              | vs Free-air temperature          | 26     |
| SR          | Slew rate                            | vs Supply voltage                | 27     |
| $V_n$       | Equivalent input noise voltage       | vs Frequency                     | 28, 29 |
|             |                                      | vs Common-mode input voltage     | 30, 31 |
| THD         | Total harmonic distortion            | vs Frequency                     | 32, 33 |
| THD+N       | Total harmonic distortion plus noise | vs Peak-to-peak signal amplitude | 34, 35 |
| $\phi_m$    | Phase margin                         | vs Frequency                     | 11, 12 |
|             |                                      | vs Load capacitance              | 36     |
|             |                                      | vs Free-air temperature          | 37     |
|             | Gain bandwidth product               | vs Supply voltage                | 38     |
|             |                                      | vs Free-air temperature          | 39     |
|             | Large signal follower                |                                  | 40, 41 |
|             | Small signal follower                |                                  | 42, 43 |
|             | Inverting large signal               |                                  | 44, 45 |
|             | Inverting small signal               |                                  | 46, 47 |

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

### OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

#### TYPICAL CHARACTERISTICS

INPUT OFFSET VOLTAGE  
vs  
COMMON-MODE INPUT VOLTAGE




Figure 1

INPUT OFFSET VOLTAGE  
vs  
COMMON-MODE INPUT VOLTAGE




Figure 2

INPUT BIAS AND INPUT OFFSET CURRENT  
vs  
FREE-AIR TEMPERATURE




Figure 3

INPUT BIAS AND INPUT OFFSET CURRENT  
vs  
FREE-AIR TEMPERATURE




Figure 4

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS




Figure 5




Figure 6




Figure 7




Figure 8

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

## TYPICAL CHARACTERISTICS




Figure 9




Figure 10




Figure 11

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS

#### OPEN-LOOP GAIN AND PHASE VS FREQUENCY




Figure 12

#### DIFFERENTIAL VOLTAGE AMPLIFICATION VS LOAD RESISTANCE




Figure 13

#### CAPACITIVE LOAD VS LOAD RESISTANCE




Figure 14

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS

OUTPUT IMPEDANCE  
vs  
FREQUENCY




Figure 15

OUTPUT IMPEDANCE  
vs  
FREQUENCY




Figure 16

COMMON-MODE REJECTION RATIO  
vs  
FREQUENCY




Figure 17



# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS




Figure 18




Figure 19




Figure 20




Figure 21

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

## TYPICAL CHARACTERISTICS

AMPLIFIER WITH A SHUTDOWN PULSE  
TURNON CHARACTERISTICS




Figure 22

AMPLIFIER WITH A SHUTDOWN PULSE  
TURNOFF CHARACTERISTICS




Figure 23

SUPPLY CURRENT WITH A SHUTDOWN PULSE  
TURNON CHARACTERISTICS




Figure 24

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS

#### TURN-OFF SUPPLY CURRENT WITH A SHUTDOWN PULSE




Figure 25

#### SHUTDOWN SUPPLY CURRENT VS FREE-AIR TEMPERATURE




Figure 26

#### SLEW RATE VS SUPPLY VOLTAGE




Figure 27

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS

EQUIVALENT INPUT NOISE VOLTAGE  
vs  
FREQUENCY




Figure 28

EQUIVALENT INPUT NOISE VOLTAGE  
vs  
FREQUENCY




Figure 29

EQUIVALENT INPUT NOISE VOLTAGE  
vs  
COMMON-MODE INPUT VOLTAGE




Figure 30

EQUIVALENT INPUT NOISE VOLTAGE  
vs  
COMMON-MODE INPUT VOLTAGE




Figure 31

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

### OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

#### TYPICAL CHARACTERISTICS




Figure 32




Figure 33




Figure 34




Figure 35

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### TYPICAL CHARACTERISTICS




Figure 36




Figure 37




Figure 38




Figure 39

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

### OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

#### TYPICAL CHARACTERISTICS




Figure 40




Figure 41




Figure 42




Figure 43

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

### OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

#### TYPICAL CHARACTERISTICS




Figure 44




Figure 45




Figure 46




Figure 47



# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### PARAMETER MEASUREMENT INFORMATION




Figure 48

### APPLICATION INFORMATION

#### driving a capacitive load

When the amplifier is configured in this manner, capacitive loading directly on the output will decrease the device's phase margin leading to high frequency ringing or oscillations. Therefore, for capacitive loads of greater than 10 pF, it is recommended that a resistor be placed in series ( $R_{NULL}$ ) with the output of the amplifier, as shown in Figure 49. A minimum value of 20  $\Omega$  should work well for most applications.




Figure 49. Driving a Capacitive Load

#### offset voltage

The output offset voltage, ( $V_{OO}$ ) is the sum of the input offset voltage ( $V_{IO}$ ) and both input bias currents ( $I_{IB}$ ) times the corresponding gains. The following schematic and formula can be used to calculate the output offset voltage:




Figure 50. Output Offset Voltage Model

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### APPLICATION INFORMATION

#### general configurations

When receiving low-level signals, limiting the bandwidth of the incoming signals into the system is often required. The simplest way to accomplish this is to place an RC filter at the noninverting terminal of the amplifier (see Figure 51).




Figure 51. Single-Pole Low-Pass Filter

If even more attenuation is needed, a multiple pole filter is required. The Sallen-Key filter can be used for this task. For best results, the amplifier should have a bandwidth that is 8 to 10 times the filter frequency bandwidth. Failure to do this can result in phase shift of the amplifier.




Figure 52. 2-Pole Low-Pass Sallen-Key Filter

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### APPLICATION INFORMATION

#### shutdown function

Three members of the TLV246x family (TLV2460/3/5) have a shutdown terminal for conserving battery life in portable applications. When the shutdown terminal is tied low, the supply current is reduced to 0.3  $\mu\text{A}/\text{channel}$ , the amplifier is disabled, and the outputs are placed in a high impedance mode. To enable the amplifier, the shutdown terminal can either be left floating or pulled high. When the shutdown terminal is left floating, care should be taken to ensure that parasitic leakage current at the shutdown terminal does not inadvertently place the operational amplifier into shutdown. The shutdown terminal threshold is always referenced to  $V_{DD}/2$ . Therefore, when operating the device with split supply voltages (e.g.  $\pm 2.5\text{ V}$ ), the shutdown terminal needs to be pulled to  $V_{DD-}$  (not GND) to disable the operational amplifier.

The amplifier's output with a shutdown pulse is shown in Figures 22, 23, 24, and 25. The amplifier is powered with a single 5-V supply and configured as a noninverting configuration with a gain of 5. The amplifier turnon and turnoff times are measured from the 50% point of the shutdown pulse to the 50% point of the output waveform. The times for the single, dual, and quad are listed in the data tables.

#### circuit layout considerations

To achieve the levels of high performance of the TLV246x, follow proper printed-circuit board design techniques. A general set of guidelines is given in the following.

- Ground planes – It is highly recommended that a ground plane be used on the board to provide all components with a low inductive ground connection. However, in the areas of the amplifier inputs and output, the ground plane can be removed to minimize the stray capacitance.
- Proper power supply decoupling – Use a 6.8- $\mu\text{F}$  tantalum capacitor in parallel with a 0.1- $\mu\text{F}$  ceramic capacitor on each supply terminal. It may be possible to share the tantalum among several amplifiers depending on the application, but a 0.1- $\mu\text{F}$  ceramic capacitor should always be used on the supply terminal of every amplifier. In addition, the 0.1- $\mu\text{F}$  capacitor should be placed as close as possible to the supply terminal. As this distance increases, the inductance in the connecting trace makes the capacitor less effective. The designer should strive for distances of less than 0.1 inches between the device power terminals and the ceramic capacitors.
- Sockets – Sockets can be used but are not recommended. The additional lead inductance in the socket pins will often lead to stability problems. Surface-mount packages soldered directly to the printed-circuit board is the best implementation.
- Short trace runs/compact part placements – Optimum high performance is achieved when stray series inductance has been minimized. To realize this, the circuit layout should be made as compact as possible, thereby minimizing the length of all trace runs. Particular attention should be paid to the inverting input of the amplifier. Its length should be kept as short as possible. This will help to minimize stray capacitance at the input of the amplifier.
- Surface-mount passive components – Using surface-mount passive components is recommended for high performance amplifier circuits for several reasons. First, because of the extremely low lead inductance of surface-mount components, the problem with stray series inductance is greatly reduced. Second, the small size of surface-mount components naturally leads to a more compact layout thereby minimizing both stray inductance and capacitance. If leaded components are used, it is recommended that the lead lengths be kept as short as possible.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### APPLICATION INFORMATION

#### general power dissipation considerations

For a given  $\theta_{JA}$ , the maximum power dissipation is shown in Figure 53 and is calculated by the following formula:

$$P_D = \left( \frac{T_{MAX} - T_A}{\theta_{JA}} \right)$$

Where:

$P_D$  = Maximum power dissipation of THS246x IC (watts)


$T_{MAX}$  = Absolute maximum junction temperature (150°C)

$T_A$  = Free-ambient air temperature (°C)

$\theta_{JA} = \theta_{JC} + \theta_{CA}$

$\theta_{JC}$  = Thermal coefficient from junction to case

$\theta_{CA}$  = Thermal coefficient from case to ambient air (°C/W)



NOTE A: Results are with no air flow and using JEDEC Standard Low-K test PCB.

**Figure 53. Maximum Power Dissipation vs Free-Air Temperature**

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

## APPLICATION INFORMATION

### macromodel information

Macromodel information provided was derived using Microsim *Parts*™ Release 8, the model generation software used with Microsim *PSpice*™. The Boyle macromodel (see Note 2) and subcircuit in Figure 54 are generated using the TLV246x typical electrical and operating characteristics at  $T_A = 25^\circ\text{C}$ . Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification
- Unity-gain frequency
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit

NOTE 2: G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, "Macromodeling of Integrated Circuit Operational Amplifiers", *IEEE Journal of Solid-State Circuits*, SC-9, 353 (1974).




Figure 54. Boyle Macromodels and Subcircuit

*PSpice* and *Parts* are trademarks of MicroSim Corporation.

# TLV2460, TLV2461, TLV2462, TLV2463, TLV2464, TLV2465, TLV246xA

## FAMILY OF LOW-POWER RAIL-TO-RAIL INPUT/OUTPUT

## OPERATIONAL AMPLIFIERS WITH SHUTDOWN

SLOS220J – JULY 1998 – REVISED FEBRUARY 2004

### macromodel information (continued)

|                                       |                                                       |    |    |          |
|---------------------------------------|-------------------------------------------------------|----|----|----------|
| .subckt TLV_246Y 1 2 3 4 5 6          | rp                                                    | 3  | 71 | 8.9127   |
| c1 11 12 2.4603E-12                   | rss                                                   | 10 | 99 | 10.610E6 |
| c2 72 7 10.000E-12                    | rs1                                                   | 6  | 4  | 1G       |
| css 10 99 443.21E-15                  | rs2                                                   | 6  | 4  | 1G       |
| dc 70 53 dy                           | rs3                                                   | 6  | 4  | 1G       |
| de 54 70 dy                           | rs4                                                   | 6  | 4  | 1G       |
| dlp 90 91 dx                          | s1                                                    | 71 | 4  | 6 4 s1x  |
| dln 92 90 dx                          | s2                                                    | 70 | 5  | 6 4 s1x  |
| dp 4 3 dx                             | s3                                                    | 10 | 74 | 6 4 s1x  |
| egnd 99 0 poly(2) (3,0) (4,0) 0 .5 .5 | s4                                                    | 74 | 4  | 6 4 s2x  |
| fb 7 99 poly(5) vb vc ve vlp vln 0    | vb                                                    | 9  | 0  | dc 0     |
| 21.600E6 -1E3 1E3 22E6 -22E6          | vc                                                    | 3  | 53 | dc .7836 |
| ga 72 0 11 12 345.26E-6               | ve                                                    | 54 | 4  | dc .7436 |
| gcm 0 72 10 99 15.422E-9              | vlim                                                  | 7  | 8  | dc 0     |
| iss 74 4 dc 18.850E-6                 | vlp                                                   | 91 | 0  | dc 117   |
| hlim 90 0 vlim 1K                     | vln                                                   | 0  | 92 | dc 117   |
| j1 11 2 10 jx1                        | .model dx D(Is=800.00E-18)                            |    |    |          |
| j2 12 1 10 jx2                        | .model dy D(Is=800.00E-18 Rs=1m Cjo=10p)              |    |    |          |
| r2 72 9 100.00E3                      | .model jx1 NJF(Is=1.0000E-12 Beta=6.3239E-3 Vto=-1)   |    |    |          |
| rd1 3 11 2.8964E3                     | .model jx2 NJF(Is=1.0000E-12 Beta=6.3239E-3 Vto=-1)   |    |    |          |
| rd2 3 12 2.8964E3                     | .model s1x VSWITCH(Roff=1E8 Ron=1.0 Voff=2.5 Von=0.0) |    |    |          |
| ro1 8 70 5.6000                       | .model s2x VSWITCH(Roff=1E8 Ron=1.0 Voff=0 Von=2.5)   |    |    |          |
| ro2 7 99 6.2000                       | .ends                                                 |    |    |          |

Figure 54. Boyle Macromodels and Subcircuit (Continued)

## PACKAGING INFORMATION

| Orderable part number           | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                     |
|---------------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|-----------------------------------------|
| <a href="#">5962-0051201QHA</a> | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051201QHA<br>TLV2460M                  |
| <a href="#">5962-0051203QHA</a> | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051203QHA<br>TLV2461M                  |
| <a href="#">5962-0051205QHA</a> | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051205QHA<br>TLV2462M                  |
| <a href="#">5962-0051206Q2A</a> | Active        | Production           | LCCC (FK)   20   | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-<br>0051206Q2A<br>TLV2462A<br>MFKB |
| <a href="#">5962-0051206QHA</a> | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051206QHA<br>TLV2462AM                 |
| <a href="#">5962-0051206QPA</a> | Active        | Production           | CDIP (JG)   8    | 50   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051206QPA<br>TLV2462AM                 |
| <a href="#">TLV2460AIDR</a>     | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2460AI                                  |
| TLV2460AIDR.A                   | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2460AI                                  |
| <a href="#">TLV2460AIP</a>      | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2460AI                               |
| TLV2460AIP.A                    | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2460AI                               |
| <a href="#">TLV2460CD</a>       | Active        | Production           | SOIC (D)   8     | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2460C                                   |
| TLV2460CD.A                     | Active        | Production           | SOIC (D)   8     | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2460C                                   |
| <a href="#">TLV2460CDBVR</a>    | Active        | Production           | SOT-23 (DBV)   6 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAOC                                    |
| TLV2460CDBVR.A                  | Active        | Production           | SOT-23 (DBV)   6 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAOC                                    |
| <a href="#">TLV2460CDBVT</a>    | Active        | Production           | SOT-23 (DBV)   6 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAOC                                    |
| TLV2460CDBVT.A                  | Active        | Production           | SOT-23 (DBV)   6 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAOC                                    |
| TLV2460CDBVTG4                  | Active        | Production           | SOT-23 (DBV)   6 | 250   SMALL T&R       | -           | Call TI                              | Call TI                           | 0 to 70      |                                         |
| <a href="#">TLV2460CDR</a>      | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2460C                                   |
| TLV2460CDR.A                    | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2460C                                   |
| <a href="#">TLV2460CP</a>       | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2460C                                |
| TLV2460CP.A                     | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2460C                                |
| <a href="#">TLV2460ID</a>       | Active        | Production           | SOIC (D)   8     | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2460I                                   |
| TLV2460ID.A                     | Active        | Production           | SOIC (D)   8     | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2460I                                   |

| Orderable part number        | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)    |
|------------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|------------------------|
| <a href="#">TLV2460IDBVR</a> | Active        | Production           | SOT-23 (DBV)   6 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAOI                   |
| TLV2460IDBVR.A               | Active        | Production           | SOT-23 (DBV)   6 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAOI                   |
| <a href="#">TLV2460IDBVT</a> | Active        | Production           | SOT-23 (DBV)   6 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAOI                   |
| TLV2460IDBVT.A               | Active        | Production           | SOT-23 (DBV)   6 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAOI                   |
| <a href="#">TLV2460IDR</a>   | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2460I                  |
| TLV2460IDR.A                 | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2460I                  |
| <a href="#">TLV2460IP</a>    | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2460I               |
| TLV2460IP.A                  | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2460I               |
| <a href="#">TLV2460MUB</a>   | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051201QHA<br>TLV2460M |
| TLV2460MUB.A                 | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051201QHA<br>TLV2460M |
| <a href="#">TLV2461AID</a>   | Obsolete      | Production           | SOIC (D)   8     | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | 2461AI                 |
| <a href="#">TLV2461AIDR</a>  | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2461AI                 |
| TLV2461AIDR.A                | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2461AI                 |
| <a href="#">TLV2461AIP</a>   | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2461AI              |
| TLV2461AIP.A                 | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2461AI              |
| <a href="#">TLV2461CD</a>    | Active        | Production           | SOIC (D)   8     | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2461C                  |
| TLV2461CD.A                  | Active        | Production           | SOIC (D)   8     | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2461C                  |
| <a href="#">TLV2461CDBVR</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAPC                   |
| TLV2461CDBVR.A               | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAPC                   |
| <a href="#">TLV2461CDBVT</a> | Active        | Production           | SOT-23 (DBV)   5 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAPC                   |
| TLV2461CDBVT.A               | Active        | Production           | SOT-23 (DBV)   5 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | VAPC                   |
| <a href="#">TLV2461CDR</a>   | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2461C                  |
| TLV2461CDR.A                 | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2461C                  |
| <a href="#">TLV2461CP</a>    | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2461C               |
| TLV2461CP.A                  | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2461C               |
| <a href="#">TLV2461IDBVR</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAPI                   |
| TLV2461IDBVR.A               | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAPI                   |
| <a href="#">TLV2461IDBVT</a> | Active        | Production           | SOT-23 (DBV)   5 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAPI                   |
| TLV2461IDBVT.A               | Active        | Production           | SOT-23 (DBV)   5 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | VAPI                   |



| Orderable part number        | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                     |
|------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|-----------------------------------------|
| <a href="#">TLV2461IDR</a>   | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2461I                                   |
| TLV2461IDR.A                 | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2461I                                   |
| <a href="#">TLV2461IP</a>    | Active        | Production           | PDIP (P)   8   | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2461I                                |
| TLV2461IP.A                  | Active        | Production           | PDIP (P)   8   | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2461I                                |
| <a href="#">TLV2461MUB</a>   | Active        | Production           | CFP (U)   10   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051203QHA<br>TLV2461M                  |
| TLV2461MUB.A                 | Active        | Production           | CFP (U)   10   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051203QHA<br>TLV2461M                  |
| <a href="#">TLV2462AID</a>   | Active        | Production           | SOIC (D)   8   | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462AI                                  |
| TLV2462AID.A                 | Active        | Production           | SOIC (D)   8   | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462AI                                  |
| TLV2462AID.B                 | Active        | Production           | SOIC (D)   8   | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462AI                                  |
| <a href="#">TLV2462AIDR</a>  | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462AI                                  |
| TLV2462AIDR.A                | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462AI                                  |
| TLV2462AIDR.B                | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462AI                                  |
| <a href="#">TLV2462AIP</a>   | Active        | Production           | PDIP (P)   8   | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2462AI                               |
| TLV2462AIP.A                 | Active        | Production           | PDIP (P)   8   | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2462AI                               |
| <a href="#">TLV2462AMFKB</a> | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-<br>0051206Q2A<br>TLV2462A<br>MFKB |
| TLV2462AMFKB.A               | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-<br>0051206Q2A<br>TLV2462A<br>MFKB |
| <a href="#">TLV2462AMJG</a>  | Active        | Production           | CDIP (JG)   8  | 50   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | TLV2462AMJG                             |
| TLV2462AMJG.A                | Active        | Production           | CDIP (JG)   8  | 50   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | TLV2462AMJG                             |
| <a href="#">TLV2462AMJGB</a> | Active        | Production           | CDIP (JG)   8  | 50   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051206QPA<br>TLV2462AM                 |
| TLV2462AMJGB.A               | Active        | Production           | CDIP (JG)   8  | 50   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051206QPA<br>TLV2462AM                 |
| <a href="#">TLV2462AMUB</a>  | Active        | Production           | CFP (U)   10   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051206QHA<br>TLV2462AM                 |
| TLV2462AMUB.A                | Active        | Production           | CFP (U)   10   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051206QHA<br>TLV2462AM                 |

| Orderable part number         | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-------------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">TLV2462AQD</a>    | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| TLV2462AQD.A                  | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| TLV2462AQD.B                  | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| <a href="#">TLV2462AQDG4</a>  | Obsolete      | Production           | SOIC (D)   8    | -                     | -           | Call TI                              | Call TI                           | -            | V2462A              |
| <a href="#">TLV2462AQDRG4</a> | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -            | V2462A              |
| TLV2462AQDRG4.A               | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| TLV2462AQDRG4.B               | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| <a href="#">TLV2462AQPWR</a>  | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| TLV2462AQPWR.A                | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| TLV2462AQPWR.B                | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462A              |
| <a href="#">TLV2462CD</a>     | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2462C               |
| TLV2462CD.A                   | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2462C               |
| TLV2462CD.B                   | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2462C               |
| TLV2462CDG4                   | Active        | Production           | SOIC (D)   8    | 75   TUBE             | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">TLV2462CDGK</a>   | Active        | Production           | VSSOP (DGK)   8 | 80   TUBE             | Yes         | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM                | 0 to 70      | AAI                 |
| TLV2462CDGK.A                 | Active        | Production           | VSSOP (DGK)   8 | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AAI                 |
| <a href="#">TLV2462CDGKR</a>  | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AAI                 |
| TLV2462CDGKR.B                | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AAI                 |
| TLV2462CDGKRG4                | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">TLV2462CDR</a>    | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2462C               |
| TLV2462CDR.A                  | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2462C               |
| TLV2462CDR.B                  | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2462C               |
| TLV2462CDRG4                  | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">TLV2462CP</a>     | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2462CP           |
| TLV2462CP.A                   | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2462CP           |
| TLV2462CP.B                   | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2462CP           |
| TLV2462CPE4                   | Active        | Production           | PDIP (P)   8    | 50   TUBE             | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">TLV2462ID</a>     | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462I               |
| TLV2462ID.A                   | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462I               |
| TLV2462ID.B                   | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462I               |
| TLV2462IDG4                   | Active        | Production           | SOIC (D)   8    | 75   TUBE             | -           | Call TI                              | Call TI                           | -40 to 125   |                     |

| Orderable part number         | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                     |
|-------------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|-----------------------------------------|
| <a href="#">TLV2462IDGK</a>   | Active        | Production           | VSSOP (DGK)   8  | 80   TUBE             | Yes         | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM                | -40 to 125   | AAJ                                     |
| TLV2462IDGK.A                 | Active        | Production           | VSSOP (DGK)   8  | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | AAJ                                     |
| TLV2462IDGKG4                 | Active        | Production           | VSSOP (DGK)   8  | 80   TUBE             | -           | Call TI                              | Call TI                           | -40 to 125   |                                         |
| <a href="#">TLV2462IDGKR</a>  | Active        | Production           | VSSOP (DGK)   8  | 2500   LARGE T&R      | Yes         | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM                | -40 to 125   | AAJ                                     |
| TLV2462IDGKR.B                | Active        | Production           | VSSOP (DGK)   8  | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | AAJ                                     |
| <a href="#">TLV2462IDR</a>    | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462I                                   |
| TLV2462IDR.A                  | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462I                                   |
| TLV2462IDR.B                  | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2462I                                   |
| <a href="#">TLV2462IP</a>     | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2462IP                               |
| TLV2462IP.A                   | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2462IP                               |
| TLV2462IP.B                   | Active        | Production           | PDIP (P)   8     | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2462IP                               |
| <a href="#">TLV2462MUB</a>    | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051205QHA<br>TLV2462M                  |
| TLV2462MUB.A                  | Active        | Production           | CFP (U)   10     | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 0051205QHA<br>TLV2462M                  |
| <a href="#">TLV2462QPWR</a>   | Active        | Production           | TSSOP (PW)   8   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462Q                                  |
| TLV2462QPWR.A                 | Active        | Production           | TSSOP (PW)   8   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462Q                                  |
| TLV2462QPWR.B                 | Active        | Production           | TSSOP (PW)   8   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462Q                                  |
| <a href="#">TLV2462QPWRG4</a> | Active        | Production           | TSSOP (PW)   8   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -            | V2462Q                                  |
| TLV2462QPWRG4.A               | Active        | Production           | TSSOP (PW)   8   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462Q                                  |
| TLV2462QPWRG4.B               | Active        | Production           | TSSOP (PW)   8   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | V2462Q                                  |
| <a href="#">TLV2463AIDR</a>   | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2463AI                               |
| TLV2463AIDR.A                 | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2463AI                               |
| TLV2463AIDR.B                 | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2463AI                               |
| TLV2463AMFKB                  | Obsolete      | Production           | LCCC (FK)   20   | -                     | -           | Call TI                              | Call TI                           | -            | 5962-<br>0051208Q2A<br>TLV2463<br>AMFKB |
| <a href="#">TLV2463AMJ</a>    | Active        | Production           | CDIP (J)   14    | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | TLV2463AMJ                              |
| TLV2463AMJ.A                  | Active        | Production           | CDIP (J)   14    | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | TLV2463AMJ                              |
| <a href="#">TLV2463CDGS</a>   | Active        | Production           | VSSOP (DGS)   10 | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AAK                                     |
| TLV2463CDGS.A                 | Active        | Production           | VSSOP (DGS)   10 | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AAK                                     |

| Orderable part number          | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|--------------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">TLV2463CDGSR</a>   | Active        | Production           | VSSOP (DGS)   10 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AAK                 |
| TLV2463CDGSR.B                 | Active        | Production           | VSSOP (DGS)   10 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AAK                 |
| <a href="#">TLV2463CDR</a>     | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2463C            |
| TLV2463CDR.A                   | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2463C            |
| TLV2463CDR.B                   | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2463C            |
| <a href="#">TLV2463CN</a>      | Active        | Production           | PDIP (N)   14    | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2463CN           |
| TLV2463CN.A                    | Active        | Production           | PDIP (N)   14    | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2463CN           |
| <a href="#">TLV2463ID</a>      | Active        | Production           | SOIC (D)   14    | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2463I            |
| TLV2463ID.A                    | Active        | Production           | SOIC (D)   14    | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2463I            |
| TLV2463ID.B                    | Active        | Production           | SOIC (D)   14    | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2463I            |
| <a href="#">TLV2463IDGS</a>    | Active        | Production           | VSSOP (DGS)   10 | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | AAL                 |
| TLV2463IDGS.B                  | Active        | Production           | VSSOP (DGS)   10 | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | AAL                 |
| <a href="#">TLV2463IDGSR</a>   | Active        | Production           | VSSOP (DGS)   10 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | AAL                 |
| TLV2463IDGSR.B                 | Active        | Production           | VSSOP (DGS)   10 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | AAL                 |
| <a href="#">TLV2463IN</a>      | Active        | Production           | PDIP (N)   14    | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2463IN           |
| TLV2463IN.A                    | Active        | Production           | PDIP (N)   14    | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2463IN           |
| <a href="#">TLV2464AID</a>     | Active        | Production           | SOIC (D)   14    | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2464AI              |
| TLV2464AID.A                   | Active        | Production           | SOIC (D)   14    | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2464AI              |
| TLV2464AIDG4                   | Active        | Production           | SOIC (D)   14    | 50   TUBE             | -           | Call TI                              | Call TI                           | -40 to 125   |                     |
| <a href="#">TLV2464AIDR</a>    | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2464AI              |
| TLV2464AIDR.A                  | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2464AI              |
| TLV2464AIDRG4                  | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | -           | Call TI                              | Call TI                           | -40 to 125   |                     |
| <a href="#">TLV2464AIN</a>     | Active        | Production           | PDIP (N)   14    | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2464AIN          |
| TLV2464AIN.A                   | Active        | Production           | PDIP (N)   14    | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2464AIN          |
| <a href="#">TLV2464AIPW</a>    | Active        | Production           | TSSOP (PW)   14  | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464A             |
| TLV2464AIPW.A                  | Active        | Production           | TSSOP (PW)   14  | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464A             |
| <a href="#">TLV2464AIPWR</a>   | Active        | Production           | TSSOP (PW)   14  | 2000   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | TY2464A             |
| TLV2464AIPWR.A                 | Active        | Production           | TSSOP (PW)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464A             |
| <a href="#">TLV2464AIPWRG4</a> | Active        | Production           | TSSOP (PW)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464A             |
| <a href="#">TLV2464CD</a>      | Active        | Production           | SOIC (D)   14    | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2464C            |
| TLV2464CD.A                    | Active        | Production           | SOIC (D)   14    | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2464C            |

| Orderable part number       | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-----------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">TLV2464CDR</a>  | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2464C            |
| TLV2464CDR.A                | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2464C            |
| <a href="#">TLV2464CN</a>   | Active        | Production           | PDIP (N)   14   | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2464CN           |
| TLV2464CN.A                 | Active        | Production           | PDIP (N)   14   | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TLV2464CN           |
| TLV2464CNE4                 | Active        | Production           | PDIP (N)   14   | 25   TUBE             | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">TLV2464CPW</a>  | Active        | Production           | TSSOP (PW)   14 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TV2464              |
| TLV2464CPW.A                | Active        | Production           | TSSOP (PW)   14 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TV2464              |
| <a href="#">TLV2464CPWR</a> | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | 0 to 70      | TV2464              |
| TLV2464CPWR.A               | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TV2464              |
| <a href="#">TLV2464ID</a>   | Active        | Production           | SOIC (D)   14   | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2464I            |
| TLV2464ID.A                 | Active        | Production           | SOIC (D)   14   | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2464I            |
| TLV2464ID.B                 | Active        | Production           | SOIC (D)   14   | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2464I            |
| TLV2464IDG4                 | Active        | Production           | SOIC (D)   14   | 50   TUBE             | -           | Call TI                              | Call TI                           | -40 to 125   |                     |
| <a href="#">TLV2464IDR</a>  | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2464I            |
| TLV2464IDR.A                | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2464I            |
| <a href="#">TLV2464IN</a>   | Active        | Production           | PDIP (N)   14   | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2464IN           |
| TLV2464IN.A                 | Active        | Production           | PDIP (N)   14   | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2464IN           |
| <a href="#">TLV2464IPW</a>  | Active        | Production           | TSSOP (PW)   14 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464              |
| TLV2464IPW.A                | Active        | Production           | TSSOP (PW)   14 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464              |
| <a href="#">TLV2464IPWR</a> | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464              |
| TLV2464IPWR.A               | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TY2464              |
| TLV2464IPWRG4               | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | -           | Call TI                              | Call TI                           | -40 to 125   |                     |
| <a href="#">TLV2465CDR</a>  | Active        | Production           | SOIC (D)   16   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2465C            |
| TLV2465CDR.A                | Active        | Production           | SOIC (D)   16   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TLV2465C            |
| <a href="#">TLV2465CPWR</a> | Active        | Production           | TSSOP (PW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2465C               |
| TLV2465CPWR.A               | Active        | Production           | TSSOP (PW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 2465C               |
| <a href="#">TLV2465ID</a>   | Active        | Production           | SOIC (D)   16   | 40   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2465I            |
| TLV2465ID.A                 | Active        | Production           | SOIC (D)   16   | 40   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2465I            |
| <a href="#">TLV2465IDR</a>  | Active        | Production           | SOIC (D)   16   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2465I            |
| TLV2465IDR.A                | Active        | Production           | SOIC (D)   16   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | TLV2465I            |
| <a href="#">TLV2465IN</a>   | Active        | Production           | PDIP (N)   16   | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2465IN           |

| Orderable part number       | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-----------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| TLV2465IN.A                 | Active        | Production           | PDIP (N)   16   | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | TLV2465IN           |
| <a href="#">TLV2465IPW</a>  | Active        | Production           | TSSOP (PW)   16 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2465I               |
| TLV2465IPW.A                | Active        | Production           | TSSOP (PW)   16 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2465I               |
| TLV2465IPW.B                | Active        | Production           | TSSOP (PW)   16 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2465I               |
| <a href="#">TLV2465IPWR</a> | Active        | Production           | TSSOP (PW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2465I               |
| TLV2465IPWR.A               | Active        | Production           | TSSOP (PW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2465I               |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "-" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF TLV2460, TLV2460A, TLV2460M, TLV2461, TLV2461A, TLV2461M, TLV2462, TLV2462A, TLV2462AM, TLV2462M, TLV2463A, TLV2463AM, TLV2464A :**


- Catalog : [TLV2460](#), [TLV2461](#), [TLV2462A](#), [TLV2462](#), [TLV2463A](#)
- Automotive : [TLV2460A-Q1](#), [TLV2461A-Q1](#), [TLV2462-Q1](#), [TLV2462A-Q1](#), [TLV2462A-Q1](#), [TLV2462-Q1](#), [TLV2463A-Q1](#), [TLV2463A-Q1](#), [TLV2464A-Q1](#)
- Enhanced Product : [TLV2462A-EP](#), [TLV2462A-EP](#), [TLV2464A-EP](#)
- Military : [TLV2460M](#), [TLV2461M](#), [TLV2462M](#), [TLV2462AM](#), [TLV2463AM](#)

NOTE: Qualified Version Definitions:


- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications
- Military - QML certified for Military and Defense Applications



## TAPE AND REEL INFORMATION



### QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



\*All dimensions are nominal

| Device       | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|--------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TLV2460AIDR  | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2460CDBVR | SOT-23       | DBV             | 6    | 3000 | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| TLV2460CDBVT | SOT-23       | DBV             | 6    | 250  | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| TLV2460CDR   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2460IDBVR | SOT-23       | DBV             | 6    | 3000 | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| TLV2460IDBVT | SOT-23       | DBV             | 6    | 250  | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| TLV2460IDR   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2461AIDR  | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2461CDBVR | SOT-23       | DBV             | 5    | 3000 | 178.0              | 9.0                | 3.3     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| TLV2461CDBVT | SOT-23       | DBV             | 5    | 250  | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| TLV2461CDR   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2461IDBVR | SOT-23       | DBV             | 5    | 3000 | 178.0              | 9.0                | 3.3     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| TLV2461IDBVT | SOT-23       | DBV             | 5    | 250  | 178.0              | 9.0                | 3.3     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| TLV2461IDR   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2462AIDR  | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2462AQPWR | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |



| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TLV2462CDGKR   | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| TLV2462CDR     | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2462IDGKR   | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| TLV2462IDR     | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TLV2462QPWR    | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| TLV2462QPWRG4  | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| TLV2463AIDR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| TLV2463CDGSR   | VSSOP        | DGS             | 10   | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| TLV2463CDR     | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| TLV2463IDGSR   | VSSOP        | DGS             | 10   | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| TLV2464AIDR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| TLV2464AIPWR   | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| TLV2464AIPWRG4 | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| TLV2464CDR     | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| TLV2464CPWR    | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| TLV2464IDR     | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| TLV2464IPWR    | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| TLV2465CDR     | SOIC         | D               | 16   | 2500 | 330.0              | 16.4               | 6.5     | 10.3    | 2.1     | 8.0     | 16.0   | Q1            |
| TLV2465CPWR    | TSSOP        | PW              | 16   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| TLV2465IPWR    | TSSOP        | PW              | 16   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |


## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device       | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|--------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TLV2460AIDR  | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| TLV2460CDBVR | SOT-23       | DBV             | 6    | 3000 | 180.0       | 180.0      | 18.0        |
| TLV2460CDBVT | SOT-23       | DBV             | 6    | 250  | 180.0       | 180.0      | 18.0        |
| TLV2460CDR   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2460IDBVR | SOT-23       | DBV             | 6    | 3000 | 180.0       | 180.0      | 18.0        |
| TLV2460IDBVT | SOT-23       | DBV             | 6    | 250  | 180.0       | 180.0      | 18.0        |
| TLV2460IDR   | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| TLV2461AIDR  | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2461CDBVR | SOT-23       | DBV             | 5    | 3000 | 180.0       | 180.0      | 18.0        |
| TLV2461CDBVT | SOT-23       | DBV             | 5    | 250  | 180.0       | 180.0      | 18.0        |
| TLV2461CDR   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2461IDBVR | SOT-23       | DBV             | 5    | 3000 | 180.0       | 180.0      | 18.0        |
| TLV2461IDBVT | SOT-23       | DBV             | 5    | 250  | 180.0       | 180.0      | 18.0        |
| TLV2461IDR   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2462AIDR  | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2462AQPWR | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| TLV2462CDGKR | VSSOP        | DGK             | 8    | 2500 | 358.0       | 335.0      | 35.0        |
| TLV2462CDR   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |

| Device         | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TLV2462IDGKR   | VSSOP        | DGK             | 8    | 2500 | 358.0       | 335.0      | 35.0        |
| TLV2462IDR     | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2462QPWR    | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| TLV2462QPWRG4  | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| TLV2463AIDR    | SOIC         | D               | 14   | 2500 | 350.0       | 350.0      | 43.0        |
| TLV2463CDGSR   | VSSOP        | DGS             | 10   | 2500 | 358.0       | 335.0      | 35.0        |
| TLV2463CDR     | SOIC         | D               | 14   | 2500 | 350.0       | 350.0      | 43.0        |
| TLV2463IDGSR   | VSSOP        | DGS             | 10   | 2500 | 358.0       | 335.0      | 35.0        |
| TLV2464AIDR    | SOIC         | D               | 14   | 2500 | 333.2       | 345.9      | 28.6        |
| TLV2464AIPWR   | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| TLV2464AIPWRG4 | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| TLV2464CDR     | SOIC         | D               | 14   | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2464CPWR    | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| TLV2464IDR     | SOIC         | D               | 14   | 2500 | 353.0       | 353.0      | 32.0        |
| TLV2464IPWR    | TSSOP        | PW              | 14   | 2000 | 353.0       | 353.0      | 32.0        |
| TLV2465CDR     | SOIC         | D               | 16   | 2500 | 350.0       | 350.0      | 43.0        |
| TLV2465CPWR    | TSSOP        | PW              | 16   | 2000 | 353.0       | 353.0      | 32.0        |
| TLV2465IPWR    | TSSOP        | PW              | 16   | 2000 | 353.0       | 353.0      | 32.0        |

**TUBE**


\*All dimensions are nominal

| Device          | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-----------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 5962-0051201QHA | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| 5962-0051203QHA | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| 5962-0051205QHA | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| 5962-0051206Q2A | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| 5962-0051206QHA | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2460AIP      | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2460AIP.A    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2460CD       | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2460CD.A     | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2460CP       | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2460CP.A     | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2460ID       | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2460ID       | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2460ID.A     | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2460ID.A     | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2460IP       | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2460IP.A     | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2460MUB      | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2460MUB.A    | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2461AIP      | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2461AIP.A    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2461CD       | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2461CD.A     | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2461CP       | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2461CP.A     | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2461IP       | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2461IP.A     | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2461MUB      | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2461MUB.A    | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |

| Device         | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|----------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| TLV2462AID     | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462AID     | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462AID.A   | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462AID.A   | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462AID.B   | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462AID.B   | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462AIP     | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462AIP.A   | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462AMFKB   | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| TLV2462AMFKB.A | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| TLV2462AMUB    | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2462AMUB.A  | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2462AQD     | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462AQD.A   | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462AQD.B   | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462CD      | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462CD      | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462CD.A    | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462CD.A    | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462CD.B    | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462CD.B    | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462CDGK    | DGK          | VSSOP        | 8    | 80  | 330    | 6.55   | 500    | 2.88   |
| TLV2462CDGK.A  | DGK          | VSSOP        | 8    | 80  | 330    | 6.55   | 500    | 2.88   |
| TLV2462CP      | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462CP.A    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462CP.B    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462ID      | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462ID      | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462ID.A    | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462ID.A    | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462ID.B    | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| TLV2462ID.B    | D            | SOIC         | 8    | 75  | 507    | 8      | 3940   | 4.32   |
| TLV2462IDGK    | DGK          | VSSOP        | 8    | 80  | 330    | 6.55   | 500    | 2.88   |
| TLV2462IDGK.A  | DGK          | VSSOP        | 8    | 80  | 330    | 6.55   | 500    | 2.88   |
| TLV2462IP      | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462IP.A    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462IP.B    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| TLV2462MUB     | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2462MUB.A   | U            | CFP          | 10   | 25  | 506.98 | 26.16  | 6220   | NA     |
| TLV2463CN      | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2463CN.A    | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2463ID      | D            | SOIC         | 14   | 50  | 505.46 | 6.76   | 3810   | 4      |
| TLV2463ID.A    | D            | SOIC         | 14   | 50  | 505.46 | 6.76   | 3810   | 4      |


| Device        | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|---------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| TLV2463ID.B   | D            | SOIC         | 14   | 50  | 505.46 | 6.76   | 3810   | 4      |
| TLV2463IN     | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2463IN.A   | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2464AID    | D            | SOIC         | 14   | 50  | 505.46 | 6.76   | 3810   | 4      |
| TLV2464AID    | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| TLV2464AID.A  | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| TLV2464AID.A  | D            | SOIC         | 14   | 50  | 505.46 | 6.76   | 3810   | 4      |
| TLV2464AIN    | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2464AIN.A  | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2464AIPW   | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2464AIPW.A | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2464CD     | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| TLV2464CD     | D            | SOIC         | 14   | 50  | 505.46 | 6.76   | 3810   | 4      |
| TLV2464CD.A   | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| TLV2464CD.A   | D            | SOIC         | 14   | 50  | 505.46 | 6.76   | 3810   | 4      |
| TLV2464CN     | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2464CN.A   | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2464CPW    | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2464CPW.A  | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2464ID     | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| TLV2464ID.A   | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| TLV2464ID.B   | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| TLV2464IN     | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2464IN.A   | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2464IPW    | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2464IPW.A  | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2465ID     | D            | SOIC         | 16   | 40  | 505.46 | 6.76   | 3810   | 4      |
| TLV2465ID.A   | D            | SOIC         | 16   | 40  | 505.46 | 6.76   | 3810   | 4      |
| TLV2465IN     | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2465IN.A   | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TLV2465IPW    | PW           | TSSOP        | 16   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2465IPW.A  | PW           | TSSOP        | 16   | 90  | 530    | 10.2   | 3600   | 3.5    |
| TLV2465IPW.B  | PW           | TSSOP        | 16   | 90  | 530    | 10.2   | 3600   | 3.5    |

JG0008A

## PACKAGE OUTLINE

CDIP - 5.08 mm max height

CERAMIC DUAL IN-LINE PACKAGE



4230036/A 09/2023

### NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package can be hermetically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification.
5. Falls within MIL STD 1835 GDIP1-T8

# EXAMPLE BOARD LAYOUT

JG0008A

CDIP - 5.08 mm max height

CERAMIC DUAL IN-LINE PACKAGE



LAND PATTERN EXAMPLE  
NON SOLDER MASK DEFINED  
SCALE: 9X

4230036/A 09/2023




U0010A



## PACKAGE OUTLINE

CFP - 2.03 mm max height

CERAMIC FLATPACK




4225582/A 01/2020

### NOTES:

1. All linear dimensions are in inches. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.

**DBV0005A****PACKAGE OUTLINE****SOT-23 - 1.45 mm max height**

SMALL OUTLINE TRANSISTOR

**NOTES:**


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-178.
4. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.25 mm per side.
5. Support pin may differ or may not be present.

# EXAMPLE BOARD LAYOUT


DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214839/K 08/2024

NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR




SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4214839/K 08/2024

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.


DGK0008A



# PACKAGE OUTLINE

VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



4214862/A 04/2023

## NOTES:

PowerPAD is a trademark of Texas Instruments.


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-187.

# EXAMPLE BOARD LAYOUT


DGK0008A

<sup>TM</sup> VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 15X



SOLDER MASK DETAILS

4214862/A 04/2023

## NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.
8. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.
9. Size of metal pad may vary due to creepage requirement.

## EXAMPLE STENCIL DESIGN

DGK0008A

<sup>TM</sup> VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE




SOLDER PASTE EXAMPLE  
SCALE: 15X


4214862/A 04/2023

NOTES: (continued)

11. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
12. Board assembly site may have different recommendations for stencil design.

**D0014A****PACKAGE OUTLINE****SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



4220718/A 09/2016

**NOTES:**

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm, per side.
5. Reference JEDEC registration MS-012, variation AB.




# EXAMPLE BOARD LAYOUT



D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
SCALE:8X



SOLDER MASK DETAILS

4220718/A 09/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:8X


4220718/A 09/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

D (R-PDSO-G16)


PLASTIC SMALL OUTLINE



4040047-6/M 06/11

NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
- D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
- E. Reference JEDEC MS-012 variation AC.



4221984/A 05/2015

**NOTES:**


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-187, variation BA.

# EXAMPLE BOARD LAYOUT



DGS0010A

VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221984/A 05/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DGS0010A

VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221984/A 05/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## GENERIC PACKAGE VIEW


**FK 20**

**LCCC - 2.03 mm max height**

8.89 x 8.89, 1.27 mm pitch

LEADLESS CERAMIC CHIP CARRIER

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.




4229370VA\

**J 14**

## GENERIC PACKAGE VIEW

**CDIP - 5.08 mm max height**


CERAMIC DUAL IN LINE PACKAGE




Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4040083-5/G



**J0014A****PACKAGE OUTLINE****CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE



4214771/A 05/2017

**NOTES:**

1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermetically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
5. Falls within MIL-STD-1835 and GDIP1-T14.




**TEXAS  
INSTRUMENTS**  
www.ti.com

# EXAMPLE BOARD LAYOUT



J0014A

CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE



LAND PATTERN EXAMPLE  
NON-SOLDER MASK DEFINED  
SCALE: 5X




4214771/A 05/2017



**PW0016A**

## TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE




1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

# EXAMPLE BOARD LAYOUT


PW0016A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



4220204/B 12/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

PW0016A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4220204/B 12/2023

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

**D0008A**

## PACKAGE OUTLINE

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



4214825/C 02/2019

NOTES:



1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019


NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.



P (R-PDIP-T8)

PLASTIC DUAL-IN-LINE PACKAGE




- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Falls within JEDEC MS-001 variation BA.


## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



| PINS **             | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| DIM                 |                  |                  |                  |                  |
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



14/18 Pin Only  
20 Pin vendor option

4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.



## SOT-23 - 1.45 mm max height

## SMALL OUTLINE TRANSISTOR




1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.25 per side.
4. Leads 1,2,3 may be wider than leads 4,5,6 for package orientation.
5. Reference JEDEC MO-178.

# EXAMPLE BOARD LAYOUT


DBV0006A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214840/G 08/2024

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DBV0006A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4214840/G 08/2024

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

**PW0014A**

## PACKAGE OUTLINE

**TSSOP - 1.2 mm max height**

SMALL OUTLINE PACKAGE



4220202/B 12/2023

NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

# EXAMPLE BOARD LAYOUT



PW0014A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4220202/B 12/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

PW0014A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4220202/B 12/2023

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.








## PACKAGE OUTLINE

## TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



4221848/A 02/2015

NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153, variation AA.

# EXAMPLE BOARD LAYOUT



PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221848/A 02/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221848/A 02/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025