


REV	DATE	APPROVED	DESCRIPTION
1	8-17-80	MS	
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			



1. WIRE INSULATION SEALING RANGE .070-.130 DIA.
2. THIN MEMBRANE PERMISSIBLE ON SMALL DIAMETER OF WIRE SEALS.

RECOMMENDED
PANEL CUTOUT
SCALE 2:1

DO NOT SCALE PRINT. DIMENSIONS SPECIFIED UNLESS SPECIFIED DIMENSIONS IN INCHES TOLERANCES ON: 2 PLG DEC $\pm .005$ 3 PLG DEC $\pm .005$ ANGLES $\pm .005$ MATERIAL		DR 8-17-80 J. GALLAGHER BS CHK <i>[Signature]</i> APPRO <i>[Signature]</i> 1-2-91 1-21-91	DATE 1-2-91 1-21-91
SEE CALLOUTS		PRODUCT SPEC 0	DATE 1-2-91 1-21-91
FINISH SEE CALLOUTS		APPLICATION SPEC	DATE 1-2-91 1-21-91
WEIGHT		SCALE 4:1	DATE 1-2-91 1-21-91
SIZE C 00779		FSCH NO 207982	DATE 1-2-91 1-21-91
SCALE 4:1		DRAWING NO 207982	DATE 1-2-91 1-21-91
SHEET 1 OF 1			

207982-1
PART
NUMBER

207982

CUSTOMER DRAWING