
Super Micro	Computer, Inc.				
		Contact Us Adv	anced Search \Box	Reseller Resource Center 🗆 📗	Search
About Us	Products	Support	News	Where To Buy	

Products □ Chassis □ 1U □ [SC818A-1400B]



Key Features

- 1. 1400W High-efficiency Power Supply **Gold Level Certified**
- 2. 3x 3.5" Hot-Swap SAS / SATA
- Drive Bays 3. 1x Slim DVD-ROM Drive (optional)
- 4. 7x 4cm Counter-rotating PVVM Fans
- 5. 1x Low Profile I/O Expansion Slot
- 6. Power Switch, Reset Switch and
- 7. Full SES2 support is available with SAS $\,$ motherboards and other compatible components.



Product SKUs

CSE-818A-1400B

• SuperChassis 818A-1400B (Black)

- 1U chassis support for max. motherboard size 16.48" x 14.3" (Quad-processor motherboards) - 16.48" x 16.8" (for X8 motherboards)

Quad Intel 1567-pin LGA Socket Processors

Dimensions	
Dimensions	
Height	• 1.7" (43mm)
Width	• 17.2" (437mm)
Depth	• 27.75" (705mm)
Gross Weight	• 38 lbs (17.2 kg)
Available Colors	Black

Expansion Slots

• 1x full-height, full-length expansion slot (Riser Card Required)

Drive Bays

Hot-swap

• 3x 3.5" hot-swap U320/160 SAS / SATA drive bays with SES2

SAS or enterprise SATA HDD only recommended

Backplane

SAS HDD Backplane with SES2

Peripheral Drives

DVD-ROM Slim DVD-ROM drive (optional)

Front Panel

LEDs

Buttons

- Power On/Off button System Reset button Power LED
- Hard drive activity LED
- 2x Network activity LEDsSystem Overheat LED
- 2x Front USB Ports1x Serial COM Port Ports

System Cooling

• 7x PWM cooling fans Fans

Operating Environment (System)

Operating

Temperature • 5°C ~ 35°C (41°F ~ 95°F) Range

Range

• -40°C ~ 60°C (-40°F ~ 140°F)

Operating Relative

• 8% ~ 90% (non-condensing) Humidity Range

Non-Operating

Range

Relative Humidity • 5% - 95% (non-condensing)

1400W high-efficiency power supply with PWBus

• 1200W: 100 - 140V, 50 - 60Hz, 10.5 - 14.7 AC Input

• 1400W: 180 - 240V, 50 - 60Hz, 7.2 - 9.5

Amp

DC Output 4 Amp +5V standby

DC Output

100 Amp @ 100-140V117 Amp @ 180-240V

With Power Distributor

Certification

+5V: 30 Amp • +3.3V: 25 Amp

Gold Certified [Test Report]

Regulatory (Power Supply) USA - UL listed, FCCCanada - CUL listed

Power

Europe/CE Mark

Supply
Safety / BMC

BN 60950/IEC 60950-Compliant
Germany - TUV Certified
CCC Certification

Standard Parts List			
	Part Number	Qty	Description
Chassis	CSE-818A-1400LPB	1	1U Chassis 818A
Air Shroud	MOP-310-81804-0B	1	Mylar Air Shroud for SC818A (X8QB6)
Backplane	BPN-SAS-818TQ	1	HDD backplane supports 3x SAS/SATA HDD
Cable(s)	CBL-0108L-02 CBL-0087 CBL-0154L CBL-0260L	1 1 1 1	IPASS TO IPASS 39cm Front ctrl cable round 16 to 16 pin ribbon 20" AC power cable for SO818, 36.5cm US power cord 18AWG 6ft, PBF (default for low watt)
Fan(s)	FAN-0101L4	7	40x56mm4-pin PWM Cooling Fans
Front Panel	MCP-280-81301-0N	1	Non-U front control board (FP813)
Hard Drive Carrier(s)	CSE-PT39-B0	3	SCA Type Assy Without Logo, Black
I/O Shield	MOP-260-81801-0N	1	1U I/O shield for SC818 (X8QB6)
Mounting Rails	MCP-290-00016-0N MCP-290-00042-0V	1 1	1U open rack bracket set for CSE-PT51L, MCP-290-00054-0N Rail set for SC808, 809, 818
Peripheral Drives/Covers	CSE-PT93L-B CSE-PT94L-B	1 1	Black DVD dummy cover Black FDD or USB tray dummy cover
Power Supply	PWS-1K41F-1R PDB-PT818-8824 MCP-250-00001-00	1 1 1	1400W 1U Gold Level Power Supply with PMBus and WX106MM Power Distributor Board BM filter for AC power cable
Rear Window	MCP-240-81807-0N MCP-240-81806-0N	1 1	Riser card bracket for SC818 Rear window for SC818

Optional Parts List				
	Part Number	Qty	Description	
Air Shroud	CSE-PT0128 MCP-310-81801-0B MCP-310-00017-01	-	Air shroud for SC318 (H8QM16DIMM) Mylar air shroud for SC318 (H8QM32DIMM) Mylar air shroud for SC318 (X7QC)	
Cable(s)	CBL-0078	-	Round Floppy Cable, 45cm	
Mounting Rails	MCP-290-00056-0N MCP-290-00052-0N-BULK	-	19" to 26.4" outer rail, /quick, for 1U 17.2" W chassis 25.6" to 33.05" outer rail, /quick, for 1U 17.2" W chassis (10 sets/pack)	
Peripheral Drives	FPD-TEAC-S(B) CSE-PT91L CSE-PT93L(-B) CSE-PT94L(-B)	- - -	TEAC 3.5" 1.44MB Slim Floppy Drive (B = black) Slim FDD kit DVD or CD dummy cover (B = black) FDD or USB tray dummy cover (B = black)	

Peripheral Drives	DVM-TEAC-824B DVM-TEAC-DVD-SBT2 DVM-PNSC-DVD-SBT2 MCP-220-81502-0N	- - -	Black slim IDE DVD (8x DVD, 24x CDR), TEAC Black slim SATA DVD (8x DVD, 24x CDR), TEAC Black slim SATA DVD (8x DVD, 24x CDR), Panasonic Slim SATA DVD kit (include backplane, cable)
Power Supply	CSE-PT0126	-	Power Distributor Cover For SC818 Chassis
Front Bezel (Compatibility Table)	CSE-PTFB-813(B) CSE-PTFB-813-02(B)		Front Bezel Cover with Horizontal Slits, Black (B) & Beige Front Bezel Cover with Round Venting Holes, Black (B) & Beige
LCD/OLED Solutions	-	-	Rease reference the LCD/OLED Display Solutions for details
Adaptor HDD carrier	MCP-220-00043-0N	-	Adaptor HDD carrier to install 2.5" HDD in 3.5" HDD tray

Terms & Conditions | Privacy | Investor Relations | Jobs | Site Map
:SuperServer® | Motherboard | Chassis | Rack Cabinet | SuperBlade® | Embedded | Networking | Storage | Accessories | AMD Solution | Power Supplies

Copyright © 2013 Super Mcro Computer, Inc.

Information in this document is subject to change without notice.
Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.