

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

CE

00

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D	ECO-12-015760	04SEP2012	JM	TE

25.9 MAX

502850-2, -4, -6

32.89 MAX

502850-1, -3, -5

15.49 MAX

1

MATL: TPE: UL94 V-0 RATED AT QUALIFYING THICKNESS, SEE DASH NUMBER FOR COLOR.

2

FITS STANDARD MIC RECEPTACLE, ALL KEYING TYPES.

OBSOLETE	PEARL	WITH MOUNTING STRAP	502850-6
OBSOLETE	WHITE	W/O MOUNTING STRAP	502850-5
OBSOLETE	BLACK	WITH MOUNTING STRAP	502850-4
OBSOLETE		W/O MOUNTING STRAP	502850-3
OBSOLETE	BEIGE	WITH MOUNTING STRAP	502850-2
OBSOLETE		W/O MOUNTING STRAP	502850-1
	COLOR	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

MATERIAL -

FINISH -

DWN - R.HILEMAN 6-26-96

CHK - F.ROVENOLT 7-9-96

APVD - F.ROVENOLT 7-9-96

PRODUCT SPEC - F.ABENDSCHEIN 7-9-96

APPLICATION SPEC -

WEIGHT -

STE

TE Connectivity

DUST COVER,
FIELD KEY RECEPTACLE

CUSTOMER DRAWING

SCALE 2:1

SHEET 1 OF 1

REV D

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-502850

-

1470-19

(3/11)