

TWO HOLE HYLUG™ CODE CONDUCTOR STANDARD BARREL (Continued)





Fig. 1




Fig. 2




Fig. 3

C-46

Catalog Number	Fig #	Conductor		Stud Hole Size	Stud Hole Spacing	Tongue Width	Figure Dimensions			▲ Installation Tooling							Wire Strip Length								
		AWG	*** MM²				Dieless (# of crimps)			Mechanical	Hydraulic		Color Code	Die Index											
							MD6, OUR840, MD7-34R	BCT500HS, Y500CTHS	Y35, Y39, Y750, Y46*, PAT750																
YA1CL-2TC38	1	-	-	3/8"	1	.68"	.88"	.10"	3.07"	MY29-3 (1) MY29-11 (1) MRC840 (1) Y644M (1)	W1CVT (1)	X1CRT-1 (1)	U1CRT (1)	Green	11	15/16"									
YA1CL-2TC38-45	2																2.96"								
YA1CL-2TC38-90	3																	2.17"							
YA25-2L	1	1/0 AWG	-	5/16"	7/8"	.75"	.88"	.12"	2.85"	MY29-3 (1) MY29-11 (1) MRC840 (2) Y644M (1)	W25VT (2) W25RT (2) X25RT (2)	W25VT (2) W25RT (2) X25RT (2)	U25RT (1) U2CABT (1)	Pink	12	15/16"									
YA25-2L-45	2																2.77"								
YA25-2L-90	3																	1.95"							
YA252LN	1																		4.29"						
YA252LN-45	2																			1/2"	1-3/4"	.83"	.88"	.11"	4.20"
YA252LN-90	3																								
YA25L-2TC14	1			2.64"																					
YA25L-2TC14-45	2				1/4"	5/8"	.75"	.88"	.12"								2.45"								
YA25L-2TC14-90	3																	1.58"							
YA25L-2TC14E1	1																		3.01"						
YA25L-2TC14E1-45	2																			1"	4	.75"	.88"	.12"	2.91"
YA25L-2TC14E1-90	3																								
YA25L-2TC14E2	1			2.66"																					
YA25L-2TC14E2-45	2				1/4"	3/4"	.75"	.88"	.12"								2.58"								
YA25L-2TC14E2-90	3																	1.70"							
YA25L-2TC38	1																		3.10"						
YA25L-2TC38-45	2																			3/8"	1	.75"	.88"	.12"	3.02"
YA25L-2TC38-90	3																								
YA26-2L	1			2.95"																					
YA26-2L-45	2				5/16"	7/8"	.83"	.94"	.12"								2.84"								
YA26-2L-90	3																	1.98"							
YA262LN	1																		4.39"						
YA262LN-45	2																			1/2"	1-3/4"	.83"	.94"	.12"	4.27"
YA262LN-90	3																								
YA26L-2TC14	1	2.64"																							
YA26L-2TC14-45	2		1/4"	5/8"	.83"	.94"	.12"	2.52"																	
YA26L-2TC14-90	3								1.66"																
YA26L-2TC14E1	1									3.01"															
YA26L-2TC14E1-45	2										1/4"	1	.83"	.94"	.12"	2.90"									
YA26L-2TC14E1-90	3																2.04"								
YA26L-2TC14E2	1	2.76"																							
YA26L-2TC14E2-45	2		1/4"	3/4"	.83"	.94"	.12"	2.65"																	
YA26L-2TC14E2-90	3								1.79"																
YA26L-2TC38	1									3.20"															
YA26L-2TC38-45	2										3/8"	1	.83"	.94"	.12"	3.09"									
YA26L-2TC38-90	3																2.22"								
YA272LN	1	4.48"																							
YA272LN-45	2		1/2"	1-3/4"	.91"	1.00"	.13"	4.35"																	
YA272LN-90	3								3.44"																
YA27L-2TC14E2	1									2.86"															
YA27L-2TC14E2-45	2										1/4"	3/4"	.91"	1.00"	.12"	2.73"									
YA27L-2TC14E2-90	3																1.81"								
YA27L-2TC38	1	3.30"																							
YA27L-2TC38-45	2		3/8"	1	.91"	1.00"	.12"	3.17"																	
YA27L-2TC38-90	3								2.25"																

-- Color code not assigned.

▲ See tooling section of this catalog for complete tool and die listings.

◆ For applications greater than 2000 volts consult cable manufacturer for voltage stress relief instructions.

* Use PUADP-1 adapter with "U" dies in Y46 HYPRESS™.

** P-RT die sets for use in Y46 HYPRESS™ only, PUADP-1 adapter not required.

*** The MM² conductor sizes listed are the recommendations for Class 2 conductor