

Setting Up the Evaluation Board for the ADCLK946

PACKAGE LIST

Evaluation board with ADCLK946 component installed

Applicable documents (schematic, layout)

GENERAL DESCRIPTION

This user guide describes how to set up and use the evaluation board for the [ADCLK946](#). The ADCLK946 data sheet should be used in conjunction with this user guide.

The data sheet contains full technical details about the specifications and operation of this device.

The ADCLK946 is a very high performance clock fanout buffer. The evaluation board is fabricated using a high quality Rogers dielectric material. Transmission line paths are kept as close to 50 Ω as possible.

DIGITAL PICTURE OF EVALUATION BOARD




Figure 1. ADCLK946 Evaluation Board

09668-101

TABLE OF CONTENTS

Package List	1	Recommended Board Setup	3
General Description	1	Clock Outputs.....	4
Digital Picture of Evaluation Board	1	Evaluation Board Schematic and Artwork.....	5
Revision History	2	ESD Caution.....	8
Evaluation Board Hardware.....	3		

REVISION HISTORY

11/09—Revision 0: Initial Version

EVALUATION BOARD HARDWARE

RECOMMENDED BOARD SETUP

The recommended setup for the ADCLK946 evaluation board is shown in Figure 2. V_{CC} is set to 3.3 V and V_{EE} is set to GND.

On the evaluation board, the clock input is set up for single-ended-to-differential operation via the balun. In addition, series capacitors in the path provide ac-coupled inputs to the ADCLK946. The common-mode voltage for both inputs is provided by tying V_{REF} and V_T together. This connection is made with R13 installed at the factory.

The range of the peak-to-peak input voltage swing at CLK is 0.2 V p-p to 1.7 V p-p. Note that output jitter performance is degraded by an input slew rate, as shown in the [ADCLK946](#) data sheet.

Table 1. Basic Equipment Required

Quantity	Description
1	Single power supply
1	Signal source
1	High bandwidth oscilloscope
4	Matched high speed cables




Figure 2. Recommended Setup for Device Evaluation

CLOCK OUTPUTS

The ADCLK946 has six differential outputs. All differential clock outputs on the evaluation board are biased to GND via 200 Ω and ac-coupled to the SMAs. From the SMAs, use matched 50 Ω coaxial cables into the oscilloscope for evaluation. See the evaluation board schematic in Figure 4 for more details.

Table 2. Power Connections via P1

Label	ADCLK946
GND	Connect to GND
VCC	Connect to 3.3 V
VEE	Connect to GND






Figure 3. ADCLK946 1:6 Clock/Data Buffer Block Diagram


08668-004






08668-005

Figure 5. Top Trace Layer




08668-006

Figure 6. Ground Plane Layer



08668-007

Figure 7. V_{CC} and V_{EE} Power Plane Layer

08668-008

Figure 8. Bottom Trace Layer

NOTES

ESD CAUTION

**ESD (electrostatic discharge) sensitive device.**

Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

Evaluation boards are only intended for device evaluation and not for production purposes. Evaluation boards are supplied “as is” and without warranties of any kind, express, implied, or statutory including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. No license is granted by implication or otherwise under any patents or other intellectual property by application or use of evaluation boards. Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Analog Devices reserves the right to change devices or specifications at any time without notice. Trademarks and registered trademarks are the property of their respective owners. Evaluation boards are not authorized to be used in life support devices or systems.