


BD533/535/537

Medium Power Linear and Switching Applications

- Low Saturation Voltage
- Complement to BD534, BD536 and BD538 respectively



1. Base 2. Collector 3. Emitter

NPN Epitaxial Silicon Transistor

Absolute Maximum Ratings $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage : BD533	45	V
	: BD535	60	V
	: BD537	80	V
V_{CES}	Collector-Emitter Voltage : BD533	45	V
	: BD535	60	V
	: BD537	80	V
V_{CEO}	Collector-Emitter Voltage : BD533	45	V
	: BD535	60	V
	: BD537	80	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current	8	A
I_B	Base Current	1	A
P_C	Collector Dissipation ($T_C=25^\circ\text{C}$)	50	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature	- 65 ~ 150	$^\circ\text{C}$

Electrical Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
I_{CBO}	Collector Cut-off Current : BD533	$V_{CB} = 45\text{V}$, $I_E = 0$			100	μA
	: BD535	$V_{CB} = 60\text{V}$, $I_E = 0$			100	μA
	: BD537	$V_{CB} = 80\text{V}$, $I_E = 0$			100	μA
I_{CES}	Collector Cut-off Current : BD533	$V_{CE} = 45\text{V}$, $V_{BE} = 0$			100	μA
	: BD535	$V_{CE} = 60\text{V}$, $V_{BE} = 0$			100	μA
	: BD537	$V_{CE} = 80\text{V}$, $V_{BE} = 0$			100	μA
I_{EBO}	Emitter Cut-off Current	$V_{EB} = 5\text{V}$, $I_C = 0$			1	mA
h_{FE}	* DC Current Gain : BD533/535	$V_{CE} = 5\text{V}$, $I_C = 10\text{mA}$	20			
	: BD537		15			
	: ALL DEVICE	$V_{CE} = 2\text{V}$, $I_C = 500\text{mA}$	40			
	: BD533/535	$V_{CE} = 2\text{V}$, $I_C = 2\text{A}$	25			
	: BD537		15			
h_{FE}	h_{FE} Groups J : ALL DEVICE	$V_{CE} = 2\text{V}$, $I_C = 2\text{A}$ $V_{CE} = 2\text{V}$, $I_C = 3\text{A}$	30		75	
	K : ALL DEVICE	$V_{CE} = 2\text{V}$, $I_C = 2\text{A}$ $V_{CE} = 2\text{V}$, $I_C = 3\text{A}$	40		100	
			20			
$V_{CE(\text{sat})}$	* Collector-Emitter Saturation Voltage	$I_C = 2\text{A}$, $I_B = 0.2\text{A}$ $I_C = 6\text{A}$, $I_B = 0.6\text{A}$		0.8	0.8	V
$V_{BE(\text{on})}$	* Base-Emitter ON Voltage	$V_{CE} = 2\text{V}$, $I_C = 2\text{A}$			1.5	V
f_T	Current Gain Bandwidth Product	$V_{CE} = 1\text{V}$, $I_C = 500\text{mA}$	3	12		MHz

* Pulse Test: $PW = 300\mu\text{s}$, duty Cycle = 1.5% Pulsed

Typical characteristics




Figure 1. DC current Gain




Figure 2. Collector-Emitter Saturation Voltage




Figure 3. Base-Emitter Saturation Voltage




Figure 4. Safe Operating Area





Figure 5. Power Derating

Package Demensions

TO-220



Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE TM	HiSeC TM	SuperSOT TM -8
Bottomless TM	ISOPLANAR TM	SyncFET TM
CoolFET TM	MICROWIRE TM	TinyLogic TM
CROSSVOLT TM	POP TM	UHC TM
E ² CMOS TM	PowerTrench [®]	VCX TM
FACT TM	QFET TM	
FACT Quiet Series TM	QS TM	
FAST [®]	Quiet Series TM	
FAST TM	SuperSOT TM -3	
GTO TM	SuperSOT TM -6	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.