



Specifications:

Conductor	: Bare copper, fine wire, IEC 228 class 5 VDE 0295
Insulation	: PVC compound
Screen	: Galvanized Steel wire screening
Inner jacket	: PVC compound
Outer sheath	: PVC compound
Nominal Voltage	: 300 / 500 V
Test voltage	: 4,000 V
Temperature range (static)	: -30 +70°C
Temperature range (flexing)	: -5 +70°C
Bending radius	: 15 × D
Flame Retardant	: IEC 332-1
Core colour	: Cores black with continuous white figure imprint earth conductor green / yellow

Specification Table

Description	Number of Cores x Cores Section (mm ²)	Outer Diameter (mm)	Part Number
Cable, CTRL, SY, 4 Core, 0.75mm, 50m	4 × 0.75	8.1	10985000-50M
Cable, CTRL, SY, 4 Core, 0.75mm, 100m			10985000-100M
Cable, CTRL, SY, 4 Core, 1mm, 50m	4 × 1	8.7	10998400-50M
Cable, CTRL, SY, 4 Core, 1mm, 100m			10998400-100M
Cable, CTRL, SY, 4 Core, 1.5mm, 50m	4 × 1.5	9.3	10979400-50M
Cable, CTRL, SY, 4 Core, 1.5mm, 100m			10979400-100M
Cable, CTRL, SY, 4 Core, 2.5mm, 50m	4 × 2.5	10.8	10998700-50M
Cable, CTRL, SY, 4 Core, 4mm, 50m	4 × 4	12.7	10994200-50M
Cable, CTRL, SY, 5 Core, 0.75mm, 50m	5 × 0.75	8.9	10988500-50M
Cable, CTRL, SY, 5 Core, 1mm, 50m	5 × 1	9.2	10997800-50M
Cable, CTRL, SY, 5 Core, 2.5mm, 50m	5 × 2.5	11.7	10997900-50M
Cable, CTRL, SY, 5 Core, 4mm, 50m	5 × 4	14.1	10999000-50M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2011.