



Straight Boot

As Supplied (a)



After Unrestricted Recovery (b)



Applications

Use for mechanical protection and connector/cable strain relief. This family of boots has no lip, so that a boot can be installed directly onto the connector accessory thread.

Materials Available

Material*	Material Description	Precoating No.	Adhesive Part No.**
-3	Semirigid polyolefin	/42 or /86	S-1017 or S-1048
-4	Flexible polyolefin	/42 or /86	S-1017 or S-1048
-12	Viton®	N/A	S-1255-04
-25	Fluid-resistant elastomer	/42 or /86 or /225	S-1017 or S-1048 or S-1125
-100	Polyolefin, Zerohal	/86 or /180	S-1048 or S-1030

*For more information, please see the appropriate material page in this section.

**For more information, please see section 5.

Product Dimensions

Part No.	H			J			P ±10% b	R ±10% b	JO Ref. b	W ±20% b
	Min.		Max. b	Min.		Max. b				
	-3, -4, -25 a	-12, -100 a		-3, -4, -25 a	-12, -100 a					
202A111	16.5 [65]	16.5 [65]	7.9 [31]	16.5 [65]	11.9 [47]	3.8 [15]	25.4 [1.00]	14.2 [56]	5.8 [23]	1.27 [05]
202A121	24.6 [97]	22.6 [89]	9.9 [39]	24.6 [97]	17.8 [70]	5.3 [21]	38.1 [1.50]	21.8 [86]	9.1 [36]	1.52 [06]
202A132	28.4 [1.12]	26.2 [1.03]	14.2 [56]	28.4 [1.12]	20.3 [80]	6.6 [26]	51.3 [2.02]	27.9 [1.10]	13.0 [51]	1.78 [07]
202A142	31.0 [1.22]	31.0 [1.22]	17.8 [70]	31.0 [1.22]	25.4 [1.00]	7.4 [29]	66.8 [2.63]	35.6 [1.40]	17.8 [70]	1.78 [07]
202A153	36.1 [1.42]	36.1 [1.42]	21.9 [86]	36.1 [1.42]	26.2 [1.03]	8.6 [34]	73.7 [2.90]	41.4 [1.63]	16.0 [63]	1.78 [07]
202A163	42.7 [1.68]	42.7 [1.68]	27.4 [1.08]	42.7 [1.68]	27.2 [1.07]	9.4 [37]	99.1 [3.90]	62.7 [2.47]	18.0 [71]	2.03 [08]
202A174	51.8 [2.04]	48.3 [1.90]	35.3 [1.39]	51.8 [2.04]	48.3 [1.90]	16.0 [63]	130.0 [5.13]	64.8 [2.55]	41.9 [1.65]	3.30 [13]
202A185	66.0 [2.60]	66.0 [2.60]	43.7 [1.72]	66.0 [2.60]	54.1 [2.13]	19.6 [77]	161.3 [6.35]	90.2 [3.55]	47.8 [1.88]	3.81 [15]
202A196	86.4 [3.40]	86.4 [3.40]	57.2 [2.25]	86.4 [3.40]	71.4 [2.81]	26.9 [1.06]	212.6 [8.37]	113.0 [4.45]	62.2 [2.45]	4.06 [16]

Note: Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by 1.5 [.06] max.

VITON is a trademark of DuPont
Performance Elastomers

Available in:	Americas	Europe	Asia Pacific
	■	■	■