



Home» Products > Linear and Rotary Potentiometric Sensors» AQLT > Product Page

AQLT06N06KFC



Actual product appearance may vary.

AQLT Series Shaftless Waterproof Linear Position Transducer, 152,4 mm [6.0 in] Electrical Travel, Item Number 9812201

Features

3/8 inch (AQMLT)and 1/2 inch (AQLT) body diameter - Fit in tight spaces and clamps easily to cylinders
Multiple finger wiper design - Improves shock and vibration performance
Extruded wiper block guides - Smooth quiet motion; extends operating life
MystR² plastic element- tested up to one billion operations
Anodized extruded aluminum housing- Tolerates clamping loads
Sealed construction - Full performance in hositle environments
Precious metal contact- Low noise level over entire life
Absolute continuous measurement- Accurate position at power up

Potential Applications

In-tank level sensing
Robotic motion control
Woodworking guides
Seismology
Packaging and processing equipment
Animated characters
Marine steering systems
Off-road vehicles
Semiconductor Process Equipment
Medical Equipment

Description

The AQ Series are shaftless waterproof linear potentiometers designed to operate in wet/washdown and in -tank environments.
The AQ series features an external actuator magnetically coupled to a position feedback element. The magnetic actuator replaces the shaft found in traditional linear transducers, which eliminates the need for additional stroke length mounting space and improves shock and vibration performance.
Precious metal dual wipers, MystR² proprietary conductive plastic, and anodized aluminum housings assure long life and reliable operation in numerous applications
Intrinsically safe for Class I, II and III Division I, Groups A, B, C, D, E, F and G for hazardous (indoor/outdoor) NEMA 4 locations. V max.=30 V, I max.=100 mA, Ci=0, Li.=0mH.

Supporting Documentation

- 📄 Dimensions
- 📄 Circuitry
- 📄 Actuator Dimensions

Product Specifications	
Supply Voltage	30 Vdc max.
Measurement Type	Linear
Housing Size	207,264 mm [8.16 in]
Total Mechanical Travel	154,94 mm [6.1 in]
Electrical Travel	152,4 mm [6.0 in]
Starting Force (max.)	56,7 g max. [2.0 oz max.]
Linearity	± 1.0 %
Type of Element	MystR [®] conductive plastic film
Housing Style	Anodized Aluminum
Termination	28 awg, 3 cond. - 3,048 m [10 ft] cable
Wiper Current	<1 μ A
Resolution	Infinite
Operating Temperature Range	- 40 °C to 80 °C [- 40 °F to 176 °F]
Vibration	20 g / 0,75 mm (rms) 5 hz to 2 khz
Shock	50 g 11 ms half sine
Operating Life	one billion dither operations
Total Resistance	6,000 Ohms
Resistance Tolerance	± 20 %
Insulation Resistance	500 MOhm @ 500 Vdc
Dielectric Strength	250 V rms
Sealing	Sealed Construction IP68
UNSPSC Code	41111945
UNSPSC Commodity	41111945 Linear position sensors
Availability	Global
Series Name	AQLT

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control▼

Product Search

Part number search:

Use (*) to expand search

Specification Search